

X-Plor KS520N

X-Plor 38L Black Plastic Top Case Instruction Manual

Model: KS520N | Brand: X-Plor

INTRODUCTION

This manual provides essential information for the safe and effective use of your X-Plor 38L Black Plastic Top Case. Designed for motorcycles, this top case offers secure storage for your belongings, including a modular or full-face helmet. Please read this manual thoroughly before installation and use to ensure proper function and longevity of the product.

The X-Plor top case is constructed from durable plastic, featuring a robust design and an internal lining for protection. It includes an aluminum mounting plate for convenient attachment to the rear of your motorcycle. The top case also provides external attachment points on its lid for securing additional items.

SAFETY INFORMATION

- **Maximum Load Capacity:** Do not exceed the recommended maximum load of **8 kg (17.6 lbs)**. Overloading can affect motorcycle stability and handling.
- **Secure Mounting:** Always ensure the top case is securely attached to the mounting plate and the mounting plate is firmly fixed to your motorcycle. Regularly check all fasteners for tightness, especially after long rides or rough terrain.
- **Weight Distribution:** Distribute weight evenly inside the top case. Heavy items should be placed at the bottom and centered.
- **Speed Limit:** Some users report recommendations to not exceed 120 km/h (75 mph) with the top case mounted. Always adhere to local traffic laws and adjust your speed according to road conditions and load.
- **Water Resistance:** While designed to protect contents, the top case may not be entirely waterproof under heavy rain or prolonged exposure. Consider using waterproof bags for sensitive items.
- **Maintenance:** Periodically inspect the top case for any signs of wear, damage, or loose components.

PACKAGE CONTENTS

Verify that all components are present before beginning installation:

- X-Plor 38L Black Plastic Top Case
- Aluminum Mounting Plate
- Internal Lining
- Fastening Straps (internal)

- Keys for Locking Mechanism
- Mounting Hardware (bolts, nuts, washers - typically included with mounting plate)

SETUP AND INSTALLATION

The X-Plor top case is designed for easy installation using the provided aluminum mounting plate. Specific motorcycle models may require additional adapter kits (not included) to fit the mounting plate.

1. Mounting the Plate to Your Motorcycle

1. Identify suitable mounting points on your motorcycle's rear rack.
2. Position the aluminum mounting plate ([view image](#)) on the rack, ensuring it is centered and stable.
3. Use the provided mounting hardware to securely fasten the plate to your motorcycle's rack. Tighten all bolts firmly, but do not overtighten.
4. Verify that the plate is stable and does not wobble.



Figure 1: The aluminum mounting plate, essential for securing the top case to your motorcycle's rear rack.

2. Attaching the Top Case to the Plate

1. Align the bottom of the top case with the mounting points on the aluminum plate. The top case features a specific base design for this purpose ([view image](#)).
2. Push the top case down firmly until it clicks into place, indicating a secure connection.
3. Verify the top case is locked onto the plate by gently attempting to lift it. It should not detach easily.



Figure 2: Underside of the X-Plor top case, showing the integrated base designed to interface with the aluminum mounting plate.

OPERATING INSTRUCTIONS

Opening and Closing the Top Case

To open the top case, insert the key into the lock mechanism ([view image](#)) and turn it to the unlock position. Press the release button or lever (if present) and lift the lid. To close, simply lower the lid until it latches securely. Ensure the lock is engaged by turning the key back to the locked position and removing it.



Figure 3: Detailed view of the robust locking mechanism on the X-Plor top case, ensuring secure closure.



Figure 4: The X-Plor top case with its lid fully open, revealing the spacious interior and internal lining.

Loading the Top Case

- The top case has a capacity of **38 liters**, sufficient for one modular or full-face helmet.
- Utilize the internal lining and fastening straps to secure items and prevent them from shifting during transit ([view image](#)).
- Do not exceed the maximum load capacity of **8 kg**.
- For additional storage, the top case lid features attachment points for securing external bags or items with bungee cords (not included).



Figure 5: Inside the X-Plor top case, showing the protective internal lining and the base design.

MAINTENANCE

- **Cleaning:** Clean the top case with a mild soap and water solution. Avoid abrasive cleaners or solvents that could damage the plastic finish. Wipe dry with a soft cloth.
- **Fastener Check:** Regularly inspect all mounting bolts and the top case attachment mechanism for tightness. Vibrations from riding can cause fasteners to loosen over time.
- **Seal Inspection:** Check the rubber seal around the lid for cracks or damage. A compromised seal can lead to water ingress.
- **Lubrication:** Periodically apply a small amount of silicone spray or light lubricant to the lock mechanism to ensure smooth operation.
- **Storage:** When not in use, store the top case in a cool, dry place away from direct sunlight to prevent material degradation.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Top case feels loose or wobbles on the mounting plate.	Mounting bolts are loose; top case not fully engaged with the plate.	Tighten all bolts securing the mounting plate to the motorcycle. Ensure the top case is pushed down firmly until it clicks into place. Regularly check tightness.
Water inside the top case after rain.	Lid seal is damaged or improperly seated; not fully closed.	Inspect the rubber seal around the lid for damage or debris. Ensure the lid is fully closed and the lock is engaged. Consider using waterproof inner bags for sensitive items.
Lock mechanism is stiff or difficult to operate.	Lack of lubrication; debris in the lock.	Apply a small amount of graphite powder or silicone spray to the lock cylinder. Avoid oil-based lubricants that can attract dirt.
Top case cannot be detached from the plate.	Release mechanism stuck or obstructed.	Ensure the lock is fully disengaged. Check for any debris obstructing the release mechanism. Apply light pressure while attempting to release.

SPECIFICATIONS

Feature	Detail
Brand	X-Plor
Model Number	KS520N
Capacity	38 Liters
Material	Plastic
Color	Black
Maximum Recommended Load	8 kg (17.6 lbs)
Item Weight	2.5 Kilograms (5.5 lbs)
Product Dimensions (Approx.)	1 x 1 x 1 cm (This dimension appears to be a placeholder or packaging dimension. Actual external dimensions for a 38L top case will be significantly larger.)
Vehicle Service Type	Motorcycle

WARRANTY AND SUPPORT

For information regarding warranty coverage, please refer to the documentation provided at the time of purchase or contact your retailer. X-Plor products are typically covered by a manufacturer's warranty against defects in materials and workmanship.

If you encounter any issues not covered in the troubleshooting section or require further assistance, please contact the seller from whom you purchased the product or visit the official X-Plor website for support contact information.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question