

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [VECELO](#) /

› [VECELO Twin Size Metal Daybed Frame with Headboard - Instruction Manual](#)

VECELO KHD-LT-T06-BC06

VECELO Twin Size Metal Daybed Frame with Headboard

Instruction Manual

1. INTRODUCTION

Thank you for choosing the VECELO Twin Size Metal Daybed Frame. This manual provides detailed instructions for assembly, usage, maintenance, and troubleshooting to ensure safe and proper operation of your new daybed. Please read all instructions carefully before assembly and retain this manual for future reference.

Safety Warnings

- Do not exceed the maximum weight capacity of 660 lbs.
- Exercise caution around sharp edges during assembly and use.
- Ensure all bolts and screws are securely tightened before use. Periodically check and re-tighten as necessary.
- Keep small parts away from children during assembly to prevent choking hazards.
- Assembly should ideally be performed by two adults.

2. PACKAGE CONTENTS

Before beginning assembly, verify that all parts and hardware are present. Refer to the diagrams below for identification.



Figure 2.1: Main components of the daybed frame. (Image from assembly video)



Figure 2.2: Hardware components for assembly. (Image from assembly video)

List of Components:

Part	Description	Quantity
A	Headboard Panel	1
B	Footboard Panel	1
C	Side Rail (Left)	1
D	Side Rail (Right)	1
E	Support Legs	4
F	Bed Slats	12

List of Hardware:

No.	Description	Quantity
1	M6*30mm Screws	8
2	M6*40mm Screws	8
3	M8*55mm Screws	20+2
4	M8*12*6mm Nuts	4
5	M6*10*5mm Nuts	8
6	M6*10*12mm Nuts	3
7	M8*1.5mm Washers	20+2
8	M8*1.5mm Washers	8
9	Allen Wrench (M4-22/62MM)	1
10	Wrench (10MM)	1
11	Wrench (12MM)	1

3. ASSEMBLY INSTRUCTIONS

Follow these steps carefully to assemble your VECELO Daybed Frame. It is recommended to have two people for assembly.

Step 1: Attach Headboard and Footboard Panels

Connect the Headboard Panel (A) and Footboard Panel (B) to the main frame posts using M6*60mm screws (part 2) and the Allen wrench (part 5). Ensure the decorative elements are facing outwards.



Figure 3.1: Attaching the headboard and footboard panels.

Step 2: Install Side Rails

Attach the Left Side Rail (C) and Right Side Rail (D) to the assembled headboard and footboard posts. Use M8*50mm screws (part 3), M8*12*6mm nuts (part 4), and M8*1.5mm washers (part 7). Secure tightly with the provided wrenches.



Figure 3.2: Connecting the side rails to the frame.

Step 3: Insert Bed Slats

Place the Bed Slats (F) into the designated U-shaped grooves on the side rails. Ensure each slat is firmly seated to provide stable mattress support. Some slats may require M6*60mm screws (part 2) for additional security.



Figure 3.3: Securing the bed slats.

Assembly Video Guide

Your browser does not support the video tag.

Video 3.1: Official VECELO assembly guide for the metal daybed frame. This video demonstrates the step-by-step process of putting together the daybed, including attaching the headboard, footboard, side rails, and slats.

4. USAGE GUIDELINES

The VECELO Twin Size Metal Daybed Frame is designed for versatile use in various rooms, functioning as a bed, sofa, or extra seating.

Mattress Compatibility

This daybed is designed for a standard twin-size mattress. No box spring is required due to the sturdy steel slat support system.

Weight Capacity

The frame has a maximum weight capacity of 660 lbs, ensuring robust support.

Under-bed Storage

The design provides 12.6 inches of clearance underneath the bed, offering ample space for storage containers, luggage, or other items.



Figure 4.1: Illustration of the 12.6-inch under-bed clearance for storage.

Product Overview Video

Your browser does not support the video tag.

Video 4.1: An overview of the VECELO Daybed Metal Bed Frame, highlighting its features and design. This video showcases the daybed in a room setting, demonstrating its aesthetic appeal and functionality.

5. MAINTENANCE

Proper maintenance will extend the life and appearance of your daybed frame.

- **Cleaning:** Wipe the metal frame with a soft, damp cloth. Avoid harsh chemicals or abrasive cleaners that could damage the finish.
- **Inspection:** Periodically check all bolts and connections to ensure they remain tight. Re-tighten any loose fasteners to maintain stability and prevent squeaking.

- **Movement:** When moving the daybed, lift it rather than dragging it to prevent damage to the frame or floor.

6. TROUBLESHOOTING

If you encounter any issues with your daybed frame, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Frame is wobbly or unstable.	Loose bolts or incorrect assembly.	Check all connections and tighten any loose bolts. Review assembly instructions to ensure all parts are correctly installed.
Squeaking noises.	Loose connections or friction between metal parts.	Tighten all bolts. Apply a small amount of lubricant (e.g., silicone spray) to points of friction if tightening does not resolve the issue.
Missing parts or hardware.	Packaging error.	Contact VECELO customer service with your product model number and a list of missing items.

7. SPECIFICATIONS

Feature	Detail
Brand	VECELO
Model Number	KHD-LT-T06-BC06
Size	Twin
Product Dimensions	77.8"L x 41.5"W x 39.8"H
Material	Metal (Heavy Duty Steel)
Color	Dark Black
Finish Type	Powder, Steel
Weight Capacity	Up to 660 lbs
Under-bed Clearance	12.6 Inches
Assembly Required	Yes
UPC	810110789227



Figure 7.1: Key dimensions of the daybed frame.

8. WARRANTY AND SUPPORT

For any questions, missing parts, or support needs, please contact VECELO customer service. Refer to your purchase documentation for specific warranty details.

You can visit the official VECELO Store for more information: [VECELO Store on Amazon](#)