

Crivit 89fef

Livarno Home Automatic Soft-Close Toilet Seat Instruction Manual

Model: 89fef

INTRODUCTION

Thank you for choosing the Livarno Home Automatic Soft-Close Toilet Seat. This manual provides essential information for the safe and efficient installation, operation, and maintenance of your new toilet seat. Please read these instructions carefully before use and retain them for future reference.

Product Features:

- Silent automatic soft-close system for quiet operation.
- Quick-release function (Easy-Click) allows for easy removal of the entire toilet seat for thorough cleaning.
- Compatible with all standard toilets.
- Maximum load capacity: 150 kg.
- Durable construction from plastic and stainless steel.

SAFETY INSTRUCTIONS

To ensure safe operation and prevent damage, please observe the following safety guidelines:

- Do not stand on the toilet seat or lid.
- Do not exceed the maximum load capacity of 150 kg.
- Keep children away from the soft-close mechanism to prevent pinching, although it is designed for safety.
- Use only mild cleaning agents. Abrasive cleaners can damage the surface.
- Ensure all fittings are securely tightened during installation to prevent movement.
- If any part is damaged, discontinue use and replace the affected component.

SETUP AND INSTALLATION

The Livarno Home toilet seat is designed for easy installation on most standard toilets. Follow these steps for proper setup:

1. **Prepare the Toilet:** Ensure the toilet bowl is clean and dry. Remove any old toilet seat and clean the mounting area thoroughly.
2. **Position the Hinges:** Place the two hinge posts into the mounting holes on the toilet bowl. Ensure the rubber gaskets are correctly seated under the hinge posts.
3. **Secure the Hinges:** From underneath the toilet bowl, thread the nuts onto the bolts of the hinge posts. Hand-tighten

them initially.

4. **Attach the Seat:** Align the quick-release mechanism on the underside of the toilet seat with the hinge posts. Press down firmly until you hear a "click," indicating the seat is securely locked onto the hinges.
5. **Adjust and Tighten:** With the seat attached, adjust its position on the toilet bowl to ensure it is centered and aligned. Once satisfied with the alignment, fully tighten the nuts from underneath the toilet bowl using an appropriate wrench. Do not overtighten.
6. **Test Soft-Close:** Gently push the lid down to test the soft-close function. It should close slowly and silently.



This image displays the Livarno Home Automatic Soft-Close Toilet Seat. On the left, the seat is shown with the lid partially open, revealing the white seat and the blue-patterned lid. On the right, the seat is shown with the lid closed, showcasing the full design of the lid, which features an underwater scene with a sea turtle. This illustrates the product's aesthetic and its two main positions, relevant for understanding installation and use.

OPERATING INSTRUCTIONS

Soft-Close Function:

The toilet seat is equipped with an integrated soft-close mechanism. To activate, simply push the lid or seat down gently. The mechanism will take over, allowing the lid and seat to close slowly and silently without slamming. Do not force the lid or seat down, as this can damage the soft-close mechanism.

Quick-Release (Easy-Click) Function:

For easy cleaning, the entire toilet seat can be quickly removed. Locate the two quick-release buttons or levers near the hinges on the underside of the seat. Press or lift these mechanisms simultaneously, then lift the seat straight up from the hinge posts. To reattach, align the seat with the hinge posts and press down until it clicks securely into place.

Maintenance and Cleaning

Regular cleaning will help maintain the appearance and longevity of your toilet seat. Use the quick-release function for thorough cleaning.

- Daily Cleaning:** Wipe the seat and lid with a soft cloth dampened with water and a mild, non-abrasive soap.
- Deep Cleaning:** Use the quick-release function to remove the seat. Clean the seat, lid, and hinge areas with a mild bathroom cleaner. Rinse thoroughly with water and dry with a soft cloth.
- Avoid:** Do not use abrasive cleaners, scouring pads, strong acids, alkalies, or organic solvents (e.g., alcohol, acetone) as these can damage the plastic and stainless steel surfaces.
- Hinge Care:** Periodically check the hinge connections for tightness. If they become loose, re-tighten the nuts underneath the toilet bowl.

Troubleshooting

Problem	Possible Cause	Solution
Seat is loose or wobbly.	Mounting nuts are not tight enough.	Tighten the mounting nuts underneath the toilet bowl.
Soft-close function not working or closing too fast.	Mechanism is damaged or obstructed.	Ensure no debris is obstructing the hinges. If damaged, the mechanism may need replacement.
Seat difficult to remove/attach with quick-release.	Buttons/levers not pressed correctly or mechanism is dirty.	Ensure both quick-release buttons/levers are fully engaged. Clean around the quick-release mechanism.

Specifications

Feature	Detail
Brand	Crivit
Model Number	89fef
Product Dimensions (L x W x H)	45 x 38 x 2.51 cm (17.7 x 15 x 1 inch)
Material	Plastic, Stainless Steel
Color	Blue (design)
Style	Modern
Shape	Oval
Operation Mode	Automatic (soft-close)
Maximum Load Capacity	150 kg (330 lbs)
Components Included	Toilet Seat

Warranty and Support

Information regarding spare parts availability is currently unavailable. For any product-related inquiries or support, please refer to your point of purchase or the manufacturer's official website.

© 2023 Crivit. All rights reserved.