

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Monzana](#) /

› [MONZANA Pipe Cleaning Hose Kit - 30m, 200 Bar Instruction Manual](#)

Monzana Pipe Cleaning Hose 30m

MONZANA Pipe Cleaning Hose Kit Instruction Manual

Model: Pipe Cleaning Hose 30m

Brand: Monzana

INTRODUCTION

This manual provides comprehensive instructions for the safe and effective use of your MONZANA Pipe Cleaning Hose Kit. This high-quality 5-piece kit is designed to reliably clear clogged drains and pipes in bathrooms, kitchens, cellars, and outdoor areas such as gutters and sewers. Please read these instructions carefully before initial use and retain them for future reference.

The kit includes a 30-meter PVC hose, two premium nozzles, and three adapters with brass threads, ensuring compatibility with standard high-pressure cleaners. It is built for durability and high-pressure performance, capable of handling up to 200 bar working pressure and a maximum of 500 bar.

SETUP INSTRUCTIONS

Before connecting the pipe cleaning hose, ensure your high-pressure cleaner is turned off and disconnected from the power supply. Wear appropriate personal protective equipment, including safety glasses and gloves.

- Identify Components:** Unpack all components of the 5-piece kit. You should have the 30-meter PVC hose, three adapters, two nozzles (one standard, one rotating), and a roll of Teflon tape.
- Select the Correct Adapter:** Choose the adapter that matches the connection type of your high-pressure cleaner. The kit includes three different brass-threaded adapters for broad compatibility.
- Apply Teflon Tape:** Wrap the threads of the chosen adapter with the provided Teflon tape to ensure a watertight seal.
- Connect Adapter to Pressure Washer:** Securely screw the selected adapter onto the high-pressure cleaner's spray gun or hose outlet. Ensure it is tightened firmly by hand, then use a wrench if necessary, but do not overtighten.
- Attach Nozzle to Hose:** Select either the standard nozzle (0.35 mm) or the rotating nozzle (0.45 mm) based on the type of blockage. Apply Teflon tape to the nozzle threads and securely screw it onto the end of the pipe cleaning hose. The hose features anti-kink protection at the connection point for durability.
- Connect Hose to Adapter:** Connect the pipe cleaning hose (with the attached nozzle) to the adapter on your high-pressure cleaner. Ensure all connections are secure before proceeding.



Image: Overview of the MONZANA 5-piece pipe cleaning kit, showing the 30m hose, three adapters, two nozzles, and Teflon tape.

OPERATING INSTRUCTIONS

Always ensure the hose is fully uncoiled before use to prevent kinks and damage. Never operate the high-pressure cleaner without water supply. Keep hands and face clear of the nozzle when the system is pressurized.

- 1. Insert the Hose:** Carefully feed the nozzle end of the pipe cleaning hose into the clogged drain or pipe. Push it as far as possible by hand until resistance is met.
- 2. Activate Pressure Washer:** Turn on your high-pressure cleaner. Slowly activate the trigger on the spray gun to allow water to flow through the hose and nozzle. The backward-facing jets on the nozzles will propel the hose further into the pipe.
- 3. Monitor Progress:** Guide the hose into the pipe, allowing the water pressure to clear the blockage. The red marking ring on the hose helps you monitor the cleaning process and how much hose has entered the pipe.
- 4. Nozzle Functionality:**
 - The **standard nozzle** (0.35 mm) features powerful front and rear jets to break up and flush away blockages.
 - The **rotating nozzle** (0.45 mm) provides a rotating action with its rear jets, effectively tackling stubborn obstructions.

5. **Retract the Hose:** Once the blockage is cleared, slowly retract the hose from the pipe while maintaining water flow. This helps to flush out any remaining debris.
6. **Deactivate Pressure Washer:** Turn off the high-pressure cleaner and release any remaining pressure by briefly activating the spray gun trigger. Disconnect the hose from the pressure washer.

BEFREIT ZUVERLÄSSIG VERSTOPFTE ABFLÜSSE IN...



BAD



KÜCHE UND KELLER



AUSSENBEREICHEN

Auch verschmutzte
**Regenrinnen und
Abwasserkanäle** im
Freien können schnell
und professionell
gesäubert werden.

Image: The pipe cleaning hose effectively clearing a clogged toilet drain.



Image: Detailed view of the two premium nozzles, highlighting their design for effective blockage removal.

MAINTENANCE

Proper maintenance ensures the longevity and optimal performance of your pipe cleaning hose kit.

- **Cleaning:** After each use, thoroughly rinse the hose and nozzles with clean water to remove any debris or residue.
- **Inspection:** Regularly inspect the hose for any signs of wear, cuts, or damage. Check the nozzles for blockages or damage to the jets. Inspect the adapters for thread wear.
- **Storage:** Coil the hose neatly and store all components in the provided practical storage and transport bag. Store in a dry, cool place, away from direct sunlight and extreme temperatures.
- **Teflon Tape:** Replace Teflon tape on connections as needed to maintain a secure, leak-free seal.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Low or no pressure from the nozzle.	<ul style="list-style-type: none"> • Insufficient water supply to the pressure washer. • Nozzle partially or fully blocked. • Loose connections causing leaks. • Pressure washer not operating at full capacity. 	<ul style="list-style-type: none"> • Ensure adequate water supply to the pressure washer. • Clean the nozzle jets using a thin wire or needle. • Check all connections (hose to adapter, adapter to pressure washer) and re-seal with Teflon tape if necessary. • Refer to your pressure washer's manual for troubleshooting pressure issues.
Hose not advancing into the pipe.	<ul style="list-style-type: none"> • Severe or solid blockage. • Incorrect nozzle type for the blockage. • Insufficient pressure. 	<ul style="list-style-type: none"> • Try using the rotating nozzle for stubborn blockages. • Increase pressure if your pressure washer allows. • Gently push and pull the hose to help it navigate the blockage. Do not force it. • Consider professional help for extremely stubborn blockages.
Hose getting stuck when retracting.	<ul style="list-style-type: none"> • Nozzle catching on pipe irregularities or broken sections. • Debris accumulating around the nozzle. 	<ul style="list-style-type: none"> • Slowly and gently pull the hose, rotating it slightly if possible. • Maintain water flow while retracting to help clear debris. • Avoid excessive force to prevent damage to the hose or pipe.

SPECIFICATIONS

Feature	Detail
Model	Pipe Cleaning Hose 30m
Brand	Monzana
Hose Length	30 meters
Working Pressure	Up to 200 bar
Maximum Pressure	500 bar
Material	PVC (Polychlorure de vinyle) with reinforced polyethylene inner tube and polyester braiding
Nozzle Sizes	Standard Nozzle: 0.35 mm, Rotating Nozzle: 0.45 mm
Color	Black
Product Dimensions (L x W x H)	3000 x 1.1 x 1.1 cm (Hose)
Weight	3.44 kilograms



Image: Visual representation of the hose's pressure capabilities and compatibility with pressure washers.

WARRANTY INFORMATION

Specific warranty details for the MONZANA Pipe Cleaning Hose Kit are typically provided at the point of purchase or within the product packaging. Please refer to your sales receipt, product documentation, or the seller's terms and conditions for information regarding warranty coverage, duration, and claims process.

CUSTOMER SUPPORT

For technical assistance, questions regarding product operation, or in case of defects, please contact the seller or manufacturer directly. Contact information can usually be found on your purchase invoice, the product packaging, or the official Monzana website. When contacting support, please have your product model (Pipe Cleaning Hose 30m) and purchase details readily available.

