

Nora NMP2-LED

Nora NMP2-LED30B Josh LED Puck Light User Manual

Model: NMP2-LED

1. INTRODUCTION

The Nora NMP2-LED30B Josh LED Puck Light is a versatile, low-profile lighting solution designed for accent, under-cabinet, in-cabinet, niche, and jewelry case applications. Its slim design allows for installation in limited spaces, providing excellent and even illumination without producing a diode image. This fixture can be either recessed or surface mounted and is dimmable with a compatible dimmable power supply. It features LED technology that eliminates forward heat, UV, and infrared rays, making it safe for heat-sensitive items.

Key Features:

- Compact design: 0.57 inches deep with a 2.72-inch diameter.
- Flexible installation: Recessed or Surface Mount options.
- Dimmable with appropriate power supply.
- Instant illumination: No flicker, delay, or warm-up time.
- No diode image, UV, or infrared wavelengths.
- cULus Listed for safety.

2. SAFETY INFORMATION

Please read all instructions carefully before installation and use. Retain this manual for future reference.

- **Electrical Safety:** Installation should be performed by a qualified electrician or a person familiar with the construction and operation of the product and the hazards involved. Disconnect power at the fuse or circuit breaker before installation or servicing.
- **Voltage:** This product operates on 24V DC. Ensure you use a compatible 24V DC power supply (sold separately). Connecting to an incorrect voltage will damage the unit and void the warranty.
- **Environment:** For indoor use only. Do not expose to water or excessive moisture.
- **Heat:** Do not cover the fixture with materials that may restrict airflow, as this can lead to overheating.
- **Modifications:** Do not attempt to modify or disassemble the fixture. This will void the warranty and may pose a safety risk.

3. PACKAGE CONTENTS

Verify that all components are present before beginning installation:

- 1 x Josh LED Puck Light
- 1 x 72-inch wire with connector

Note: A 24V DC power supply and dimmer (if dimming functionality is desired) are required and sold separately.

4. SETUP AND INSTALLATION

The Josh LED Puck Light can be installed as either a recessed or surface-mounted fixture. Choose the method that best suits your application.

4.1. Installation Overview



Figure 1: Front view of the Nora Josh LED Puck Light, showcasing its black finish and diffused light surface.



Figure 2: Top-down view of the Nora Josh LED Puck Light, highlighting its circular design and even light distribution.

4.2. Dimensions and Mounting Options




Figure 3: Detailed dimensional drawing illustrating the specifications for both recessed and surface mounting options. The recessed mount requires a 2.5-inch cutout (without mounting bracket) or 2.74-inch (with mounting bracket) and has a depth of 0.06 inches. The surface mount has a depth of 0.57 inches and a diameter of 2.72 inches.

4.3. Recessed Mount Installation

1. **Prepare the Surface:** Ensure the mounting surface is clean and free of obstructions.

2. **Cutout:** Based on Figure 3, create a circular cutout in the desired location. For recessed mounting, the cutout diameter is approximately 2.5 inches (without mounting bracket) or 2.74 inches (with mounting bracket).
3. **Wiring:** Route the 72-inch wire from the puck light through the cutout. Connect the wire to a compatible 24V DC power supply (not included). Ensure polarity is correct.
4. **Insert Fixture:** Gently push the puck light into the cutout until it sits flush with the surface. The spring clips (if present) will secure it.

4.4. Surface Mount Installation

1. **Prepare the Surface:** Ensure the mounting surface is clean and free of obstructions.
2. **Mark Mounting Points:** Use the puck light as a template to mark the screw locations for the mounting bracket (if included) or directly for the fixture.
3. **Secure Mounting Bracket (if applicable):** Attach the mounting bracket to the surface using appropriate screws (not included).
4. **Wiring:** Route the 72-inch wire from the puck light to the location of the 24V DC power supply (not included). Connect the wire, ensuring correct polarity.
5. **Attach Fixture:** Secure the puck light to the mounting bracket or directly to the surface using screws.

5. OPERATING INSTRUCTIONS

Once installed and connected to a compatible 24V DC power supply, the Nora Josh LED Puck Light is ready for operation.

- **Power On/Off:** The light will turn on when power is supplied from the 24V DC power source. Use the switch on your power supply or a connected wall switch to control power.
- **Dimming:** If connected to a dimmable 24V DC power supply and a compatible dimmer switch (e.g., remote control or app-controlled dimmer), you can adjust the brightness of the puck light. Follow the instructions provided with your specific dimmer and power supply for operation.

6. MAINTENANCE

The Nora Josh LED Puck Light requires minimal maintenance.

- **Cleaning:** Ensure the power is off before cleaning. Wipe the fixture with a soft, dry, or slightly damp cloth. Do not use abrasive cleaners, solvents, or harsh chemicals, as these can damage the finish or electrical components.
- **Bulb Replacement:** The LED light source is integrated and not user-replaceable. The average lifespan of the LEDs is 50,000 hours.

7. TROUBLESHOOTING

If you encounter issues with your Nora Josh LED Puck Light, refer to the following common problems and solutions:

Problem	Possible Cause	Solution

Problem	Possible Cause	Solution
Light does not turn on.	No power supply; incorrect wiring; faulty power supply.	Check if the 24V DC power supply is connected and receiving power. Verify all wiring connections are secure and correct polarity is observed. Test the power supply with another device if possible.
Light flickers or dims unexpectedly.	Incompatible dimmer; unstable power supply; loose connection.	Ensure your dimmer is compatible with 24V DC LED lighting. Check for stable power from the supply. Inspect all wiring for loose connections.
Light is not as bright as expected.	Dimmer setting too low; insufficient power supply wattage.	Adjust the dimmer to maximum brightness. Ensure your 24V DC power supply has sufficient wattage for all connected puck lights.
Fixture feels hot to the touch.	Restricted airflow; incorrect voltage.	Ensure the fixture is not covered and has adequate ventilation. Verify the power supply is 24V DC. Discontinue use if overheating persists.

8. SPECIFICATIONS



Brand	Nora (Generic)
Model Name	Josh LED Puck
Part Number	NMP2-LED30B
Light Source Type	LED
Voltage	24 Volts (DC)
Wattage	3.5 watts
Brightness	302 Lumens
Efficiency	85.71 lm/W
Color Temperature	3000 Kelvin (available in 2700K, 3000K, 3500K, 4000K)
Color Rendering Index (CRI)	90.00
Average Life	50,000 Hours
Material	Aluminum
Finish Type	Black (available in Bronze, Brushed Nickel, White)
Product Dimensions	2.72" L x 1.63" W x 0.57" H
Item Weight	8 ounces
Installation Type	Recessed or Flush Mount
Special Feature	Dimmable

Indoor/Outdoor Usage	Indoor
Certification	cULus Listed

9. WARRANTY AND SUPPORT

For warranty information or technical support, please contact the manufacturer or your point of purchase. Keep your purchase receipt as proof of purchase.

Related Documents - NMP2-LED

	<p>NORA in Bloom: 44th Annual Dinner & Auction Gala - Sponsorship and Support Opportunities</p> <p>Discover how to support survivors of sexual assault, domestic violence, and child abuse by sponsoring the NORA in Bloom 44th Annual Dinner & Auction Gala. Explore sponsorship levels, advertising options, and donation impacts.</p>
	<p>u-blox NORA-B2 Series Bluetooth Low Energy Modules System Integration Manual</p> <p>This system integration manual for u-blox NORA-B2 series Bluetooth Low Energy modules provides comprehensive guidance on hardware design-in, software integration, component handling, regulatory compliance, and testing for engineers.</p>
	<p>CB07 Puck Light Installation Guide Abba Lighting USA</p> <p>Detailed installation guide for the Abba Lighting CB07 Puck Light. Learn about product features, specifications, safety, and step-by-step installation for this versatile LED cabinet light.</p>
	<p>Aura Light Safie MP LED Downlight Installation Manual & Specifications</p> <p>Comprehensive installation manual and technical specifications for the Aura Light Safie MP LED downlight. Includes safety instructions, dimensions, IP ratings, and dimming compatibility.</p>

Documents - Nora – NMP2-LED

[\[pdf\]](#) Specifications Accessories Catalog

Specification Sheet Nora Lighting NMP2 LED40B Josh 24 2 75 inch Black LED Puck Light in 4000K
nmp2 led spec lightingnewyork on demandware static Sites master catalog lny default dwd00dd0e4 brand
nra assets specsheets |||

NMP2-LED 24V Josh LED Puck Light Source: 3.5W LED 300lm Type Project Catalog
No. Notes PRODUCT DESCRIPTION Josh, a slim light disk LED system for accent,
under cabinet, in-cabinet, niche, and jewelry cases, and other applications with
limited space. These low-profile fixtures can be spaced together...

lang:en score:31 filesize: 749.5 K page_count: 4 document date: 2024-10-21

[\[pdf\]](#) Installation Guide Instructions Catalog

Install Sheet Nora Lighting NMP2 LED27W Josh 24 2 75 inch White Under Cabinet in 2700K is nmp2 led lightingnewyork on demandware static Sites master catalog lny default dw7857e903 brand nra assets install |||

Installation Instructions **NMP2-LED** 24VDC Josh LED Puck Light READ PRIOR TO ATTEMPTING INSTALLATION ALWAYS TURN OFF MAIN POWER BEFORE INSTALLATION INSTALLATION SHOULD BE CARRIED OUT BY YOUR LOCAL ELECTRICIAN IMPORTANT - This equipment is intended to be installed only by qualified personnel. The ins...

lang:en score:30 filesize: 206.25 K page_count: 1 document date: 2022-11-23

[\[pdf\]](#) Accessories Catalog

opens in a new window NMP2 LED35BZ Nora Lighting LED Puck Light EverLights spec nora lighting 2023
03 ||| ||| NMP2-LED 24V Josh LED Puck Light Source: 3.5W LED 300lm Type Project Catalog No. Notes
PRODUCT DESCRIPTION Josh, a slim light disk LED system for accent, under cabinet, in-cabinet, niche, and jewelry cases, and other applications with limi

NMP2-LED 24V Josh LED Puck Light Source: 3.5W LED 300lm Type Project Catalog
No. Notes **PRODUCT DESCRIPTION** Josh, a slim light disk LED system for accent,
under cabinet, in-cabinet, niche, and jewelry cases, and other applications with
limited space. These low-profile fixtures can be spaced together...

lang:en score:29 filesize: 2.16 M page_count: 4 document date: 2023-04-13

MP3-60W/24 / MP3-60W/24	
24V Constant Voltage Class 2 Dimmable Driver (Phase, 0-10V & PWM dimming)	
Source:	0-10V / PWM / DALI
Output:	0-10V / PWM / DALI
PRODUCT DESCRIPTION	
MP3-60W/24 is a 24V Class 2 dimmable driver for all MP3 series lamps. Compatible with the LUX, LUMINA, and LUMINA PRO series. MP3-60W/24 is a compact driver with a built-in power factor correction.	
FEATURES	
• Constant Voltage Class 2 dimmable driver	
• 0-10V dimming	
• PWM dimming	
• DALI dimming	
• 0-100% dimming range	
• 0.9 PF (Power Factor)	
• 0.05% THD (Total Harmonic Distortion)	
• 100% THD (Total Harmonic Distortion)	
• Protection against short circuit and temperature protection	
OPERATING DATA & FEATURES	
• Input Voltage: 100-240V AC, 50-60Hz	
• Input Current: 0.2A	
• MP3-24: 24V 60W	
• MP3-24: 24V 120W	
• MP3-24: 24V 180W	
• MP3-24: 24V 240W	
• MP3-24: 24V 300W	
• MP3-24: 24V 360W	
• MP3-24: 24V 420W	
• MP3-24: 24V 480W	
• MP3-24: 24V 540W	
• MP3-24: 24V 600W	
• MP3-24: 24V 660W	
• MP3-24: 24V 720W	
• MP3-24: 24V 780W	
• MP3-24: 24V 840W	
• MP3-24: 24V 900W	
• MP3-24: 24V 960W	
• MP3-24: 24V 1020W	
• MP3-24: 24V 1080W	
• MP3-24: 24V 1140W	
• MP3-24: 24V 1200W	
• MP3-24: 24V 1260W	
• MP3-24: 24V 1320W	
• MP3-24: 24V 1380W	
• MP3-24: 24V 1440W	
• MP3-24: 24V 1500W	
• MP3-24: 24V 1560W	
• MP3-24: 24V 1620W	
• MP3-24: 24V 1680W	
• MP3-24: 24V 1740W	
• MP3-24: 24V 1800W	
• MP3-24: 24V 1860W	
• MP3-24: 24V 1920W	
• MP3-24: 24V 1980W	
• MP3-24: 24V 2040W	
• MP3-24: 24V 2100W	
• MP3-24: 24V 2160W	
• MP3-24: 24V 2220W	
• MP3-24: 24V 2280W	
• MP3-24: 24V 2340W	
• MP3-24: 24V 2400W	
• MP3-24: 24V 2460W	
• MP3-24: 24V 2520W	
• MP3-24: 24V 2580W	
• MP3-24: 24V 2640W	
• MP3-24: 24V 2700W	
• MP3-24: 24V 2760W	
• MP3-24: 24V 2820W	
• MP3-24: 24V 2880W	
• MP3-24: 24V 2940W	
• MP3-24: 24V 3000W	
• MP3-24: 24V 3060W	
• MP3-24: 24V 3120W	
• MP3-24: 24V 3180W	
• MP3-24: 24V 3240W	
• MP3-24: 24V 3300W	
• MP3-24: 24V 3360W	
• MP3-24: 24V 3420W	
• MP3-24: 24V 3480W	
• MP3-24: 24V 3540W	
• MP3-24: 24V 3600W	
• MP3-24: 24V 3660W	
• MP3-24: 24V 3720W	
• MP3-24: 24V 3780W	
• MP3-24: 24V 3840W	
• MP3-24: 24V 3900W	
• MP3-24: 24V 3960W	
• MP3-24: 24V 4020W	
• MP3-24: 24V 4080W	
• MP3-24: 24V 4140W	
• MP3-24: 24V 4200W	
• MP3-24: 24V 4260W	
• MP3-24: 24V 4320W	
• MP3-24: 24V 4380W	
• MP3-24: 24V 4440W	
• MP3-24: 24V 4500W	
• MP3-24: 24V 4560W	
• MP3-24: 24V 4620W	
• MP3-24: 24V 4680W	
• MP3-24: 24V 4740W	
• MP3-24: 24V 4800W	
• MP3-24: 24V 4860W	
• MP3-24: 24V 4920W	
• MP3-24: 24V 4980W	
• MP3-24: 24V 5040W	
• MP3-24: 24V 5100W	
• MP3-24: 24V 5160W	
• MP3-24: 24V 5220W	
• MP3-24: 24V 5280W	
• MP3-24: 24V 5340W	
• MP3-24: 24V 5400W	
• MP3-24: 24V 5460W	
• MP3-24: 24V 5520W	
• MP3-24: 24V 5580W	
• MP3-24: 24V 5640W	
• MP3-24: 24V 5700W	
• MP3-24: 24V 5760W	
• MP3-24: 24V 5820W	
• MP3-24: 24V 5880W	
• MP3-24: 24V 5940W	
• MP3-24: 24V 6000W	
• MP3-24: 24V 6060W	
• MP3-24: 24V 6120W	
• MP3-24: 24V 6180W	
• MP3-24: 24V 6240W	
• MP3-24: 24V 6300W	
• MP3-24: 24V 6360W	
• MP3-24: 24V 6420W	
• MP3-24: 24V 6480W	
• MP3-24: 24V 6540W	
• MP3-24: 24V 6600W	
• MP3-24: 24V 6660W	
• MP3-24: 24V 6720W	
• MP3-24: 24V 6780W	
• MP3-24: 24V 6840W	
• MP3-24: 24V 6900W	
• MP3-24: 24V 6960W	
• MP3-24: 24V 7020W	
• MP3-24: 24V 7080W	
• MP3-24: 24V 7140W	
• MP3-24: 24V 7200W	
• MP3-24: 24V 7260W	
• MP3-24: 24V 7320W	
• MP3-24: 24V 7380W	
• MP3-24: 24V 7440W	
• MP3-24: 24V 7500W	
• MP3-24: 24V 7560W	
• MP3-24: 24V 7620W	
• MP3-24: 24V 7680W	
• MP3-24: 24V 7740W	
• MP3-24: 24V 7800W	
• MP3-24: 24V 7860W	
• MP3-24: 24V 7920W	
• MP3-24: 24V 7980W	
• MP3-24: 24V 8040W	
• MP3-24: 24V 8100W	
• MP3-24: 24V 8160W	
• MP3-24: 24V 8220W	
• MP3-24: 24V 8280W	
• MP3-24: 24V 8340W	
• MP3-24: 24V 8400W	
• MP3-24: 24V 8460W	
• MP3-24: 24V 8520W	
• MP3-24: 24V 8580W	
• MP3-24: 24V 8640W	
• MP3-24: 24V 8700W	
• MP3-24: 24V 8760W	
• MP3-24: 24V 8820W	
• MP3-24: 24V 8880W	
• MP3-24: 24V 8940W	
• MP3-24: 24V 9000W	
• MP3-24: 24V 9060W	
• MP3-24: 24V 9120W	
• MP3-24: 24V 9180W	
• MP3-24: 24V 9240W	
• MP3-24: 24V 9300W	
• MP3-24: 24V 9360W	
• MP3-24: 24V 9420W	
• MP3-24: 24V 9480W	
• MP3-24: 24V 9540W	
• MP3-24: 24V 9600W	
• MP3-24: 24V 9660W	
• MP3-24: 24V 9720W	
• MP3-24: 24V 9780W	
• MP3-24: 24V 9840W	
• MP3-24: 24V 9900W	
• MP3-24: 24V 9960W	
• MP3-24: 24V 10020W	
• MP3-24: 24V 10080W	
• MP3-24: 24V 10140W	
• MP3-24: 24V 10200W	
• MP3-24: 24V 10260W	
• MP3-24: 24V 10320W	
• MP3-24: 24V 10380W	
• MP3-24: 24V 10440W	
• MP3-24: 24V 10500W	
• MP3-24: 24V 10560W	
• MP3-24: 24V 10620W	
• MP3-24: 24V 10680W	
• MP3-24: 24V 10740W	
• MP3-24: 24V 10800W	
• MP3-24: 24V 10860W	
• MP3-24: 24V 10920W	
• MP3-24: 24V 10980W	
• MP3-24: 24V 11040W	
• MP3-24: 24V 11100W	
• MP3-24: 24V 11160W	
• MP3-24: 24V 11220W	
• MP3-24: 24V 11280W	
• MP3-24: 24V 11340W	
• MP3-24: 24V 11400W	
• MP3-24: 24V 11460W	
• MP3-24: 24V 11520W	
• MP3-24: 24V 11580W	
• MP3-24: 24V 11640W	
• MP3-24: 24V 11700W	
• MP3-24: 24V 11760W	
• MP3-24: 24V 11820W	
• MP3-24: 24V 11880W	
• MP3-24: 24V 11940W	
• MP3-24: 24V 12000W	
• MP3-24: 24V 12060W	
• MP3-24: 24V 12120W	
• MP3-24: 24V 12180W	
• MP3-24: 24V 12240W	
• MP3-24: 24V 12300W	
• MP3-24: 24V 12360W	
• MP3-24: 24V 12420W	
• MP3-24: 24V 12480W	
• MP3-24: 24V 12540W	
• MP3-24: 24V 12600W	
• MP3-24: 24V 12660W	
• MP3-24: 24V 12720W	
• MP3-24: 24V 12780W	
• MP3-24: 24V 12840W	
• MP3-24: 24V 12900W	
• MP3-24: 24V 12960W	
• MP3-24: 24V 13020W	
• MP3-24: 24V 13080W	
• MP3-24: 24V 13140W	
• MP3-24: 24V 13200W	
• MP3-24: 24V 13260W	
• MP3-24: 24V 13320W	
• MP3-24: 24V 13380W	
• MP3-24: 24V 13440W	
• MP3-24: 24V 13500W	
• MP3-24: 24V 13560W	
• MP3-24: 24V 13620W	
• MP3-24: 24V 13680W	
• MP3-24: 24V 13740W	
• MP3-24: 24V 13800W	
• MP3-24: 24V 13860W	
• MP3-24: 24V 13920W	
• MP3-24: 24V 13980W	
• MP3-24: 24V 14040W	
• MP3-24: 24V 14100W	
• MP3-24: 24V 14160W	
• MP3-24: 24V 14220W	
• MP3-24: 24V 14280W	
• MP3-24: 24V 14340W	
• MP3-24: 24V 14400W	
• MP3-24: 24V 14460W	
• MP3-24: 24V 14520W	
• MP3-24: 24V 14580W	
• MP3-24: 24V 14640W	
• MP3-24: 24V 14700W	
• MP3-24: 24V 14760W	
• MP3-24: 24V 14820W	
• MP3-24: 24V 14880W	
• MP3-24: 24V 14940W	
• MP3-24: 24V 15000W	
• MP3-24: 24V 15060W	
• MP3-24: 24V 15120W	
• MP3-24: 24V 15180W	
• MP3-24: 24V 15240W	
• MP3-24: 24V 15300W	
• MP3-24: 24V 15360W	
• MP3-24: 24V 15420W	

[pdf] Specifications

NPSU 60W 24 96W Nora Lighting prolighting âº specsheets 24V spec |||

NPSU-60W/24 / NPSU-96W/24 24V Constant Voltage Class 2 Dimmable Driver

Phase, 0-10V PWM dimming ... are compatible with Nora Lighting s 24V systems

SERIES DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixed

NUTP1 24V Standard Tape Light Silicone Encapsulated NUTP3 24V RGB Co

[\[pdf\]](#) Specifications Catalog

Specification Sheet Nora Lighting NATL 596W Aaliyah 24 White Driver natl 24v plug in driver spec
lightingnewyork on demandware static Sites master catalog lny default dw3ae88201 brand nra assets
specsheets NATL-524 / NATL-545 / NATL-596 24V Plug-In LED Driver Source: 120V Input / 24V
Output 24W, 45W or 96W PRODUCT DESCRIPTION 24V plug-in driver to be used with Nora Lighting
24 Volt systems. FEATURES Direct connection to a wall outlet Non-d

NATL-524 / NATL-545 / NATL-596 24V Plug-In LED Driver Source: 120V Input / 24V Output 24W, 45W or 96 ... are compatible with Nora Lighting's 24V systems SERIES DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixed NUTP1 24V Standard-Tape Light Silicone Encapsulated NUTP2 24V RGB Color

lang:en score:21 filesize:444.81 K page_count:1 document_date:2023.03.20

[pdf] User Manual Specifications Catalog

Specification Sheet Nora Lighting NMT 48 24C2D1 Aaliyah Transformer nmt 24c2d1 spec
lightingnewyork on demandware static Sites master catalog Iny default dw53c1a8cc brand nra assets
specsheet |||

NMT-48/24C2D1 24V Dimmable Class II Hardwire Magnetic Driver Source: 120V Input / 24V Output 48W PR ... are compatible with Nora Lighting's 24V systems
SERIES DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixe
NIITP1 24V Standard Tape Light Silicone Encapsulated NIITP3 24V RGB Col

lang:en score:21 filesize: 414.71 K page_count: 1 document date: 2023-03-20

[\[pdf\]](#) Specifications Catalog

Specification Sheet Nora Lighting NATLED 5040HW Constant Voltage White LED Tape Driver natled
spec lightingnewyork on demandware static Sites master catalog lny default dwaf5cce9 brand nra assets
specsheet |||

NATLED-5040HW / NATLED-5075HW 24V Constant Voltage Dimmable Hardwire Electronic Driver Source: 120V ... are compatible with Nora Lighting's 24V systems
SERIES DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixed NUTP1 24V Standard Tape Light Silicone Encapsulated NUTP3 24V RGB Colo...
lang:en **score:21** filesize: 410.52 K page_count: 1 document date: 2023-03-20

[\[pdf\]](#) Specifications Catalog

Specification Sheet Nora Lighting NATL 5096 24 HWD10 Aaliyah White Driver natl hwd10 spec
lightingnewyork on demandware static Sites master catalog lny default dwadc3a702 brand nra assets
specsheet |||

NATL-5096-24-HWD10 24V Class II Dimmable Hardwire LED Driver 0-10V dimming
Source: 120-277V Input ... are compatible with Nora Lighting s 24V systems SERIES
DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixed NUTP1
24V Standard Tape Light Silicone Encapsulated NUTP3 24V RGB Colo...
lang:en score:21 filesize: 427.61 K page_count: 1 document_date: 2023-04-11

[pdf] Flyer Accessories

Sales Sheet NMP A Nora Lighting Josh Flyer noralighting 2021 12 |||

NEW PRODUCT ADDITION JOSH LED PUCK Adjustable or Fixed 12V or 24V / 300lm Slim LED disk light for a ... 0 CRI DAMP D M RoHS COMPLIANT Black Brushed Nickel JOSH LED PUCK TYPE NMP-A NMP-LED NMP2-A **NMP2-LED** 12V Adjustable 12V Fixed 24V Adjustable 24V Fixed CCT 27 2700K 30 3000K 35 3500K 40 4000K

lang:en score:21 filesize: 4.27 M page_count: 2 document_date: 2023-03-13

[pdf] User Manual Specifications Catalog

Specification Sheet Nora Lighting NMT 303 24C2D1 Aaliyah White Transformer in 120V nmt 24c2d spec
lightingnewyork on demandware static Sites master catalog lny default dw61d483c8 brand nra assets
specsheet III

NMT-303/24C2D1 / NMT-303/24C2D2 24V Class II Dimmable Hardwire Magnetic LED Driver with Breakers Sou ... are compatible with Nora Lighting s 24V systems
SERIES DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixed NUTP1 24V Standard Tape Light Silicone Encapsulated NUTP3 24V RGB Colo...
lang:en **score:21** filesize: 424.75 K page count: 1 document date: 2023-03-20

lang.en score.21 filesize. 424.75 K page_count. 1 document date. 2023-03-20

[pdf] User Manual

NMT 96 24C2D1 Nora Lighting Produces watts and can be dimmed with low voltage magnetic dimmer
24V RGBW Color Changing Tape Light NUTP12 Comfort Dim warm dim Tape spec noralighting 2022 06

NMT-96/24C2D1 24V Dimmable Class II Hardwire Magnetic Driver Source: 120V

Input / 24V Output 96W PR ... are compatible with Nora Lighting s 24V systems

SERIES DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixe

NU1P1 24V Standard Tape Light Silicone Encapsulated NU1P3 24V RGB Color

lang:en score:21 filesize: 415.02 K page_count: 1 document date: 2023-03-20

[\[pdf\]](#) Specifications Catalog

Specification Sheet Nora Lighting NMTD 96 24D MAG Black Driver Transformer Undercabinet nmtd 24d
spec lightingnewyork on demandware static Sites master catalog lny default dw7a6a3a86 brand nra
assets specsheets |||

NMTD-60/24D / NMTD-96/24D 24V Class II Dimmable Hardwire Magnetic LED Driver w/Regulator for Constant Current ... are compatible with Nora Lighting's 24V systems SERIES DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixed NUTP5 24V Hy-Brite Tape Light NUTP8 24V High Output Tape Light NUTP9 2...


lang:en score:21 filesize: 381.76 K page_count: 1 document date: 2024-11-04

[\[pdf\]](#) Specifications Catalog

Specification Sheet Nora Lighting NMTD 60 24D Silk 24 LED 3 inch Black Driver Undercabinet nmtd 24d
spec lightingnewyork on demandware static Sites master catalog lny default dw93c43953 brand nra
assets specsheets |||

NMTD-60/24D / NMTD-96/24D 24V Class II Dimmable Hardwire Magnetic LED Driver w/Regulator for Constant Current ... are compatible with Nora Lighting's 24V systems SERIES DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixed NUTP1 24V Standard Tape Light Silicone Encapsulated NUTP3 24V RGB Color...

lang:en score:21 filesize: 378.22 K page_count: 1 document date: 2023-03-20



[\[pdf\]](#)

NPSU 60W 24 96W 24V spec noralighting 2024 03 |||


NPSU-60W/24 / NPSU-96W/24 24V Constant Voltage Class 2 Dimmable Driver

Phase, 0-10V PWM dimming ... are compatible with Nora Lighting s 24V systems

SERIES DESCRIPTION NMP2-A 24V Josh Adjustable **NMP2-LED** 24V Josh Fixed

NUTP5 24V Hy-Brite Tape Light NUTP8 24V High Output Tape Light NUTP9 2...

lang:en score:17 filesize: 450.57 K page_count: 1 document date: 2024-11-04



[\[pdf\]](#)

PRODUCT PREVIEW Nora Lighting Available in a beautiful array of fixed and adjustable styles ten finishes each Pearl includes three field changeable optics for maximum design control Product Preview Q3 2024 noralighting 06 |||

PRODUCT PREVIEW 3RD Quarter 2024 FLAT Series Onyx Downlights NFJB-R4 Junction Box Housing ii M2 ... for info. 12V / 24V LED Puck Light Up to 300 lumens / 4.5W Now available in Adjustable NMP-LED / **NMP2-LED** Fixed Josh LED puck lights can be surface or recessed mounted with an included finished co...

lang:en score:14 filesize: 21.79 M page_count: 44 document date: 2024-09-10



[\[pdf\]](#)

PRODUCT PREVIEW Nora Lighting Trimless requires three parts Iolite Housing Mud Ring and Reflector Each trimless delivers from 800 to 2500 lumens in various kelvin temperatures 2700K Product Preview Q1 2025 noralighting 01 |||

PRODUCT PREVIEW 1ST Quarter 2025 Can-less LED Downlights BULK PACK SIZE LUMENS / WATTAGE 12 per ... nterchangeable Face Plate NSW-730 Vertical Face Plate NSW-740 Horizontal Face Plate NMP-LED 12V **NMP2-LED** 24V Fixed Adjust up to 18 NMP-A / NMP-AREC 12V NMP2-A / NMP-AREC 24V Adjustable with...

lang:en score:12 filesize: 22.53 M page_count: 48 document date: 2024-12-24