

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [UTG](#) /

› [UTG DS3039 ITA Red/Green Dot Sight Instruction Manual](#)

## UTG SCP-DS3039W

# UTG DS3039 ITA Red/Green Dot Sight Instruction Manual

Model: SCP-DS3039W | Brand: UTG

## PRODUCT OVERVIEW

The UTG DS3039 Instant Target Aiming (ITA) Combat Red/Green Dot Sight is a precision optical instrument designed for rapid target acquisition. It features a 30mm diameter, 3.9-inch length, and a 4.0 MOA dot. This sight comes complete with a Smart Riser Adaptor and a Straight-up Quick Detachable Tactical Mount, equipped with a fully adjustable cam lever lock system, and flip-open lens caps.

## Key Features

- Great Field of View and Unlimited Eye Relief, Clear and Sharp 4.0 MOA Dot Sight, No-Reflection High Tech Emerald Coatings.
- Red or Green Dot Adapts to Any Environmental Background, Optimal Height Design to Co-witness with Iron Sights.
- Includes Both Smart Adaptor & Straight-up Quick Detachable Tactical Mount with Innovative Quick Detach Mounting Deck to Use on Any Picatinny Rail.
- Patterned Illumination Rheostat with Variable Brightness Levels Offers Stealthy and Infinitely Fine Adjustment.
- Aim and Instant Lock On Target to Enhance Shooting Accuracy and Performance, Most Versatile Dot Sight for Wide Range of Pistols, Shotguns & Rifles.

## Included Components

- Mounts
- Sight

## SETUP

### Unpacking

Carefully remove all components from the packaging. Inspect the sight and accessories for any signs of damage. Retain the packaging for future storage or transport.



**YOUR SATISFACTION IS OUR GOAL**

Image: The product packaging for the UTG Red/Green Dot Sight, showing the 3.9" total length and 30mm diameter specifications.


### **Mounting Instructions**

The sight includes a Quick Detachable Tactical Mount designed for Picatinny rails. To mount, open the cam lever lock, position the sight on the rail, and close the lever firmly. Ensure the mount is securely fastened to prevent movement during use. The sight also features an offset-adjustable mounting deck for riser configurations.



# UTG MAGNIFIER/RED DOT CROSS REFERENCE

(V1.0 2012-03-25)



ITEM NUMBER	LENGTH	CENTER HEIGHT	SCP-MF3WQ	SCP-MF3WQ	SCP-MF3WQS
SCP-DS3026W	2.6" Tactical Dot Sight	25mm		NO	YES ON 1/2" RISER
SCP-DS3028W	3" Tactical Dot Sight	25mm		NO	YES ON 1/2" RISER
SCP-DS3039W	3.9" Tactical Dot Sight with Low Mount	30mm		YES	NO
SCP-DS3039W	3.9" Tactical Dot Sight with High Mount	40mm		NO	YES
SCP-DS3840W	4.2" Tactical Dot Sight with Low Mount	30mm		YES	NO
SCP-DS3840W	4.2" Tactical Dot Sight with High Mount	40mm		NO	YES
SCP-DS3068W	6.8" Tactical Dot Sight	25mm		NO	YES ON 1/2" RISER
SCP-RD40RGW-A	4" Single Dot with Thumb Twist Lock	25.5mm		NO	YES ON 1/2" RISER
SCP-RD40SDQ	4" Single Dot with QD Base	25.5mm		NO	YES ON 1/2" RISER
SCP-RD40CDQ	4" Circle Dot with QD Base	25.5mm		NO	YES ON 1/2" RISER

Image: The UTG Red/Green Dot Sight mounted on a rail, illustrating the offset-adjustable mounting deck in a riser configuration.



Image: A cross-reference chart detailing compatibility of various UTG dot sights with different risers and mounts, including the SCP-DS3039W model.

## Battery Installation

The sight requires a specific battery type (typically a CR2032, though not explicitly stated in provided data). Locate the battery compartment, usually a screw-on cap on the side or top of the sight. Insert the battery with the correct polarity (+/-) as indicated inside the compartment. Securely close the cap.

## OPERATING INSTRUCTIONS

### Power On/Off and Reticle Adjustment

The sight features a patterned illumination rheostat. Rotate the rheostat knob, typically located on the side of the sight, to turn the unit on and select between red or green dot illumination. Continue rotating to adjust the brightness level. To power off, rotate the knob to the 'OFF' position.



Image: Main view of the UTG Red/Green Dot Sight, showing the overall design and adjustment knobs.

## Windage and Elevation Adjustment

Adjustment turrets for windage (horizontal) and elevation (vertical) are typically located on the top and side of the sight. Remove the protective caps. Use a flathead screwdriver or the integrated tool (if provided) to make small adjustments. Each click typically represents a specific change in point of impact at a given distance (e.g., 1 MOA per click).



## Offset-adjustable Mounting Deck (Riser Configuration)

Image: An angled view of the UTG Red/Green Dot Sight, highlighting the windage and elevation adjustment turrets.

### Zeroing the Sight

To zero the sight, mount it securely on your firearm. At a safe shooting range, fire a group of shots at a target. Observe where the shots impact relative to your aim point. Adjust the windage and elevation turrets to move the point of impact towards your aim point. Repeat this process until your shots consistently hit the desired target area. Always follow safe firearm handling procedures.

## MAINTENANCE

---

### Cleaning

To clean the lenses, use a soft, lint-free cloth and a lens cleaning solution specifically designed for optics. Gently wipe the lens surfaces. For the sight body, use a damp cloth to remove dirt and debris. Avoid using harsh chemicals or abrasive materials that could damage the finish or coatings.

### Storage

When not in use, store the sight in a cool, dry place, away from direct sunlight and extreme temperatures. It is recommended to remove the battery if the sight will be stored for an extended period to prevent battery leakage.

### Battery Replacement

When the dot illumination becomes dim or inconsistent, it is time to replace the battery. Follow the battery installation steps outlined in the Setup section. Ensure the new battery is of the correct type and inserted with the proper polarity.

## TROUBLESHOOTING

---

Problem	Possible Cause	Solution
---------	----------------	----------

Problem	Possible Cause	Solution
Dot not visible	Low battery, brightness setting too low, lens caps closed	Replace battery, increase brightness, open lens caps
Dot flickering or inconsistent	Loose battery, poor battery contact, faulty battery	Check battery connection, clean contacts, replace battery
Inaccurate aiming / Point of impact shifts	Sight not zeroed, loose mount, damaged sight	Zero the sight, tighten mount screws, contact support if damaged
Adjustment turrets not responding	Turret caps not removed, internal mechanism issue	Ensure caps are removed, contact support if issue persists

## SPECIFICATIONS

Feature	Detail
Brand	UTG
Model Name	SCP-DS3039W
Color	Black
Style	Tactical or Sporty
Sport	Hunting
Item Weight	0.16 Kilograms
Material	Aluminum
Objective Lens Diameter	26 Millimeters
Magnification Minimum	1 x
Compatible Devices	Handgun, Rifle, Shotgun
Mounting Type	Integral QD Mount
Field Of View	70 Feet
Reticle Type	Single Dot
Size	3.9"
Manufacturer	LEABG
Date First Available	December 29, 2010

## WARRANTY AND SUPPORT

## Warranty Information

This product is covered by a Lifetime Warranty. Please refer to the manufacturer's official warranty policy for full details regarding coverage and claims.



Image: A graphic displaying the LEAPERS, INC. TNR (The Best Never Rest) Lifetime Warranty statement.

## Customer Support

For technical assistance, warranty claims, or any other inquiries not covered in this manual, please contact UTG customer support through their official website or the retailer from whom the product was purchased.

---

**Legal Disclaimer:** Users are advised to check and comply with all local laws and regulations regarding the use of this product.