

[Manuals.plus](#) /

› [TEMOLA](#) /

› TEMOLA TN10 Portable Cordless Electric Air Inflator User Manual

TEMOLA TN10

TEMOLA TN10 Portable Cordless Electric Air Inflator User Manual

Model: TN10

1. INTRODUCTION

Thank you for purchasing the TEMOLA TN10 Portable Cordless Electric Air Inflator. This device is designed for convenient and efficient inflation of various items, including car tires, bicycle tires, sports balls, and inflatable toys. It features a large-capacity rechargeable battery, automatic stop function, digital pressure display, and an integrated LED light for versatile use.

Please read this manual thoroughly before use to ensure safe and optimal operation. Keep this manual for future reference.

2. SAFETY INSTRUCTIONS

- Do not leave the inflator unattended during operation.
- Keep out of reach of children.
- Do not expose to rain or moisture.
- Avoid operating in extremely hot or cold environments.
- Ensure the correct pressure setting for the item being inflated to prevent over-inflation.
- Do not use for purposes other than intended.
- If the device overheats, allow it to cool down before further use.

3. PACKAGE CONTENTS

Verify that all items are present in the package:

- 1 x TEMOLA TN10 Air Inflator
- 1 x Air Tube
- 3 x Air Nozzle Cones (various sizes)

- 1 x French/American Valve Adapter
- 1 x Needle Valve Adapter
- 1 x USB Charging Cable (Type-C)
- 1 x 12V Car Power Cable
- 1 x Storage Bag
- 1 x Safety Hammer (if included in specific package)
- 1 x User Manual



4. PRODUCT OVERVIEW

The TEMOLA TN10 features a compact design with an intuitive interface for easy operation.



Image: Front view of the TEMOLA TN10 Air Inflator, highlighting the digital display and control buttons.

4.1. Key Features

- **Cordless & Portable:** Integrated large-capacity battery for up to 30 minutes of continuous inflation.
- **Automatic Stop Function:** Automatically stops inflation once the preset pressure is reached.
- **High Pressure Capability:** Maximum pressure of 150 PSI.
- **Multiple Pressure Units:** Switch between PSI, BAR, KPA, and kg/cm².
- **Digital Display:** Large LCD screen shows real-time pressure and preset values.
- **LED Light:** Features white illumination, emergency SOS, and flashing modes for night use.
- **Power Bank Function:** Type-C output port for charging mobile phones.
- **Low Noise Operation:** Operates at less than 70 dB.

5. SETUP

5.1. Charging the Device

1. Connect the provided USB charging cable to the Type-C input port on the inflator.
2. Connect the other end of the USB cable to a compatible USB power adapter (not included) or a 12V car power outlet using the car power cable.
3. The battery indicator on the digital display will show charging status. Charge until the battery icon indicates full.

Note: Fully charge the device before first use to ensure optimal battery life.

5.2. Attaching the Air Tube and Nozzle

1. Screw the air tube securely onto the inflator's air outlet.
2. Select the appropriate nozzle for the item you wish to inflate.
3. Screw the selected nozzle onto the other end of the air tube.

梱包内容

- | | |
|---------------|----------------|
| 1. エアーインフレーター | 5. バルブアダプター |
| 2. エアチューブ | 6. USB充電ケーブル |
| 3. 日本語説明書 | 7. 12V車用電源ケーブル |
| 4. 収納袋 | 8. 安全ハンマー |



Image: The TEMOLA TN10 Air Inflator connected to its air tube and various nozzle attachments.

6. OPERATING INSTRUCTIONS

6.1. Powering On/Off

- Press and hold the Power button (U) to turn the inflator ON.
- Press and hold the Power button (U) again to turn the inflator OFF.

6.2. Setting Pressure Units

With the device ON, press the Unit button (often labeled 'M' or a similar icon) to cycle through the available pressure units: PSI, BAR, KPA, kg/cm².

6.3. Selecting Inflation Mode and Setting Target Pressure

The inflator typically has preset modes for common items (car, motorcycle, bicycle, ball). You can also use manual mode.

1. Press the Mode button (often labeled 'M' or a similar icon) to select the desired inflation mode. Each mode may have a default preset pressure.
2. Use the '+' and '-' buttons to adjust the target pressure value. The digital display will show the current preset value.
3. For manual mode, set the desired pressure directly using the '+' and '-' buttons.



Image: A close-up of the TEMOLA TN10's digital display, showing preset mode, pressure value, pressure unit, and battery level indicators.

6.4. Starting and Stopping Inflation

1. Connect the nozzle securely to the valve of the item to be inflated.
2. Press the Power button (U) to start inflation. The display will show the real-time pressure.
3. The inflator will automatically stop once the preset pressure is reached.
4. To manually stop inflation, press the Power button (U) again.
5. Carefully disconnect the nozzle from the valve.



Image: The TEMOLA TN10 Air Inflator connected to a car tire valve, demonstrating the inflation process.

6.5. Using the LED Light

Press the SOS button (often labeled 'SOS' or a light bulb icon) to cycle through the LED light modes:

- First press: White illumination (flashlight mode).
- Second press: Emergency SOS flashing mode.
- Third press: Flashing mode.
- Fourth press: Turn off the LED light.

7. MAINTENANCE

- **Cleaning:** Wipe the device with a soft, dry cloth. Do not use harsh chemicals or abrasive cleaners.
- **Storage:** Store the inflator and its accessories in the provided storage bag in a cool, dry place, away from direct sunlight and extreme temperatures.
- **Battery Care:** To prolong battery life, charge the device at least once every three months if not in regular use.
- **Nozzle Inspection:** Periodically check nozzles and the air tube for any damage or blockages.

8. TROUBLESHOOTING

Problem	Possible Cause	Solution
Device does not turn on.	Low battery or no charge.	Charge the device fully.
Inflator stops prematurely.	Target pressure reached, or device overheated.	Check preset pressure. If overheated, allow to cool down.
Inaccurate pressure reading.	Loose connection or faulty sensor.	Ensure air tube and nozzle are securely attached. Contact support if issue persists.
Slow inflation.	Low battery or large volume item.	Ensure device is fully charged. Inflation speed varies by item size.

9. SPECIFICATIONS

Feature	Detail
Brand	TEMOLA
Model Name	TN10
Maximum Pressure	150 PSI
Voltage	12 Volts
Wattage	120 W
Power Source	Battery Powered
Noise Level	70 dB
Special Feature	Pressure detection, Automatic Stop
Product Dimensions	21 x 14.2 x 7.9 cm
Item Weight	720 g

10. WARRANTY AND SUPPORT

For warranty information or technical support, please refer to the contact details provided with your purchase or visit the official TEMOLA website. Please have your model number (TN10) and purchase date available when contacting support.
Official TEMOLA Website: [TEMOLA Brand Store](#)

