

Camco 41715

Camco Premium Ceramic RV Toilet

MODEL: 41715

Instruction Manual

Introduction

Thank you for choosing the Camco Premium Ceramic RV Toilet, Model 41715. This manual provides essential information for the proper installation, operation, and maintenance of your new RV toilet. Designed for comfort and durability, this full-sized ceramic toilet features an 18-inch chair height, a soft-close wood seat and lid, and a gravity flush system with a convenient two-step foot pedal. Please read these instructions thoroughly before installation and use to ensure optimal performance and longevity of your product.

Safety Information

- Always wear appropriate personal protective equipment (PPE) during installation and maintenance.
- Ensure all water and waste connections are secure to prevent leaks.
- Do not use harsh chemicals or abrasive cleaners on any part of the toilet, as this may damage surfaces or internal components.
- Verify that the toilet is securely mounted to the floor before use to prevent tipping or instability.
- Consult local plumbing codes and regulations for proper installation and waste disposal procedures.

Parts List

The Camco Premium Ceramic RV Toilet (Model 41715) includes the following components:

- Toilet Assembly (ceramic bowl, ABS resin base, wood seat and lid)
- Floor Seal
- Mounting Hardware

Refer to the image below for a visual representation of the included components and key features.

Features:

INCLUDES:

- Toilet assembly
- Floor seal
- Mounting hardware

EASY TO INSTALL:

Standard
2-bolt installation

TOILET DIMENSIONS:

18 ½" (L) x 14 ¾" (W) x 19 ½" (H)
Weighs 32 lb



Figure 1: Included components and key features of the Camco Premium Ceramic RV Toilet.

Setup and Installation

Installation of the Camco Premium Ceramic RV Toilet is designed for a standard two-bolt setup. Follow these general steps:

1. **Preparation:** Ensure the water supply is turned off and the waste tank is empty. Remove any existing toilet. Clean the floor flange area thoroughly.
2. **Positioning:** Place the new floor seal over the waste opening on the floor flange. Carefully position the toilet assembly over the floor flange, aligning the mounting holes with the bolts.
3. **Securing:** Use the provided mounting hardware to secure the toilet to the floor. Tighten the nuts evenly to create a watertight seal, but do not overtighten to avoid cracking the ceramic.
4. **Water Connection:** Connect the water supply line to the toilet's water inlet. Ensure all connections are tight to prevent leaks.
5. **Testing:** Turn on the water supply and check for any leaks around the base and water connection. Flush the toilet several times to verify proper operation and seal.

For a visual guide, please watch the official installation video:

Your browser does not support the video tag.

Video 1: Official installation guide for the Camco Premium Ceramic RV Toilet (Models 41710/41715).

Operating Instructions

The Camco Premium Ceramic RV Toilet features a gravity flush system operated by a two-step foot pedal:

- **Adding Water to Bowl:** To add water to the bowl before use, press the foot pedal halfway down. This will open the water valve, allowing water to fill the bowl. Release the pedal to close the valve.

- **Flushing:** To flush the toilet, press the foot pedal fully down. This will open both the water valve and the waste ball valve, allowing water to rinse the bowl and waste to enter the holding tank. Hold the pedal down until the bowl is clear, then release it to close both valves.

The soft-close seat and lid ensure quiet operation. Avoid forcing the seat or lid closed manually to preserve the soft-close mechanism.

Hygienic foot
pedal for
simple flushing



Simple
two-step flush

Superior Gravity Flush System



Figure 2: Operation of the two-step foot pedal for filling and flushing.

Maintenance

Regular maintenance ensures the longevity and hygienic operation of your RV toilet:

- **Cleaning:** Clean the ceramic bowl and exterior surfaces regularly with mild soap and water or a non-abrasive bathroom cleaner. Avoid cleaners containing harsh chemicals, acids, or abrasives, as these can damage the ceramic finish, plastic components, or wood seat.

- **Seal Lubrication:** Periodically lubricate the waste ball seal with a silicone-based lubricant designed for RV toilets to maintain a good seal and smooth pedal operation.
- **Winterization:** Before storing your RV in freezing temperatures, ensure the toilet and plumbing system are properly winterized according to your RV manufacturer's guidelines. This typically involves draining all water and flushing with RV antifreeze.
- **Seat Care:** The wood seat can be cleaned with a damp cloth and mild soap. Avoid excessive moisture and harsh chemicals to prevent damage to the wood finish.

Troubleshooting

Here are solutions to common issues you might encounter:

- **Leaks at Base:** Check the tightness of the mounting bolts. Ensure the floor seal is properly seated and not damaged. If leaks persist, the floor seal may need replacement.
- **Water Leaking into Bowl:** This usually indicates a worn or dirty water valve seal. Turn off the water supply, clean the seal, or replace it if necessary.
- **Poor Flush:** Ensure adequate water pressure. Check if the waste ball opens fully when the pedal is pressed. A clogged rim jet or a partially obstructed waste ball can reduce flush effectiveness.
- **Foot Pedal Sticking:** Lubricate the pedal mechanism and waste ball seal with a silicone-based lubricant.
- **Odor:** Ensure the waste ball seal is holding water to prevent odors from the holding tank. Use appropriate RV toilet chemicals to break down waste and control odors.

If you experience persistent issues not covered here, please contact Camco customer support.

Specifications

Feature	Specification
Model Number	41715
Color	Bone
Product Dimensions (D x W x H)	18.5"D x 14.75"W x 19.5"H
Item Weight	32 Pounds
Material	Ceramic bowl, ABS resin base, Wood seat
Installation Method	Floor Mounted (Standard 2-bolt)
Flush System	Gravity Flush with Two-Step Foot Pedal
Seat Height	18 inches (Chair Height)





Figure 3: Detailed dimensions of the Camco Premium Ceramic RV Toilet.

Warranty Information

This product is covered by a Manufacturer Warranty. For specific details regarding warranty coverage, terms, and

conditions, please refer to the documentation included with your purchase or contact Camco customer service directly. Keep your proof of purchase for warranty claims.

Support

For further assistance, technical support, or to inquire about replacement parts, please contact Camco customer service. You can typically find contact information on the product packaging, the official Camco website, or by searching for 'Camco customer support' online.

© 2026 Camco. All rights reserved.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question