Manuals+
Q & A | Deep Search | Upload

PROFLO PFPHUFK

PROFLO PFPHUFK 2" PVC Horizontal Hub Urinal Flange Kit

INSTRUCTION MANUAL

Introduction

The PROFLO PFPHUFK 2" PVC Horizontal Hub Urinal Flange Kit is designed to provide a secure and adjustable connection for urinal installations. This kit ensures a reliable seal and straightforward setup, featuring durable plastic construction.

Key features include horizontal adjustability, stainless steel bolts, nuts, and washers, and a thick foam rubber gasket for a tight seal.

Safety Information

- Always turn off the water supply to the urinal before beginning any installation or maintenance work.
- Wear appropriate personal protective equipment (PPE), such as gloves and eye protection, during installation.
- Ensure all connections are secure to prevent leaks.
- **Proposition 65 Warning:** This product may expose you to chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Package Contents

Verify that all components are present before beginning installation:

- 1 x PROFLO PFPHUFK 2" PVC Horizontal Hub Urinal Flange
- 1 x Thick Foam Rubber Gasket
- 2 x Stainless Steel Bolts
- 2 x Stainless Steel Nuts
- 2 x Stainless Steel Washers

Setup and Installation

Follow these steps for proper installation of the urinal flange kit:

This image displays the main components of the PROFLO PFPHUFK kit: the white PVC horizontal hub urinal flange, the black foam rubber gasket, and two stainless steel bolts with nuts and washers.

1. **Preparation:** Ensure the urinal drain pipe is clean and free of debris. Turn off the water supply to the urinal.
2. **Gasket Placement:** Place the thick foam rubber gasket onto the base of the urinal flange. Ensure it is seated correctly and forms a complete seal around the flange opening.
3. **Flange Positioning:** Insert the PVC flange into the urinal drain opening. The horizontal hub design allows for adjustment to align with the urinal's mounting holes. Position the flange so its slots align with where the urinal will be mounted.
4. **Urinal Installation:** Carefully lower the urinal onto the flange, aligning the urinal's mounting holes with the slots on the flange. Ensure the gasket creates a tight seal between the urinal and the flange.
5. **Secure with Bolts:** Insert the stainless steel bolts through the urinal's mounting holes and the flange slots. Secure with the stainless steel washers and nuts. Tighten evenly to create a firm, leak-proof connection. **Do not overtighten** to avoid cracking the urinal or flange.
6. **Water Supply:** Once the urinal is securely mounted, turn the water supply back on and check for any leaks around the flange connection.

Maintenance

Proper maintenance ensures the longevity and performance of your urinal flange kit:

- **Regular Cleaning:** Clean the exterior of the flange and urinal regularly with mild, non-abrasive cleaners. Avoid harsh chemicals that could degrade the PVC or gasket material.
- **Leak Checks:** Periodically inspect the connection points for any signs of leaks. If a minor leak is detected, gently tighten the bolts. If leaks persist, the gasket may need inspection or replacement.
- **Avoid Harsh Chemicals:** Do not use harsh chemical drain cleaners or abrasive tools that could damage the PVC material or the gasket, compromising the seal.

Troubleshooting

Address common issues with your urinal flange kit:

- **Leakage at Flange Base:**
  - Ensure the foam rubber gasket is properly seated and not damaged.
  - Check that the bolts are tightened evenly and sufficiently. If leaks persist after tightening, the gasket may need to be replaced.
- **Urinal Not Level:**
  - Verify that the flange is installed correctly and the urinal is properly aligned. The horizontal adjustability of the flange should allow for minor adjustments.
  - Ensure the floor surface beneath the urinal is level. Shims may be required if the floor is uneven.

Specifications

Manufacturer	PROFLO
Part Number	PFPHUFK
Item Weight	8 ounces
Product Dimensions	9 x 6.8 x 1.8 inches
Material	Plastic (PVC)
Color	White
Included Components	Urinal Flange Kit (Flange, Gasket, Bolts, Nuts, Washers)

Warranty and Support

For warranty information, technical assistance, or to inquire about replacement parts, please contact PROFLO customer service directly or visit their official website.

You can also find more information and products by visiting thePROFLO Store on Amazon.