

[Manuals.plus](#) /

› [Parryware](#) /

› PARRYWARE Cute Range One Piece Rim Floor Mounted Western Commode C8851 Instruction Manual

Parryware C8851

PARRYWARE Cute Range One Piece Rim Floor Mounted Western Commode

Model: C8851 | **Brand:** Parryware

1. PRODUCT OVERVIEW

The Parryware Cute Range One Piece Rim Western Commode (Model C8851) is designed for modern bathrooms, offering both functionality and aesthetic appeal. This floor-mounted unit features a seamless one-piece ceramic structure with an exposed flush tank, simplifying cleaning and maintenance. It is equipped with a standard S-Trap outlet for versatile plumbing configurations and includes a soft-close seat cover for quiet operation.



Figure 1: Front view of the Parryware Cute Range One Piece Western Commode C8851, showcasing its compact and integrated design.

Key Features:

- One-Piece Floor-Mounted Rim Design (640×360×710mm) for sleek aesthetics and easy cleaning.
- Standard 220mm S-Trap outlet for compatibility with typical bathroom layouts.
- Soft-Close Seat Cover for quiet and comfortable use.
- Constructed from high-gloss vitreous china with an anti-germ glaze.
- Includes a dual-flush cistern for water efficiency.

2. PACKAGE CONTENTS

Verify that all components are present and undamaged before beginning installation. If any parts are missing or damaged, contact customer support.

- One-Piece Western Commode (Toilet Bowl with integrated cistern)
- Soft-Close Seat Cover
- Dual-Flush Cistern Mechanism (pre-installed or separate)

- Quick Connect Fixtures
- Wax Seal Ring
- Floor Screws and Anchors
- Installation Accessories (e.g., bolts, washers)

3. SAFETY INFORMATION

Read all instructions carefully before installation and use. Failure to follow these instructions may result in property damage or personal injury.

- Always wear appropriate personal protective equipment (PPE) such as gloves and eye protection during installation.
- Ensure the water supply to the installation area is turned off before beginning any plumbing work.
- Handle ceramic components with care to prevent chipping or breakage.
- Do not overtighten fasteners, as this can crack the ceramic.
- If you are unsure about any installation step, consult a qualified plumber.

4. SETUP AND INSTALLATION

This commode is designed for floor-mounted installation with an S-Trap outlet. Professional installation is recommended.

Required Tools (Not Included):

- Adjustable Wrench
- Screwdriver (Phillips/Flathead)
- Drill with appropriate masonry bit (if new floor anchors are needed)
- Level
- Measuring Tape
- Sealant (e.g., silicone caulk)

Installation Steps:

1. **Prepare the Area:** Turn off the water supply. Remove the old toilet if applicable and clean the flange area thoroughly. Ensure the floor is level and the S-Trap outlet is clear.
2. **Install Wax Seal:** Place the wax seal ring onto the toilet's waste outlet or directly onto the floor flange, ensuring a good seal.
3. **Position the Commode:** Carefully lift and align the commode over the floor bolts and the wax seal. Gently lower it, pressing down firmly to compress the wax seal. Do not rock the commode.
4. **Secure to Floor:** Install the washers and nuts onto the floor bolts. Hand-tighten first, then use a wrench to tighten evenly, alternating between bolts. **Do not overtighten** to avoid cracking the ceramic.
5. **Connect Water Supply:** Connect the water supply line to the fill valve inlet on the cistern. Ensure all connections are hand-tightened, then use a wrench for a final snug fit.
6. **Install Seat Cover:** Attach the soft-close seat cover according to its specific instructions, typically involving inserting hinges into designated holes and securing them.

7. **Test and Seal:** Turn on the water supply and check for leaks. Flush the commode several times to ensure proper operation of the dual-flush mechanism. Once satisfied, apply a bead of silicone sealant around the base of the commode where it meets the floor, leaving a small gap at the back for ventilation.



Figure 2: Side view of the commode, illustrating the integrated cistern and the floor-mounted design for S-Trap plumbing.

5. OPERATING INSTRUCTIONS

The Parryware C8851 commode features a dual-flush system for water conservation and a soft-close seat for user comfort.

Flushing:

- **Half Flush (Liquid Waste):** Press the smaller button on the top of the cistern for a reduced water flush.
- **Full Flush (Solid Waste):** Press the larger button for a complete water flush.

Soft-Close Seat:

The seat and lid are designed to close slowly and quietly. Simply push the seat or lid down gently, and it

will lower itself without slamming.

6. MAINTENANCE AND CLEANING

Regular cleaning and proper maintenance will ensure the longevity and hygiene of your commode.

Cleaning the Ceramic Surface:

- Use a soft cloth or sponge with mild soap and water.
- For tougher stains, use a non-abrasive bathroom cleaner specifically designed for ceramic surfaces.
- Rinse thoroughly with clean water and dry with a soft cloth to prevent water spots.
- **Avoid:** Abrasive cleaners, scouring pads, strong acids, or bleach, as these can damage the anti-germ glaze and ceramic finish.

Cleaning the Seat Cover:

- Clean the seat and lid with mild soap and water.
- Do not use harsh chemicals or abrasive cleaners, as they can discolor or damage the seat material.

Internal Maintenance:

- Periodically check the cistern mechanism for proper function.
- If the flush mechanism becomes sluggish, consult the manufacturer's guide for internal component cleaning or replacement.

7. TROUBLESHOOTING

This section addresses common issues you might encounter with your commode.

Problem	Possible Cause	Solution
Weak Flush	Low water level in cistern, partially closed water supply valve, clogged rim jets.	Check water supply valve is fully open. Adjust water level in cistern. Clean rim jets with a small wire or brush.
Continuous Water Running	Faulty flapper/seal, misaligned fill valve, debris in fill valve.	Inspect flapper/seal for wear or obstruction and replace if necessary. Check fill valve alignment and clean any debris.
Slow Cistern Refill	Partially closed water supply valve, clogged fill valve.	Ensure water supply valve is fully open. Clean or replace the fill valve if clogged.
Leaks at Base	Improperly seated wax seal, loose floor bolts, cracked ceramic.	Tighten floor bolts evenly (do not overtighten). If leak persists, remove commode and replace wax seal. Inspect for ceramic cracks.

8. SPECIFICATIONS

Model Number	C8851
Dimensions (L x W x H)	64 x 36 x 71 Centimeters (640 x 360 x 710 mm)
Weight	34 kg
Color	White
Primary Material	Vitreous China (Ceramic)
Installation Type	Floor Mounted
Trap Type	S-Trap (220mm)
Flush Type	Dual Flush
Manufacturer	Roca Bathroom Products Pvt. Ltd.

9. WARRANTY AND SUPPORT

This Parryware commode is backed by a commitment to quality and durability.

Warranty Information:

- A **10-year ceramic warranty** is provided, covering manufacturing defects in the vitreous china components.
- Warranty terms and conditions apply. Please retain your proof of purchase.

Customer Support:

For technical assistance, warranty claims, or to inquire about replacement parts, please contact Parryware customer service. Refer to the official Parryware website or your purchase documentation for current contact details.

Manufacturer: Roca Bathroom Products Pvt. Ltd.