



Manuals.plus /

› Parryware /

› PARRYWARE Claret Series T4641A1 1 Way Concealed Diverter Instruction Manual

## Parryware T4641A1

# PARRYWARE Claret Series T4641A1 1 Way Concealed Diverter Instruction Manual

## 1. INTRODUCTION

---

This manual provides essential information for the proper installation, operation, and maintenance of your PARRYWARE Claret Series T4641A1 1 Way Concealed Diverter. Please read these instructions carefully before installation and retain them for future reference. This product is designed for use in standard domestic plumbing systems to direct water flow to a single spout outlet.

## 2. SAFETY INFORMATION

---

- Always turn off the main water supply before attempting any installation, maintenance, or repair.
- If you are unsure about any part of the installation process, consult a qualified plumber.
- Wear appropriate personal protective equipment (PPE) such as safety glasses and gloves during installation.
- Ensure all connections are secure to prevent leaks.
- Do not use abrasive cleaners or harsh chemicals on the chrome finish, as this may damage the surface.

## 3. PACKAGE CONTENTS

---

Verify that all components are present before beginning installation:

- Valve
- Coupling
- Main Body with Accessories Kit



**Image 1:** The PARRYWARE Claret Series T4641A1 1 Way Concealed Diverter, showing the main body and associated components included in the package. This image helps identify the product and its parts for installation.

## 4. SPECIFICATIONS

---

<b>Model Number</b>	T4641A1
<b>Brand</b>	Parryware
<b>Material</b>	Brass
<b>Finish</b>	Chrome
<b>Mount Type</b>	Wall Mounted, Concealed Fitting
<b>Diverter Type</b>	1 Way, Knob Selector
<b>Connections</b>	Only to Spout
<b>Valve Type</b>	Dual-function
<b>Item Dimensions (L x W x H)</b>	20 x 20 x 20 Centimeters

## 5. SETUP AND INSTALLATION

---

The PARRYWARE Claret Series T4641A1 is a concealed, wall-mounted diverter designed to direct water flow to a single spout. Professional installation is highly recommended.

## 5.1 Pre-Installation Steps

1. **Turn off Water Supply:** Locate the main water shut-off valve for your property and turn it off.
2. **Clear Work Area:** Ensure the installation area is clean and free of obstructions.
3. **Inspect Components:** Check all parts for any damage before installation.

## 5.2 Installation Procedure

1. **Prepare Wall Cavity:** Create an appropriate cavity in the wall for the concealed diverter body, ensuring it aligns with the desired spout location.
2. **Connect Water Lines:** Connect the hot and cold water supply lines to the designated inlets on the diverter body. Use appropriate plumbing fittings and sealants to ensure watertight connections.
3. **Connect Spout Outlet:** Connect the single outlet of the diverter to the spout's water inlet.
4. **Secure Diverter Body:** Secure the diverter body firmly within the wall cavity using appropriate mounting hardware. Ensure it is level and properly aligned.
5. **Install Trim Kit:** Once the wall is finished, install the decorative trim kit, including the knob selector, according to the manufacturer's instructions.
6. **Test for Leaks:** Slowly turn on the main water supply and carefully check all connections for leaks. Address any leaks immediately.

## 6. OPERATING INSTRUCTIONS

---

The PARRYWARE Claret Series T4641A1 diverter features a single knob selector for controlling water flow to the spout.

- **Turning Water On/Off:** Rotate the knob selector to turn the water flow to the spout on or off.
- **Adjusting Temperature:** The diverter itself does not control temperature. Temperature adjustment is managed by the mixer valve connected upstream (if applicable).

## 7. MAINTENANCE

---

Regular maintenance will help ensure the longevity and optimal performance of your diverter.

- **Cleaning the Finish:** Clean the chrome finish regularly with a soft cloth and mild soap and water. Rinse thoroughly and dry to prevent water spots. Do not use abrasive cleaners, scouring pads, or chemicals containing ammonia, bleach, or alcohol, as these can damage the finish.
- **Checking for Leaks:** Periodically inspect the visible connections for any signs of leaks. Address any leaks promptly to prevent water damage.
- **Internal Components:** For internal component maintenance or replacement, it is recommended to contact a qualified plumber or the manufacturer's service center.

## 8. TROUBLESHOOTING

---

This section addresses common issues you might encounter with your diverter.

Problem	Possible Cause	Solution
Water leaking from connections	Loose connections, damaged seals/gaskets	Turn off water supply. Tighten connections. Replace seals/gaskets if damaged.
Low water flow to spout	Partial blockage in pipes, low water pressure, issue with upstream mixer	Check main water supply pressure. Inspect pipes for blockages. Consult a plumber if issue persists.
Knob selector is stiff or difficult to turn	Mineral buildup, worn internal cartridge	Ensure regular cleaning. If issue persists, the internal cartridge may need replacement by a qualified technician.

If you encounter problems not listed here or if the suggested solutions do not resolve the issue, please contact customer support.

## 9. WARRANTY INFORMATION

---

PARRYWARE provides the following warranty for the T4641A1 diverter:

- **Brass Body:** Standard Manufacturer's Warranty for 10 Years on the Brass Body Only.
- **Internal Fittings:** 5 Years on Internal Fittings (Inner head & Cartridges).

Please refer to Parryware's official warranty policy document for complete terms, conditions, and exclusions. Proof of purchase is required for all warranty claims.

## 10. CUSTOMER SUPPORT

---

For technical assistance, spare parts, or warranty claims, please contact Parryware customer service. You can typically find contact information on the official Parryware website or through your retailer.

**Manufacturer:** Roca Bathroom Products Pvt. Ltd.

**Address:** The Heritage No. 41, Haddows road, Nungambakkam, Chennai - 600006

When contacting support, please have your product model number (T4641A1) and proof of purchase readily available.