

95292260

Generic Fuel Tank Filler Gas Cap Instruction Manual

Model: 95292260

1. INTRODUCTION

This manual provides essential information for the proper installation, operation, and maintenance of your new Generic Fuel Tank Filler Gas Cap, model 95292260. Please read these instructions carefully before proceeding to ensure correct usage and optimal performance.

2. COMPATIBILITY

This fuel tank filler gas cap (OEM Part Number: 95292260) is designed as a direct replacement for the following vehicle models. Please verify your vehicle's OEM part number before installation to ensure compatibility.

- For BUICK CASCADA: 2016-2019
- For BUICK ENCORE: 2013-2021
- For BUICK VERANO: 2013-2017
- For CHEVROLET CRUZE: 2012-2019
- For CHEVROLET CRUZE LIMITED: 2016
- For CHEVROLET MALIBU: 2016
- For CHEVROLET ORLANDO: 2013-2014
- For CHEVROLET SONIC: 2012-2020
- For CHEVROLET SPARK: 2013-2021
- For CHEVROLET TRAX: 2013-2021

3. PRODUCT OVERVIEW

The fuel tank filler gas cap is a crucial component for sealing your vehicle's fuel tank, preventing fuel evaporation and maintaining proper fuel system pressure. This cap features a twist-on closure type and an attached tether to prevent loss.



Image 1: Top-down view of the fuel cap, highlighting the white inner sealing mechanism and the black outer cap with its tether.



Image 2: Angled view of the fuel cap, illustrating the design of the inner and outer components and the tether.



Image 3: Side profile of the fuel cap, displaying the black cap and the white threaded section.



Image 4: Alternate side view of the fuel cap, providing another perspective of its construction.

4. INSTALLATION

This fuel cap is designed for direct replacement. Follow these general steps for installation:

1. **Preparation:** Ensure your vehicle's engine is off and cool. Locate the fuel filler neck.
2. **Remove Old Cap:** Turn the old fuel cap counter-clockwise until it loosens and can be removed. If your old cap has a tether, carefully detach it from the vehicle's body or the filler neck.
3. **Attach Tether (if applicable):** If the new cap comes with a tether, secure the tether's attachment point to the designated spot near the fuel filler neck.
4. **Install New Cap:** Place the new fuel cap onto the fuel filler neck. Turn it clockwise until you hear several clicks, indicating it is securely tightened. Do not overtighten.
5. **Verify:** Ensure the cap is flush with the vehicle's body and feels secure.

Consult your vehicle's owner's manual for specific instructions regarding fuel cap replacement if needed.

5. OPERATION

To open the fuel cap for refueling, turn it counter-clockwise until it loosens and can be removed from the filler neck. To close, place the cap onto the filler neck and turn it clockwise until you hear a clicking sound, indicating it is properly sealed. The tether will keep the cap attached to the vehicle during refueling.

6. MAINTENANCE

The fuel cap requires minimal maintenance. Periodically inspect the rubber seal on the cap for cracks, tears, or signs of wear. A damaged seal can lead to fuel evaporation and trigger a 'Check Engine' light. Clean the cap and filler neck area with a damp cloth if dirt or debris accumulates.

7. TROUBLESHOOTING

- **'Check Engine' Light On:** If the 'Check Engine' light illuminates after fuel cap replacement, ensure the cap is securely tightened until it clicks. If the light persists, inspect the cap's seal for damage or consult a qualified mechanic.
- **Difficulty Tightening/Loosening:** Ensure there is no debris on the filler neck threads or the cap's threads. Clean if necessary. Do not force the cap.

8. SPECIFICATIONS

Feature	Detail
Brand	Generic
Model Number	95292260
OEM Part Number	9529-2260
Closure Type	Twist-On
Number of Items	1
Manufacturer	eGang Auto Parts

9. WARRANTY AND SUPPORT

This product comes with a one-year warranty. Returns are accepted within the specified period. For any issues or support inquiries regarding this product, please contact the seller, eGang Auto, through your purchase platform.