

Kircuit 5V AC/DC Adapter

Kircuit 5V AC/DC Adapter Instruction Manual

For HiBoost Dot F12G-3S-BTW, F12G-3S-BTWDOTT2, F12G3SBTW Home Cell Phone Signal Booster Kits

1. INTRODUCTION

This instruction manual provides essential information for the safe and effective use of your Kircuit 5V AC/DC Adapter. This adapter is designed to provide reliable power to compatible devices, specifically HiBoost Dot F12G-3S-BTW, F12G-3S-BTWDOTT2, and F12G3SBTW Home Cell Phone Signal Booster Kits.

Please read this manual thoroughly before using the product and retain it for future reference.

2. SAFETY INFORMATION

- **Electrical Safety:** Always ensure the adapter is plugged into a properly grounded and accessible wall outlet. Do not overload electrical outlets.
- **Compatibility:** Use this adapter only with devices that require a 5V DC input and have a compatible barrel plug connector. Using it with incompatible devices may cause damage.
- **Environment:** Do not expose the adapter to water, moisture, or extreme temperatures. Use indoors only.
- **Damage:** Do not use the adapter if the cord or plug is damaged. Do not attempt to open or repair the adapter. Contact support if damaged.
- **Children:** Keep the adapter out of reach of children.

3. PRODUCT OVERVIEW

3.1 Components

- **AC/DC Adapter Unit:** Converts AC wall power to 5V DC power.
- **Integrated Power Cord with Barrel Plug:** Connects the adapter to your compatible device.

3.2 Features

- **Wide Input Voltage:** Supports 100V-240V AC input, suitable for various regions.
- **Stable 5V DC Output:** Provides consistent 5V DC power to your device.
- **Built-in Protection:** Features Dynamic IC, Charger IC, and Power fuse for rapid charging and protection against overcharge.

- **Durable Design:** Constructed for reliable performance.



Image 1: The Kircuit 5V AC/DC Adapter, showing the main unit and the attached power cord with its barrel plug connector.



Image 2: The Kircuit 5V AC/DC Adapter, highlighting the approximate 6.5 ft (2 meter) cord length for flexible placement.

4. SETUP INSTRUCTIONS

1. **Verify Device Compatibility:** Ensure your device, such as the HiBoost Dot F12G-3S-BTW Signal Booster, requires a 5V DC input and has a compatible barrel plug power port.
2. **Connect to Device:** Carefully insert the barrel plug of the Kircuit adapter into the power input port of your compatible device. Ensure a snug and secure connection.
3. **Plug into Outlet:** Insert the 2-pin AC plug of the adapter into a standard 100-240V AC wall outlet.
4. **Power On:** Once connected, your device should receive power and begin operation according to its own instructions.



Image 3: The Kircuit 5V AC/DC Adapter shown in a typical setup, plugged into a power strip on a desk, ready to power a device.

5. OPERATING INSTRUCTIONS

The Kircuit 5V AC/DC Adapter operates automatically once connected to a power source and a compatible device. No user interaction is required for the adapter itself during operation.

- Ensure the adapter remains plugged in for continuous power to your device.
- To disconnect power, unplug the adapter from the wall outlet first, then disconnect the barrel plug from your device.

6. MAINTENANCE

- **Cleaning:** Wipe the adapter with a dry, soft cloth. Do not use liquid cleaners or solvents.
- **Storage:** Store the adapter in a cool, dry place when not in use. Avoid wrapping the cord too tightly around the adapter.
- **Inspection:** Periodically inspect the adapter and cord for any signs of damage, such as cuts, fraying, or bent

pins. Discontinue use if damage is found.

7. TROUBLESHOOTING

- **Device Not Powering On:**
 - Ensure the adapter is securely plugged into both the wall outlet and the device.
 - Try plugging the adapter into a different wall outlet to rule out an issue with the power source.
 - Verify that your device is indeed compatible with a 5V DC power input and the barrel plug type.
 - Check the adapter and cord for any visible damage.
- **Adapter Feels Warm:** It is normal for the adapter to feel slightly warm during operation. If it becomes excessively hot to the touch or emits a burning smell, immediately unplug it from the wall outlet and discontinue use.

8. SPECIFICATIONS

Brand	Kircuit
Manufacturer	Shenzhen Waweis Technology Co., Ltd
Input Voltage	100-240V AC
Output Voltage	5V DC
Connector Type	Barrel Plug
Main Power Connector	2-Pin (US Standard)
Compatible Devices	HiBoost Dot F12G-3S-BTW, F12G-3S-BTWDOTT2, F12G3SBTW Home Cell Phone Signal Booster Kits
Color	Black

9. WARRANTY INFORMATION

This Kircuit 5V AC/DC Adapter comes with a limited warranty. For specific warranty terms and conditions, please refer to the documentation provided at the time of purchase or contact your seller directly. The warranty typically covers manufacturing defects under normal use.

Damage resulting from misuse, accidents, unauthorized modifications, or improper installation is not covered.

10. SUPPORT

If you encounter any issues or have questions regarding your Kircuit 5V AC/DC Adapter that are not addressed in this manual, please contact the seller or manufacturer for assistance.

Please have your product model and purchase information ready when contacting support.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

<https://manuals.plus/asin/B0CH3F7V8K>

More documents and user manuals: <https://manuals.plus/>