MESTEK CGD05A

MESTEK CGD05A Gas Leak Detector User Manual

High Precision Natural Gas Detector with Triple Alarms

Introduction | Safety | Overview | Setup | Operation | Maintenance | Troubleshooting | Specifications | Warranty

1. Introduction

This manual provides detailed instructions for the safe and effective use of your MESTEK CGD05A Gas Leak Detector. This high-precision device is designed to detect various combustible gases, including methane, propane, natural gas, coal gas, LPG, LNG, butane, acetone, ammonia, ethanol, benzene, gasoline, IPA, and toluene. It features triple alarms (audible, visual, and vibration) and a clear digital and analog display for quick and accurate leak detection in residential and recreational vehicle (RV) environments.



Figure 1: MESTEK CGD05A Gas Leak Detector and accessories.

2. Safety Information

Please read and understand all safety warnings and instructions before operating the device. Failure to do so may result in injury or property damage.

- Always allow the detector to preheat for 30 seconds after powering on to ensure accurate readings.
- Do not use the device in environments with extremely high concentrations of gas, as this may pose an explosion risk.

- The detector is designed to identify potential gas leaks. It is not a substitute for professional gas leak detection services or safety equipment.
- If a gas leak is detected, immediately ventilate the area, turn off the gas supply if safe to do so, and contact emergency services or a qualified technician.
- Keep the device away from water and extreme temperatures.
- Do not attempt to disassemble or modify the detector.

3. Product Overview

3.1 Key Features

- **High-Precision Sensor:** Detects combustible gases with a 2-second response time.
- **Flexible Gooseneck Probe:** 11.3-inch flexible metal probe for reaching confined spaces.
- **Triple Alarm System:** Visual (LCD display), Audible (beeping), and Vibration alerts.
- **HD VA Reverse Color Screen:** 2.75-inch large display with ultra-clear digital and analog readings.
- **Wide Detection Range:** 50-50000 PPM / 0-100% LEL (based on methane).
- **Rechargeable Battery:** Built-in high-capacity battery with USB-C charging.
- **User-Friendly Functions:** Automatic Power-Off (APO), ZERO reset, Celsius/Fahrenheit conversion, PPM/%LEL conversion.

3.2 Components



Figure 2: Labeled diagram of the MESTEK CGD05A Gas Leak Detector.

1. **Probe:** Gas sensing element.
2. **Gooseneck:** Flexible arm for positioning the probe.
3. **VA Display:** High-definition screen showing readings and status.
4. **Power On/Off Button:** Turns the device on or off.
5. **APO (Automatic Shutdown On/Off) Button:** Activates or deactivates the auto power-off feature.
6. **°C/°F Button:** Toggles between Celsius and Fahrenheit temperature units.
7. **Sound Key:** Mutes or unmutes the audible alarm.
8. **PPM/%LEL Button:** Switches between Parts Per Million and %LEL (Lower Explosive Limit) display modes.
9. **ZERO Button:** Resets the sensor reading to zero in a clean air environment.
10. **Charging Port:** USB-C port for recharging the internal battery.

4. Setup

4.1 Charging the Device

Before first use, fully charge the MESTEK CGD05A detector using the provided USB-C charging cable.

- Connect the USB-C cable to the charging port on the device and the other end to a suitable USB power adapter (not included).
- The charging indicator light will show red while charging and turn green when fully charged.



Figure 3: USB-C Charging Port and Indicators.

4.2 Initial Power On and Calibration

The device requires a brief calibration period upon startup to ensure accuracy.

- Long press the Power On/Off button to turn on the device.
- The detector will automatically begin a 30-second preheating and calibration process. Ensure the device is in a clean, gas-free environment during this time.
- Once calibration is complete, the display will show '0' %LEL or PPM, indicating it is ready for use.

5. Operating Instructions

5.1 Gas Detection

To detect gas leaks, position the flexible gooseneck probe near the suspected leak source.

- Move the probe slowly around pipes, fittings, appliances, or any area where a gas leak is suspected.
- The device will display gas concentration levels on the VA screen.
- If the detected gas leakage value exceeds 10% LEL, the unit will activate its triple alarm system: audible beeps, vibration, and a 'HIGH' alarm displayed on the screen.
- The alarm will cease when the detected value drops below 10% LEL.



Figure 4: Triple Alarm System in action.

5.2 Understanding the Display

The HD VA reverse color screen provides clear information:

- **Digital Readout:** Shows the precise gas concentration in PPM or %LEL.
- **Analog Bar Graph:** Provides a visual representation of gas levels, from 'LOW' to 'HIGH'.
- **Temperature Display:** Shows ambient temperature in °C or °F.
- **Battery Indicator:** Displays current battery level.
- **Alarm Status:** Icons for audible, visual, and vibration alarms.



Figure 5: Clear and Easy-to-Read Display.

5.3 Button Functions

- **Power On/Off:** Long press to turn the device on or off.
- **APO:** Short press to toggle the 10-minute Automatic Power-Off function on or off. An icon on the screen indicates its status.
- **°C/°F:** Short press to switch the temperature display between Celsius and Fahrenheit.
- **Sound Key:** Short press to mute or unmute the audible alarm.
- **PPM/%LEL:** Short press to switch the gas concentration display between Parts Per Million (PPM) and %LEL.

- **ZERO:** Short press to perform a zero reset of the sensor in a clean air environment.



Figure 6: User-Friendly Design and Button Layout.

5.4 Application Scenarios

The MESTEK CGD05A is suitable for various gas leak detection applications:

- Residential homes (gas stoves, water heaters, gas pipelines).
- Recreational vehicles (RVs).
- HVAC systems.
- Industrial gas pipelines (for preliminary checks).



Figure 7: Diverse Application Scenarios.

5.5 Official Product Video

Your browser does not support the video tag.

Video 1: This video demonstrates the MESTEK CGD05A Gas Leak Detector's features, including its flexible gooseneck, quick response time, and application in various settings like gas stoves and pipelines. It also highlights the USB-C charging and key button functionalities.

6. Maintenance

- **Cleaning:** Wipe the device with a soft, dry cloth. Do not use abrasive cleaners or solvents.
- **Storage:** Store the detector in its provided storage bag in a cool, dry place away from direct sunlight and extreme temperatures.
- **Battery Care:** Recharge the battery regularly, even if the device is not in frequent use, to maintain battery health.

7. Troubleshooting

Device does not power on:

Ensure the battery is charged. Connect the USB-C charger and try again. If the issue persists, contact customer support.

Inaccurate or inconsistent readings:

Ensure the device completed its 30-second preheating and calibration in a clean air environment. Perform a ZERO reset in a known gas-free area. Check for any obstructions on the probe. If readings remain inconsistent, the sensor may need servicing.

Alarm does not sound/vibrate:

Check if the audible alarm is muted using the Sound Key. Ensure the battery has sufficient charge. If the issue continues, contact customer support.

Automatic Power-Off (APO) not working as expected:

Verify that the APO function is activated by pressing the APO button. The corresponding icon should be visible on the display.

8. Specifications

Feature	Detail
Brand	MESTEK
Model Number	CGD05A
Sensor Type	Ionization
Detection Range	50-50000 PPM / 0-100% LEL (based on methane)
Response Time	< 2 seconds
Preheating Time	30 seconds
Alarm Threshold	10% LEL
Alarm Methods	Audible, Visual (LCD), Vibration
Display	2.75-inch HD VA Reverse Color Screen (Digital & Analog)
Gooseneck Length	11.3 inches
Power Source	Built-in Rechargeable Battery (USB-C Charging)
Automatic Power-Off	10 minutes (toggleable)
Included Components	1×CGD05A Gas Leak Detector, 1×USB-C Charging Cable, 1×Storage Bag, 1×User Manual
Item Weight	14.4 ounces
Package Dimensions	8.58 x 4.41 x 1.93 inches

9. Warranty and Support

MESTEK provides a **36-month manufacturer warranty** for the CGD05A Gas Leak Detector. Additionally, lifetime customer support is available to ensure your satisfaction. For any inquiries, technical assistance, or warranty claims, please contact MESTEK customer service through the details provided on the product packaging or the official MESTEK website.

© 2023 MESTEK. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question