



[Manuals.plus](#) /

> [Senhozi](#) /

> Senhozi SE-0048-BG Brushed Gold 3-Hole Centerset Bathroom Sink Faucet Instruction Manual

## Senhozi SE-0048-BG

# Senhozi SE-0048-BG Brushed Gold 3-Hole Centerset Bathroom Sink Faucet

Instruction Manual

### 1. INTRODUCTION

This manual provides detailed instructions for the installation, operation, and maintenance of your Senhozi SE-0048-BG Brushed Gold 3-Hole Centerset Bathroom Sink Faucet. Please read all instructions carefully before beginning installation to ensure proper function and longevity of the product. Keep this manual for future reference.



*Image 1.1: The Senhozi SE-0048-BG Brushed Gold 3-Hole Centerset Bathroom Sink Faucet.*

## 2. SAFETY INFORMATION

- Always turn off the main water supply before installing or performing any maintenance on the faucet.
- Wear appropriate personal protective equipment, such as safety glasses, during installation.
- Ensure all connections are secure to prevent leaks. Do not overtighten.
- If you are unsure about any part of the installation process, consult a qualified plumber.
- Keep small parts away from children.

## 3. PACKAGE CONTENTS

Verify that all components are present before beginning installation:

- Faucet Body with 360-degree Swivel Spout

- Two Handle Assemblies
- Mounting Hardware
- Pop-up Drain Assembly
- Deck Plate
- Two 23.6-inch Hot and Cold Water Supply Hoses



*Image 3.1: All included components for the Senhozi SE-0048-BG faucet.*

#### 4. SPECIFICATIONS

Feature	Specification
Brand	Senhozi
Model Name	SE-0048-BG

Material	Stainless Steel (SUS304)
Finish Type	Brushed Gold
Mounting Type	Deck Mount
Hole Count	3
Number of Handles	2
Spout Design	Waterfall, 360° Swivel
Spout Height	5.4 Inches
Spout Reach	5 Inches
Item Weight	3.22 Pounds
Product Dimensions	6 x 3 x 7 inches
Hose Length	23.6 Inches
Recommended Uses	Bathroom
Installation Type	Centerset
Max Counter Top Thickness	1.06 Inches (27mm)
Min Counter Top Thickness	0.12 Inches (3mm)
Sink Hole Size	0.8 - 1.5 Inches (20-38mm)

 SENHOZI



Image 4.1: Faucet and pop-up drain dimensions.



Image 4.2: Sink hole and counter thickness requirements.

## 5. SETUP (INSTALLATION)

### 5.1 Pre-Installation Checks

- Ensure your sink has 3 holes with a centerset spacing of 4 inches (102mm).
- Verify that the sink hole size is between 0.8 and 1.5 inches (20-38mm).
- Confirm your countertop thickness is between 0.12 and 1.06 inches (3-27mm).

### 5.2 Recommended Tools (Not Included)

- Adjustable Wrench
- Phillips Head Screwdriver
- Plumber's Putty or Silicone Sealant
- Teflon Tape

- Basin Wrench (optional, for tight spaces)

### 5.3 Installation Steps

1. **Turn off Water Supply:** Locate the main water shut-off valve and turn off the water supply to your bathroom. Open the existing faucet to drain any remaining water.
2. **Remove Old Faucet:** Disconnect the water supply lines from the old faucet and remove any mounting nuts. Carefully lift and remove the old faucet. Clean the sink surface thoroughly.
3. **Install Deck Plate:** Place the rubber gasket on the underside of the deck plate. Position the deck plate over the faucet holes on the sink.
4. **Install Faucet Body:** Insert the faucet body through the holes in the deck plate and sink. Ensure the hot and cold indicators on the handles are correctly oriented.
5. **Secure Faucet:** From underneath the sink, place the rubber washer and metal washer onto the threaded shanks. Secure with the mounting nuts and tighten them evenly until the faucet is stable. Do not overtighten.
6. **Connect Water Supply Lines:** Attach the provided hot and cold water supply hoses to the corresponding inlets on the faucet body. Connect the other ends of the hoses to your hot and cold water supply valves. Use Teflon tape on threaded connections for a watertight seal.
7. **Install Pop-up Drain:** Follow the instructions provided with the pop-up drain assembly. Apply plumber's putty or silicone sealant around the drain flange before inserting it into the sink drain hole. Secure the drain body from underneath the sink.
8. **Test for Leaks:** Slowly turn on the main water supply. Check all connections for leaks. If leaks occur, tighten connections as needed. Operate the faucet to ensure proper water flow and temperature control.



*Image 5.1: Faucet installed on a sink.*

## 6. OPERATING INSTRUCTIONS

Your Senhozi faucet features a two-handle design for precise control over water temperature and flow, along with a 360-degree swivel waterfall spout.

- **Water Flow:** Turn the handles to open the water flow. The further you turn, the greater the flow.
- **Temperature Control:** The left handle controls hot water, and the right handle controls cold water. Mix the water by adjusting both handles to achieve your desired temperature.
- **Swivel Spout:** The spout can rotate 360 degrees, allowing for flexible use and easy cleaning of the sink basin.
- **Waterfall Design:** The unique waterfall spout provides a gentle and aesthetically pleasing water stream.



*Image 6.1: Faucet in operation, demonstrating water flow.*

SENHOZI



Image 6.2: Key features including waterfall design and swivel spout.

## 7. MAINTENANCE

Proper care and maintenance will help preserve the finish and functionality of your Senhozi faucet.

- **Cleaning:** Clean the faucet regularly with a soft cloth and mild soap. Rinse thoroughly with water and dry with a soft cloth to prevent water spots.
- **Avoid Harsh Cleaners:** Do not use abrasive cleaners, harsh chemicals, or polishes containing alcohol, ammonia, or bleach, as these can damage the brushed gold finish and internal components.
- **Material Durability:** The faucet body is constructed from SUS304 stainless steel, which offers excellent corrosion and rust resistance, ensuring durability against daily wear and tear.

## 8. TROUBLESHOOTING

Problem	Possible Cause	Solution
<b>Leaks from connections</b>	Loose connections, worn washers, improper sealing.	Ensure all connections are tightened properly. Apply Teflon tape to threaded connections. Check and replace any worn washers.
<b>Low Water Pressure</b>	Low household water pressure, clogged aerator, kinked supply lines.	Check your home's main water pressure. Remove and clean the aerator at the spout tip. Ensure supply lines are not kinked.
<b>Water not mixing properly (too hot/cold)</b>	Improper adjustment of hot/cold supply valves.	Adjust the hot and cold water supply valves under the sink to balance the flow.
<b>Difficulty turning handles</b>	Mineral buildup, worn cartridge.	Clean around the handle base. If the issue persists, the internal cartridge may need replacement (consult a plumber).

## 9. WARRANTY INFORMATION

Senhozi products are manufactured to high-quality standards. For specific warranty details regarding your SE-0048-BG faucet, please refer to the warranty card included with your purchase or contact Senhozi customer service directly. Keep your proof of purchase for warranty claims.

## 10. SUPPORT

If you encounter any issues with your Senhozi bathroom faucet or require assistance, please do not hesitate to contact our customer service team. We are committed to providing excellent service and support. For support, please visit the official Senhozi website or contact the seller directly through your purchase platform.