Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

PKPOWER ZT15-252040-CU, HLT-118A-2520400U

PKPOWER 25.2V AC DC Adapter Instruction Manual

For Hoover-1 My First 1st H1-MFH-BLU, H1-MFH-CMB, H1-MFH, H1MFH Models (ZT15-252040-CU, HLT-118A-2520400U)

1. Important Safety Instructions

Please read and understand all safety instructions before using this product. Failure to follow these instructions may result in electric shock, fire, or serious injury.

- **Indoor Use Only:** This adapter is designed for indoor use. Do not expose to rain, moisture, or extreme temperatures.
- **Proper Voltage:** Ensure the input voltage (100-240V AC) matches your power outlet.
- **Avoid Overloading:** Do not overload the adapter or the power outlet.
- **Cable Care:** Do not place heavy objects on the power cord. Avoid bending, twisting, or pulling the cord excessively.
- **Disconnect When Not in Use:** Unplug the adapter from the power outlet when not in use for extended periods.
- **No User Serviceable Parts:** Do not attempt to open or repair the adapter. Refer all servicing to qualified personnel.
- **Keep Away from Children:** Store the adapter out of reach of children.

2. Product Overview

The PKPOWER 25.2V AC DC Adapter is designed to provide reliable power for compatible Hoover-1 devices. It features robust protection mechanisms to ensure safe operation.



Figure 2.1: Front view of the PKPOWER 25.2V AC DC Adapter, showing the main unit and attached power cord.

Features:

- Input: 100-240V 50-60Hz
- Output: 25.2V, 2.0A
- OVP (Over Voltage Output Protection)
- OCP (Over Current Output Protection)
- SCP (Short Circuit Output Protection)

- CE / FCC / RoHS certified

Package Contents:

- 2 x AC Adapter (as per product listing)

3. Setup

Follow these steps to properly set up your PKPOWER AC DC Adapter:

1. **Verify Compatibility:** Ensure your device requires a 25.2V power input and is compatible with the adapter's connector type. This adapter is specifically designed for Hoover-1 My First 1st H1-MFH series devices.
2. **Connect to Device:** Insert the DC output plug of the adapter firmly into the power input port of your Hoover-1 device.
3. **Connect to Power Outlet:** Plug the AC input prongs of the adapter into a standard 100-240V AC wall outlet.
4. **Power On:** Once connected, your device should receive power. Refer to your device's manual for specific power-on procedures.



Figure 3.1: The adapter's dimensions are approximately 2.87 inches (length) x 1.57 inches (width) x 1.18 inches (height).

4. Operating Instructions

The PKPOWER AC DC Adapter operates automatically once connected to a power source and a compatible device. It provides a stable 25.2V DC output to power or charge your device.

- Ensure all connections are secure before operating.
- Monitor your device for proper charging or operation.
- If your device has a charging indicator, observe it to confirm power delivery.

5. Maintenance

Proper maintenance ensures the longevity and safe operation of your adapter.

- **Cleaning:** Disconnect the adapter from the power outlet and the device before cleaning. Use a soft, dry cloth to wipe the exterior. Do not use liquid cleaners or solvents.
- **Storage:** When not in use, store the adapter in a cool, dry place, away from direct sunlight and moisture. Avoid wrapping the cable too tightly around the adapter.
- **Inspection:** Periodically inspect the adapter and power cord for any signs of damage, such as cuts, fraying, or exposed wires. If damage is found, discontinue use immediately and replace the adapter.

6. Troubleshooting

If you encounter issues with your adapter, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Device not receiving power	Loose connection No power from outlet Incompatible device Damaged adapter/cable	Ensure all connections are secure. Test the outlet with another device. Verify device compatibility (25.2V input). Inspect adapter and cable for damage; replace if necessary.
Adapter feels hot	Normal operation (slight warmth) Overload or fault	A slight warmth is normal. If it's excessively hot, disconnect immediately. Ensure proper ventilation. If problem persists, discontinue use.
Device not charging	Device battery issue Adapter not providing sufficient current	Consult your device's manual for battery troubleshooting. Ensure the adapter's output current (2A) meets your device's requirements.

7. Specifications

Specification	Detail
Input Voltage	100-240V AC, 50/60Hz
Output Voltage	25.2V DC
Output Current	2 Amps
Connector Type	Auxiliary

Specification	Detail
Compatible Devices	Hoover-1 My First 1st H1-MFH-BLU, H1-MFH-CMB, H1-MFH, H1MFH models (21.6V 2.0Ah Li-ion Battery)
Product Dimensions	4 x 2 x 0.5 inches (approx. 10.16 x 5.08 x 1.27 cm)
Item Weight	4 ounces (approx. 113 grams)
Color	Black
Manufacturer	Shenzhen Sunshine Technological Co., Ltd

8. Warranty and Support

PKPOWER is committed to providing quality products and customer satisfaction.

For any questions, concerns, or technical assistance, please contact our customer service. Our friendly and reliable customer service team will respond to you within 24 hours.

Please refer to your purchase documentation or the PKPOWER official website for the most up-to-date warranty information and contact details.

© 2026 PKPOWER. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B0CHVMWBRM

More documents and user manuals: **https://manuals.plus/**