

[Manuals.plus](#) /

› [Losuudy](#) /

› Losuudy L-A1 Wired Backup Camera System Monitor Brackets User Manual

Losuudy L-A1

Losuudy L-A1 Wired Backup Camera System Monitor Brackets User Manual

Model: L-A1

INTRODUCTION

Thank you for choosing the Losuudy L-A1 Monitor Brackets. These brackets are designed to securely mount your monitor as part of a wired backup camera system, ensuring a stable and clear view. This manual provides detailed instructions for installation, operation, maintenance, and troubleshooting to help you get the most out of your product.

PACKAGE CONTENTS

Please check the package contents carefully. If any items are missing or damaged, contact customer support.

- Losuudy L-A1 Monitor Bracket(s)
- Mounting Hardware (screws, adhesive pads, etc.)
- User Manual



Image: Losuudy L-A1 Monitor Brackets and included components. This image displays the various parts of the monitor bracket system, including the main bracket, mounting base, and small hardware pieces like screws and washers.

SAFETY INFORMATION

Read all safety instructions before installation and use. Failure to follow these instructions may result in property damage or injury.

- Ensure the mounting surface is clean, dry, and strong enough to support the monitor and bracket.
- Do not obstruct the driver's view or interfere with vehicle controls.
- Use only the provided mounting hardware or suitable replacements.
- Keep small parts away from children.

SETUP AND INSTALLATION

The Losuudy L-A1 Monitor Brackets are designed for bracket mount installation. Follow these steps for secure mounting.

Step 1: Choose a Mounting Location

Select a location on your dashboard or windshield that provides an optimal viewing angle without obstructing your driving view or airbags. Ensure the surface is flat and clean.

Step 2: Assemble the Bracket

Connect the various parts of the bracket according to the desired angle and extension. Typically, this involves attaching the monitor plate to the arm and then to the base using screws or a locking mechanism.

Step 3: Mount the Bracket Base

Depending on your bracket type, secure the base using either adhesive or screws. For adhesive mounts, press

firmly for 30 seconds and allow sufficient time for the adhesive to cure before attaching the monitor. For screw mounts, mark the drill points, drill pilot holes, and secure the base with screws.



Image: Bracket base secured to dashboard. This image illustrates the bracket's base firmly attached to a vehicle's dashboard, demonstrating a stable mounting point.

Step 4: Attach the Monitor

Carefully slide or clip your monitor onto the bracket's monitor plate. Ensure it clicks into place or is securely fastened with any provided screws or clips. Adjust the viewing angle as needed.

Step 5: Connect the Monitor to the Backup Camera System

Once the monitor is securely mounted, connect the RCA video cable from your backup camera system to the monitor's RCA input. Connect the power cable to a suitable power source in your vehicle. Refer to your backup camera system's manual for specific wiring instructions.

OPERATING

The Losuudy L-A1 Monitor Brackets are passive accessories designed to hold your monitor. Their operation is limited to providing a stable platform. Once the monitor is installed and connected to your wired backup camera system, refer to your monitor's and camera system's user manuals for specific operating instructions, such as powering on, adjusting settings, and viewing the camera feed.

MAINTENANCE

Proper maintenance ensures the longevity and reliability of your monitor brackets.

- **Cleaning:** Use a soft, dry cloth to wipe down the brackets. Avoid abrasive cleaners or solvents that could damage the finish.

- **Inspection:** Periodically check all screws and connections to ensure they remain tight and secure. If the bracket feels loose, re-tighten the mounting hardware.
- **Environmental Conditions:** Avoid exposing the brackets to extreme temperatures or direct sunlight for prolonged periods, as this may affect material integrity.

TROUBLESHOOTING

If you encounter issues with your Losuudy L-A1 Monitor Brackets, refer to the following common problems and solutions.

- **Problem:** The monitor feels loose or wobbly on the bracket.
Solution: Ensure all screws connecting the monitor to the bracket and the bracket to its base are tightened securely. If using an adhesive mount, ensure the surface was clean and dry during installation and that the adhesive had sufficient time to cure.
- **Problem:** The bracket detaches from the mounting surface.
Solution: For adhesive mounts, the surface may not have been properly prepared or the adhesive may have failed. Clean the surface thoroughly and reapply with new, strong automotive-grade adhesive tape. For screw mounts, check if the screws are stripped or if the mounting surface is damaged.
- **Problem:** Difficulty adjusting the monitor angle.
Solution: Check for any locking mechanisms or adjustment knobs on the bracket. Loosen them slightly to adjust the angle, then tighten them firmly to secure the position.

SPECIFICATIONS

Brand	Losuudy
Model	L-A1
Product Dimensions	5.6 x 4.9 x 2.3 inches (14.2 x 12.4 x 5.8 cm)
Item Weight	8 ounces (227 grams)
Compatible Devices	Monitor
Installation Type	Bracket Mount

WARRANTY INFORMATION

Losuudy products are manufactured to high-quality standards. This product comes with a limited warranty against defects in materials and workmanship. Please retain your proof of purchase for warranty claims. For specific warranty terms and conditions, please refer to the warranty card included with your product or contact Losuudy customer support.

CUSTOMER SUPPORT

If you have any questions, require assistance with installation, or need troubleshooting help, please contact Losuudy customer support. Our team is available to provide guidance and resolve any issues you may encounter. For the most up-to-date contact information, please visit the official Losuudy website or refer to the packaging of your product.

