

[manuals.plus](#) /

- › [VEVOR](#) /
- › [VEVOR 1 Inch Double Curtain Rods \(36-72 Inches\) Instruction Manual](#)

VEVOR TW-R36/72

VEVOR 1 Inch Double Curtain Rods (36-72 Inches) Instruction Manual

Model: TW-R36/72 | Brand: VEVOR

1. INTRODUCTION

Thank you for choosing the VEVOR 1 Inch Double Curtain Rods. This product is designed to provide a versatile and durable solution for hanging curtains in various indoor spaces. Featuring an adjustable length and robust construction, it allows for dual curtain layering, offering enhanced light control and privacy. Please read this manual carefully before installation and use to ensure proper setup and long-lasting performance.

EXPANDABLE CURTAIN ROD

Easily fit different window sizes



Image: VEVOR Double Curtain Rods installed, highlighting adjustable length and suitability for various rooms.

2. PRODUCT FEATURES

- **Adjustable Length:** Easily extends from 36 inches to 72 inches, accommodating various window sizes in living rooms, bedrooms, bathrooms, kitchens, and offices.
- **Durable and Sturdy Construction:** Made from alloy steel with a 0.6mm thickness and 1 & 3/4" large diameter support, capable of holding up to 30 pounds without sagging. Features three fixed brackets (front, middle, rear) for enhanced stability.
- **Dual Rods for Layered Curtains:** Allows simultaneous hanging of sheer and blackout curtains, providing flexible control over light and privacy.
- **Modern Versatile Style:** Matte black finish with round finials seamlessly integrates with diverse decor styles.

SAY GOODBYE TO CURTAIN ROD SAGGING

Provide perfect support for heavy fabrics



Support 30lbs



1 & 3/4" Large Diameter



0.6mm Thickness

Image: The curtain rod demonstrating its robust construction and ability to support heavy fabrics without sagging.

3. PACKAGE CONTENTS

Ensure all components are present before beginning installation:

- 2 x Back Rods ($\Phi 19 \times L940 + \Phi 15.8 \times L952$)
- 2 x Front Rods ($\Phi 25.4 \times L940 + \Phi 22.2 \times L952$)
- 3 x Installation Brackets (3mm Thickness)
- 4 x Finials (2 Large + 2 Small)
- 7 x Cross Installation Screws (M4x30)
- 6 x Cross Round Head Bolts (M4x10, pre-installed on brackets)
- 7 x Anchors
- 1 x User Manual

3 x Installation Brackets

7 x Cross Installation Screws




6 x Cross Round Head Bolts



4 x Finals



7 x Anchors



Back Rods : **Φ15.8 mm(5/8") x L952**



Back Rods : **Φ19 mm(3/4") x L940**



Front Rods : **Φ22.2 mm(7/8") x L952**



Front Rods : **Φ25.4 mm(1") x L940**



Item Model Number : **TW-R36/72**

End Shape : **Cap Finial**

Effective Expandable Length : **36-72 in / 920-1830 mm**

Main Material : **Steeling**

Max. Total Load for 2 Bars : **30 lbs / 13.6 kg**

Net Weight : **3.09 lbs / 1.4 kg**

Product Dimensions : **74.8 x 6.5 x 3.35 in / 1900 x 165 x 85 mm**

2 x Front Rods (Φ25.4mm(1") x L940 + Φ22.2mm(7/8") x L952)

2 x Back Rods (Φ19mm(3/4") x L940 + Φ15.8mm(5/8") x L952)

4 x Finals (2 Large + 2 Small)

3 x Installation Brackets (3mm Thickness)

7 x Cross Installation Screws (M4x30)

1 x User Manual

6 x Cross Round Head Bolts (M4X10, pre-installed on brackets)

7 x Anchors

Image: Detailed view of all parts included in the VEVOR Double Curtain Rods package.

4. SETUP AND INSTALLATION

The VEVOR Double Curtain Rods are designed for straightforward installation. All necessary hardware is included. You will need a drill and a screwdriver for mounting.

Installation Steps:

- Measure and Mark:** Determine the desired height and width for your curtain rods. Place the brackets against the wall and mark the screw hole positions with a pencil. Ensure the marks are level.
- Drill Holes:** Use a drill to create pilot holes at the marked positions. If installing into drywall, insert the provided anchors into the pilot holes.
- Mount Brackets:** Securely attach the installation brackets to the wall using the provided screws. Ensure they are firmly fastened.
- Assemble Rods:** Connect the rod sections by twisting them together to achieve the desired length. For the double rod, ensure the larger diameter rod is for the front curtain and the smaller diameter rod is for the back curtain.

5. **Hang Curtains and Place Rods:** Slide your curtains onto the assembled rods. Carefully place the rods into the mounted brackets.
6. **Install Finials and Tighten Screws:** Attach the decorative finials to the ends of the rods. Tighten the cross installation screws on the brackets to prevent rod movement and ensure stability.



Image: Visual guide detailing the 6-step installation process for the curtain rods.

Installation Video Guide

Your browser does not support the video tag

Video: A detailed guide on installing 1 Inch Double Curtain Rods with End Caps, demonstrating each step of the assembly and mounting process.

5. USAGE AND FUNCTIONALITY

The VEVOR Double Curtain Rods offer versatile functionality to enhance your living space:

- **Layered Window Treatments:** Utilize the dual rods to hang both sheer curtains (on the inner rod) and blackout or decorative curtains (on the outer rod). This allows you to easily adjust

natural light, maintain privacy, and add aesthetic depth to your windows.

- **Versatile Curtain Compatibility:** The rods are suitable for various curtain types, including grommet curtains, strap curtains, rod pocket curtains, and other decorative curtains.

ENHANCED PRIVACY AND LIGHT CONTROL

Dual rod design for layered look



Image: Illustrates the dual functionality of the rods for enhanced privacy and light control with layered curtains.



Image: Displays the modern design and versatility of the rods with different curtain hanging methods.

6. MAINTENANCE

To ensure the longevity and appearance of your VEVOR Double Curtain Rods, follow these simple maintenance guidelines:

- **Regular Cleaning:** Wipe the rods and finials with a soft, dry cloth to remove dust and fingerprints. Avoid abrasive cleaners or harsh chemicals, as these can damage the finish.
- **Check Fastenings:** Periodically inspect the mounting screws and bracket connections to ensure they remain tight. Re-tighten if necessary to maintain stability and prevent sagging.
- **Avoid Overloading:** Do not exceed the maximum weight capacity of 30 pounds to prevent damage to the rods or mounting hardware.

7. TROUBLESHOOTING

If you encounter any issues with your curtain rods, refer to the following common troubleshooting tips:

- **Rods are Sagging:**

Solution: Ensure all three brackets (front, middle, rear) are properly installed and securely fastened. Check that the rods are not overloaded beyond the 30-pound capacity. Verify that the cross installation screws on the brackets are tightened to prevent slippage.

- **Rods are Not Stable:**

Solution: Confirm that the mounting screws are firmly in place and that the anchors (if used) are correctly installed in drywall. Ensure the rod sections are fully twisted and connected.

- **Difficulty Adjusting Length:**

Solution: The rods are designed to twist together for length adjustment. If stiff, gently twist while applying slight pressure. Ensure no debris is obstructing the telescoping mechanism.

8. SPECIFICATIONS

Attribute	Detail
Brand	VEVOR
Model Number	TW-R36/72
Color	Black
Product Dimensions	74.8" L x 6.5" W
Material	Alloy Steel
Mounting Type	Wall Mounted
Item Weight	3.09 Pounds
Adjustable Length	36-72 inches (920-1830 mm)
Rod Diameter (Front)	1 inch (Φ 25.4mm) and 7/8 inch (Φ 22.2mm)
Rod Diameter (Back)	3/4 inch (Φ 19mm) and 5/8 inch (Φ 15.8mm)
Thickness	0.6mm
Max. Load Capacity	30 lbs / 13.6 kg
UPC	197988624714

9. WARRANTY AND SUPPORT

For warranty information or technical support, please refer to the product packaging or contact VEVOR customer service directly. Keep your purchase receipt for any warranty claims.

