

Blooy 124-12508

Blooy 124-12508 Needle Driving Rod Instruction Manual

For Juki MO-3300 Industrial Overlock Sewing Machine

1. INTRODUCTION

This manual provides essential information for the proper installation, operation, and maintenance of the Blooy 124-12508 Needle Driving Rod. This component is specifically designed as a replacement part for the Juki MO-3300 Industrial Overlock Sewing Machine.

The needle driving rod is a critical part of the sewing machine's mechanism, responsible for transmitting motion to the needle bar, ensuring precise and consistent needle movement during the sewing process. This particular rod is constructed from durable copper material, ensuring longevity and reliable performance.

2. PRODUCT OVERVIEW

The Blooy 124-12508 Needle Driving Rod is a precision-engineered component. Below are images illustrating the product's design and key features.



Needle Driving Rod

Fit JUKI MO-3300 Overlock Machine



Figure 1: General view of the Blooy 124-12508 Needle Driving Rod, showing its overall structure and connection points. This rod is designed for the Juki MO-3300 Overlock Machine.



JSEWNG ACCESSORIES

Figure 2: An alternative view of the needle driving rod, highlighting its copper construction and smooth finish.



Figure 3: The needle driving rod displaying its approximate length of 110 mm, a key dimension for compatibility.

3. SETUP AND INSTALLATION

Replacing a needle driving rod requires careful attention to detail. If you are unfamiliar with sewing machine mechanics, it is recommended to consult a qualified technician or refer to your Juki MO-3300 machine's official service manual.

Installation Steps:

1. **Safety First:** Always ensure the sewing machine is powered off and unplugged from the electrical outlet before attempting any installation or maintenance.
2. **Access the Mechanism:** Carefully open the necessary covers or panels of your Juki MO-3300 machine to gain access to the needle driving mechanism. Refer to your machine's service manual for specific instructions on accessing this area.
3. **Remove Old Rod:** Loosen any screws or fasteners securing the old needle driving rod. Gently remove the old rod, noting its orientation and connection points.
4. **Install New Rod:** Position the Blooy 124-12508 Needle Driving Rod in the correct orientation, aligning it with the connecting components. Ensure all pivot points and connections are properly seated.
5. **Secure Fasteners:** Tighten all screws and fasteners securely, but do not overtighten, as this can damage the components.
6. **Test Movement:** Before reassembling the machine, manually rotate the handwheel to ensure the needle driving rod moves freely and smoothly without any obstruction or binding.
7. **Reassemble:** Replace all covers and panels that were removed.

4. OPERATING CONSIDERATIONS

Once correctly installed, the Blooy 124-12508 Needle Driving Rod will function seamlessly within your Juki MO-3300 Industrial Overlock Sewing Machine. Its primary role is to ensure the consistent vertical movement of the needle, which is crucial for forming proper stitches.

No specific operational adjustments are typically required for the needle driving rod itself, as its function is mechanical. Proper operation relies entirely on correct installation and the overall good working condition of the sewing machine.

5. MAINTENANCE

Regular maintenance helps prolong the life of your sewing machine components, including the needle driving rod.

Maintenance Tips:

- **Cleaning:** Periodically inspect the needle driving rod and its surrounding mechanism for lint, dust, and thread fragments. Use a soft brush or compressed air to clean these areas.
- **Lubrication:** Refer to your Juki MO-3300 machine's service manual for specific lubrication points and recommended lubricants. Apply a small amount of appropriate sewing machine oil to pivot points as directed. Avoid over-lubrication.
- **Inspection:** Regularly check the rod for any signs of wear, bending, or damage. Ensure all fasteners remain tight. If any damage is observed, replace the part promptly to prevent further machine issues.

6. TROUBLESHOOTING

If you experience issues after installing the new needle driving rod, consider the following troubleshooting steps:

- **Improper Needle Movement:** If the needle is not moving smoothly or is binding, re-check the installation of the rod. Ensure it is correctly aligned and all fasteners are secure. Verify that no other components are obstructing its movement.
- **Unusual Noise:** A new or improperly installed rod might cause unusual noises. Check for loose connections or parts rubbing against each other. Ensure adequate lubrication as per the machine's manual.
- **Needle Breakage:** Frequent needle breakage can sometimes be related to an improperly functioning needle driving mechanism. Ensure the rod is not bent and is moving the needle precisely. Check for proper needle insertion and type.
- **Stitch Irregularities:** If stitches are inconsistent or skipped, verify the needle driving rod's smooth operation. However, stitch issues can also stem from many other factors, so consult your machine's manual for comprehensive troubleshooting.

If problems persist, it is advisable to seek assistance from a professional sewing machine technician.

7. SPECIFICATIONS

Feature	Detail
Part Number	124-12508
Compatibility	Juki MO-3300 Industrial Overlock Sewing Machine
Material	Copper
Product Dimensions	4.33 x 1.18 x 0.2 inches (approximately 110 mm length)
Item Weight	2.47 ounces

Manufacturer	Blooy
--------------	-------

8. WARRANTY AND SUPPORT

For information regarding warranty coverage or technical support for your Blooy 124-12508 Needle Driving Rod, please contact the manufacturer directly or the retailer from whom the product was purchased. Ensure you have your purchase details and the product's part number available when seeking support.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Email

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Details

Submit question