

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

- › [Mist](#) /
- › [Mist Filtered Shower Head \(Model MSS085\) User Manual](#)

## Mist MSS085

# Mist Filtered Shower Head User Manual

Model: MSS085

## INTRODUCTION

---

The Mist Filtered Shower Head (Model MSS085) is designed to enhance your showering experience by filtering hard water and removing impurities. This shower head features 5 distinct spray modes and advanced filtration technology to improve the condition of your skin, hair, and nails by reducing chlorine and heavy metals.



*Image: The Mist Filtered Shower Head in chrome finish, showcasing its sleek design.*

## PRODUCT FEATURES

- **Enhanced Beauty:** Designed to strengthen hair follicles, soothe eczema and scalp irritation, reduce dandruff and shedding, and leave skin soft while rejuvenating nails. Suitable for all family members.
- **Advanced Water Filtration:** Utilizes KDF (Kinetic Degradation Fluxion) and GAC (Granular Activated Carbon) filtration to remove chlorine, heavy metals, and other impurities. It also helps balance pH and soften hard water.
- **High Pressure Comfort:** Engineered with pressure-boosting technology, delivering up to 2.5 Gallons Per Minute (GPM) at 20–100 psi for an efficient and spa-like shower experience.
- **5 Spray Modes:** Offers a choice of gentle mist, full coverage, invigorating spray, targeted spray+massage, or a mixed flow rain+massage to customize your shower.
- **Durable Construction:** Built from durable, lead-free materials with an adjustable metal swivel ball for optimal shower angle.



Image: A cutaway diagram showing the 15-stage filtration layers, including KDF-55, Activated Carbon, Calcium Sulfite, and Vitamin C Balls, designed to reduce water toxins, chlorine, bad odor, sediments, rust, and impurities.

## PACKAGE CONTENTS

Please verify that all components are present in the package:

- Mist Filtered Shower Head (with built-in filter cartridge)
- Teflon Tape
- O-rings (2)
- Instruction Manual

## SETUP AND INSTALLATION

The Mist Filtered Shower Head is designed for quick and easy installation, typically taking only a few minutes without the need for a plumber. It features a universal G1/2" thread, compatible with all standard US shower arms.

1. **Prepare the Shower Arm:** Ensure your existing shower arm is clean and free of debris.
2. **Apply Teflon Tape:** Wrap the provided Teflon tape clockwise around the threads of your shower arm. Apply 3-5 layers for a secure, leak-free seal.

3. **Attach the Shower Head:** Carefully screw the Mist Filtered Shower Head onto the taped shower arm threads. Hand-tighten until snug. Do not overtighten, as this can damage the connections.
4. **Check for Leaks:** Turn on the water supply and check for any leaks around the connection. If leaks occur, tighten slightly or reapply Teflon tape.



Image: A visual guide demonstrating the three simple steps for installing the shower head: 1. Clean the old shower spout. 2. Apply Teflon Tape. 3. Screw on the new head.

## OPERATING INSTRUCTIONS

The Mist Filtered Shower Head offers 5 distinct spray modes to personalize your showering experience. To change the spray mode, simply rotate the spray face of the shower head clockwise or counter-clockwise until you reach your desired setting.

- **Gentle Mist:** A fine, soft spray for a relaxing experience.
- **Full Coverage:** A standard, wide spray for thorough rinsing.
- **Invigorating Spray:** A more focused, powerful spray.
- **Targeted Spray + Massage:** Combines a focused spray with a pulsating massage function.
- **Mixed Flow Rain + Massage:** A blend of full coverage rain and a gentle massage.



*Image: An illustration detailing the five available spray settings: Rain, Spray, Rain + Massage, Spray + Massage, and Mist, each with a visual representation of its water flow.*

## MAINTENANCE

### Filter Replacement

The built-in filter cartridge has a capacity of approximately 12,000 gallons of water or lasts for about six months, whichever comes first. Regular replacement ensures optimal filtration performance.

1. Turn off the water supply to the shower.
2. Unscrew the shower head from the shower arm.
3. Carefully separate the shower head components to access the filter cartridge.
4. Remove the old filter cartridge and dispose of it properly.
5. Insert a new Mist replacement filter cartridge, ensuring it is seated correctly.
6. Reassemble the shower head, ensuring all seals and O-rings are in place.
7. Screw the shower head back onto the shower arm, applying new Teflon tape if necessary.
8. Turn on the water supply and check for leaks.

## Cleaning the Shower Head

To maintain optimal water flow and prevent mineral buildup, regularly clean the shower head nozzles. Use a soft brush or cloth and a mild cleaning solution. Avoid using abrasive cleaners or harsh chemicals, as these can damage the finish and materials.

## TROUBLESHOOTING

- **Low Water Pressure:**
  - Ensure the filter cartridge is not clogged. If it's nearing its replacement interval (6 months or 12,000 gallons), replace it.
  - Check your household water pressure.
- **Leaks from Connection:**
  - Ensure the shower head is securely hand-tightened onto the shower arm.
  - Verify that Teflon tape was applied correctly and sufficiently (3-5 layers). Reapply if necessary.
  - Check the O-rings for any damage or improper seating.
- **Reduced Filtration Effectiveness:**
  - The filter cartridge has a limited lifespan. Replace the filter if it has been in use for 6 months or filtered 12,000 gallons of water.

## SPECIFICATIONS

<b>Brand</b>	Mist
<b>Model Number</b>	MSS085
<b>Style</b>	5-mode
<b>Shape</b>	Round
<b>Material</b>	Chromium
<b>Finish Type</b>	Glossy
<b>Installation Type</b>	Wall Mounted
<b>Flow Rate</b>	2.5 Gallons Per Minute (GPM)
<b>Color</b>	Chrome
<b>Product Dimensions</b>	6.54"L x 4.13"W
<b>Number of Settings</b>	5
<b>Item Weight</b>	1.3 pounds
<b>Maximum Pressure</b>	100 psi
<b>Operating Temperature</b>	40-175°F
<b>Operating Pressure</b>	20-100 psi
<b>Filter Capacity</b>	12,000 gallons or 6 months

**Capacity**

12,000 gallons or replace every 6 months

**Installation**

Quick and easy installation process

**Compatibility**

Fits standard 1/2-inch thread valves

Not compatible with handheld shower arms

**Package Contents**

Mist filtering shower head, Filter cartridge, Teflon tape, Instruction manual, O-ring (2)

(Additional replacement filters sold separately)

Operating  
Temperature:  
40-175°F

Operating  
Pressure:  
20-100 psi

Flow  
Rate:  
2.5 GPM



*Image: An infographic summarizing key specifications including filter capacity (12,000 gallons or 6 months), quick installation, compatibility with standard 1/2-inch thread valves, and package contents. It also lists operating temperature (40-175°F), operating pressure (20-100 psi), and flow rate (2.5 GPM).*

## WARRANTY AND SUPPORT

Mist products are backed by reliable customer support. For any questions, concerns, or assistance, please reach out to us through Amazon. Our support team aims to provide responses within 24 hours.