

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [MONDAWE](#) /

› [MONDAWE MO-DT95028NS Bar Sink Faucet Instruction Manual](#)

MONDAWE MO-DT95028NS

MONDAWE MO-DT95028NS Bar Sink Faucet Instruction Manual

Model: MO-DT95028NS | Brand: MONDAWE

INTRODUCTION

This manual provides detailed instructions for the installation, operation, and maintenance of your MONDAWE MO-DT95028NS Bar Sink Faucet. Please read this manual thoroughly before installation and retain it for future reference. Proper installation and care will ensure optimal performance and longevity of your faucet.



Image: The MONDAWE MO-DT95028NS Bar Sink Faucet in brushed nickel finish, showcasing its single-handle design and curved spout.

SAFETY INFORMATION

- Always turn off the main water supply before beginning any installation or repair work.
- Wear appropriate personal protective equipment, such as safety glasses and gloves.
- If you are unsure about any part of the installation process, consult a qualified plumber.
- Ensure all connections are tight to prevent leaks, but do not overtighten.

- Keep small parts away from children.

PACKAGE CONTENTS

Verify that all components are present before beginning installation:



Image: Diagram showing all included components: (1) Bathroom Faucet, (2) Stainless Steel Deck Plate, (3) 2 Water Supply Hoses, (4) Customized Packaging Box.

- 1 x MONDAWE Bar Sink Faucet (Brushed Nickel)
- 1 x Single Handle
- 1 x Deck Plate/Escutcheon (for 3-hole installation)
- 2 x Water Supply Hoses (Hot & Cold)
- Mounting Hardware (nuts, washers, O-rings, Allen wrench)
- Instruction Manual

SPECIFICATIONS

Brand	MONDAWE
Model Name	MO-DT95028NS
Material	Stainless Steel
Finish Type	Brushed Nickel
Installation Type	Single Hole (compatible with 3-hole using deck plate)
Number of Handles	1
Maximum Flow Rate	1.2 Gallons Per Minute
Spout Height	8.03 inches (from base to aerator)
Spout Reach	6.02 inches (from faucet body to aerator)
Product Dimensions	9.64 x 2.36 x 11.57 inches
Item Weight	4.19 pounds
Durability	Rust Resistant, Scratch Resistant, Stain Resistant, Mineral Build-Up Resistant
Certification	cUPC Certified

DIMENSION



Image: Detailed diagram illustrating the dimensions of the faucet, including spout height, spout reach, and mounting hole size (1.38 inches).

SETUP AND INSTALLATION

This faucet is designed for easy installation in either a 1-hole or 3-hole configuration. A deck plate is included for 3-hole installations.

Tools You May Need (Not Included):

- Adjustable Wrench
- Phillips Head Screwdriver
- Plumber's Putty or Silicone Sealant
- Flashlight
- Bucket (for catching drips)

Installation Steps:

- 1. Prepare the Sink:** Turn off the hot and cold water supply lines at the shut-off valves under the sink. Open the existing faucet to drain any remaining water. Disconnect and remove the old faucet if applicable. Clean the sink surface around the faucet holes.
- 2. Install Deck Plate (for 3-hole sinks):** If your sink has three holes, place the included stainless steel deck plate over the holes. Ensure the gasket is properly seated underneath the deck plate to prevent water leakage.
- 3. Mount the Faucet:** Insert the faucet body through the center hole (or the center hole of the deck plate). Ensure the faucet is oriented correctly. From underneath the sink, slide the rubber washer, metal washer, and mounting nut onto the threaded shank of the faucet. Hand-tighten the mounting nut.
- 4. Secure the Faucet:** Use the provided Allen wrench to tighten the two screws on the mounting nut. This will secure the faucet firmly to the sink or countertop. Do not overtighten.
- 5. Connect Water Supply Lines:** Attach the hot and cold water supply hoses (included) to the corresponding inlets on the faucet body. The hoses are typically marked or color-coded (red for hot, blue for cold). Connect the other ends of the hoses to your hot and cold water supply valves. Use an adjustable wrench to tighten connections, ensuring a leak-free seal.
- 6. Test for Leaks:** Slowly turn on the hot and cold water supply valves. Check all connections for leaks. If any leaks are detected, tighten the connections slightly until the leak stops.
- 7. Flush the Faucet:** Remove the aerator from the spout. Turn on the faucet and let the water run for a few minutes to flush out any debris from the water lines. Turn off the faucet, reattach the aerator, and test the water flow and temperature.



Image: The MONDAWE faucet installed in a sink, with water flowing from the spout, demonstrating its functionality.

OPERATING INSTRUCTIONS

Your MONDAWE faucet features a single-handle design for convenient control of water flow and temperature.

- **Water Flow Control:** Lift the handle upwards to increase water flow. Push the handle downwards to decrease or shut off water flow.
- **Temperature Control:** Move the handle to the left for hot water and to the right for cold water. Adjust the handle position between hot and cold to achieve your desired water temperature.
- **360° Swivel Spout:** The high-arc spout can rotate 360 degrees, providing flexibility for various sink tasks and making it suitable for both single and double sinks.

360° SWIVEL AND SINGLE HANDLE

High arc 360° rotating nozzle provides all-round cleaning



Image: The faucet demonstrating its 360-degree swivel capability, highlighting its versatility for various uses.

MAINTENANCE

Regular cleaning and maintenance will help preserve the finish and functionality of your faucet.

- **Cleaning the Finish:** Clean the faucet regularly with a soft cloth and mild soap. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the brushed nickel finish. Rinse thoroughly with water and dry with a soft cloth to prevent water spots.
- **Cleaning the Aerator:** If water flow becomes restricted or irregular, the aerator may be clogged. Unscrew the aerator from the tip of the spout. Rinse any debris from the screen under running water. For stubborn mineral deposits, soak the aerator in a solution of equal parts white vinegar and water. Reattach the aerator once clean. The faucet features easy-clean silicone nozzles for simplified maintenance.
- **Leak Prevention:** The faucet is equipped with a robust ceramic valve core and an integrated rubber ring designed for lasting durability and drip resistance. If a leak occurs, check connections and ensure they are properly tightened.

NIPPER BUBLER



Image: Close-up of the faucet's aerator, highlighting the easy-clean silicone nozzles and smooth water output.

TROUBLESHOOTING

Problem	Possible Cause	Solution
No Water Flow or Low Flow	<ul style="list-style-type: none">Water supply valves are closed.Aerator is clogged.Supply lines are kinked or clogged.	<ul style="list-style-type: none">Open water supply valves fully.Clean or replace the aerator (see Maintenance section).Check supply lines for kinks or blockages.

Problem	Possible Cause	Solution
Leaking from Faucet Base	<ul style="list-style-type: none"> Mounting nut is loose. Gasket not properly seated. 	<ul style="list-style-type: none"> Tighten the mounting nut underneath the sink. Ensure the gasket between the faucet/deck plate and sink is correctly positioned.
Leaking from Spout	<ul style="list-style-type: none"> Ceramic cartridge issue. 	<ul style="list-style-type: none"> Contact customer support for assistance or replacement parts.
Improper Hot/Cold Water Mix	<ul style="list-style-type: none"> Hot and cold supply lines reversed. 	<ul style="list-style-type: none"> Turn off water supply and reverse the hot and cold supply line connections.

WARRANTY INFORMATION

The MONDAWE MO-DT95028NS Bar Sink Faucet comes with a **1 Year Limited Warranty** from the date of purchase. This warranty covers manufacturing defects in materials and workmanship under normal use. It does not cover damage resulting from improper installation, misuse, abuse, accident, or normal wear and tear.

Please retain your proof of purchase for warranty claims.

CUSTOMER SUPPORT

If you have any questions, require assistance with installation, or need to make a warranty claim, please contact MONDAWE customer support:

- Website:** [Visit the MONDAWE Store on Amazon](#)
- Refer to the contact information provided in your product packaging for direct support channels.