

Swiss Madison SM-25-BFANG04WH

Swiss Madison Angers Wall Hung Toilet Bundle

Model: SM-25-BFANG04WH

INTRODUCTION

This manual provides essential instructions for the installation, operation, and maintenance of your Swiss Madison Angers Wall Hung Toilet Bundle. Please read all instructions carefully before beginning installation and retain this manual for future reference. Proper installation and care will ensure optimal performance and longevity of your product.

SAFETY INFORMATION

- Always wear appropriate personal protective equipment (PPE) during installation, including safety glasses and gloves.
- Ensure all water supply lines are shut off before beginning any work.
- If you are unsure about any part of the installation process, consult a qualified plumber.
- Do not overtighten connections, as this may cause damage to the product or plumbing.
- The steel frame is rated for 500 lbs. Do not exceed this weight limit.

PACKAGE CONTENTS

Verify that all components are present before beginning installation.



Image: Kit Components. This diagram illustrates the main parts included in the Angers Wall Hung Toilet Bundle: the in-wall tank carrier system, the wall-hung toilet bowl, and the dual-flush actuation plate.

- Wall-Hung Toilet Bowl (Ceramic, Glossy White)
- Slymm Soft-Close, Quick-Release Toilet Seat (Plastic)

- In-Wall Tank Carrier System (Steel Frame)
- Dual-Flush Actuation Plate
- Installation Hardware

SPECIFICATIONS

Feature	Specification
Model Number	SM-25-BFANG04WH
Color	White
Product Dimensions (D x W x H)	22" x 14" x 15.3"
Material	Ceramic (Bowl), Plastic (Seat)
Item Weight	103 pounds
Installation Method	Wall Mount
Flush Type	Dual-Flush (0.8/1.6 Gallons Per Flush)
Bowl Shape	Elongated
Adjustable Height Range	15" to 22" from floor
Frame Weight Rating	500 lbs



Image: Space Saver. This image highlights the compact, space-saving design of the wall-hung toilet compared to a traditional floor-mounted toilet.

SETUP AND INSTALLATION

This section outlines the general steps for installing your wall-hung toilet bundle. Professional installation is recommended.

1. **Prepare the Wall:** Ensure the wall structure is suitable for a wall-hung toilet carrier system. The carrier system is designed for installation on 2x4 studs for residential walls. Reinforcement may be required.
2. **Install the In-Wall Tank Carrier:** Mount the steel frame carrier system securely within the wall according to the manufacturer's instructions for the specific carrier model. Connect the water supply and drain lines to the in-wall tank.
3. **Set Bowl Height:** The carrier system allows for adjustable bowl height, typically from 15 to 22 inches from the finished floor. Adjust the support bolts to your desired height before finishing the wall.
4. **Finish the Wall:** Once the carrier is installed and tested, finish the wall around the carrier and plumbing connections. Ensure access points for the actuation plate and maintenance are clear.
5. **Mount the Toilet Bowl:** Attach the ceramic toilet bowl to the support bolts extending from the wall. Secure it firmly using the provided hardware.

- 6. **Install the Toilet Seat:** Attach the Slymm soft-close, quick-release toilet seat to the bowl. Follow the seat's specific instructions for proper alignment and secure fastening.
- 7. **Install the Actuation Plate:** Connect and install the dual-flush actuation plate to the front of the in-wall tank. This plate provides access to the flush mechanism and inner tank.
- 8. **Test for Leaks:** Turn on the water supply and check all connections for leaks. Perform several test flushes to ensure proper operation.

OPERATING INSTRUCTIONS

Your Angers Wall Hung Toilet features a dual-flush system for water conservation.

- **Partial Flush (0.8 GPF):** Press the smaller button on the actuation plate for a reduced water flush, suitable for liquid waste.
- **Full Flush (1.6 GPF):** Press the larger button on the actuation plate for a full water flush, suitable for solid waste.

MAINTENANCE

- **Cleaning the Bowl:** Use a soft cloth and a non-abrasive toilet cleaner. Avoid harsh chemicals or abrasive scrubbers that can damage the ceramic surface.
- **Cleaning the Seat:** The Slymm soft-close, quick-release seat can be easily removed for thorough cleaning. Use mild soap and water. Do not use strong chemical cleaners.
- **Accessing the Inner Tank:** The actuation plate can be removed for easy access to the inner tank and shut-off valve for maintenance or repairs. Refer to the carrier system's specific manual for detailed instructions on removing the plate and accessing internal components.
- **Regular Inspection:** Periodically check for any leaks around the connections and ensure the flush mechanism operates smoothly.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Toilet not flushing or weak flush	Low water pressure; obstruction in flush mechanism; issue with actuation plate connection.	Check water supply valve; remove actuation plate to inspect flush mechanism; ensure actuation plate is correctly installed.
Continuous running water	Flapper or fill valve issue; debris in valve.	Remove actuation plate and inspect the flapper and fill valve inside the tank. Clean any debris. Adjust or replace components as needed.
Leaks around the bowl or connections	Loose connections; damaged seals; improper installation.	Tighten connections carefully; inspect and replace seals if damaged. If leaks persist, professional assistance may be required.
Toilet seat does not close softly	Soft-close mechanism malfunction; debris.	Clean hinges; ensure no obstructions. If mechanism is faulty, contact customer support for replacement parts.

WARRANTY AND SUPPORT

For warranty information or technical assistance, please contact Swiss Madison customer support. Keep your purchase

receipt and model number (SM-25-BFANG04WH) handy when contacting support.

Customer Support: [Visit the Swiss Madison Store on Amazon](#)

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question