

CNCEST ZTCYT-2224

CNCEST 1x30 Inch Belt Sander User Manual

Model: ZTCYT-2224

1. IMPORTANT SAFETY INSTRUCTIONS

Always observe basic safety precautions when operating this belt sander to reduce the risk of fire, electric shock, and serious personal injury. Read all instructions carefully before use.

- **Personal Protective Equipment (PPE):** Always wear safety glasses or goggles, hearing protection, and a dust mask. Use appropriate gloves when handling materials.
- **Work Area Safety:** Keep your work area clean and well-lit. Cluttered or dark areas invite accidents. Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases, or dust.
- **Electrical Safety:** Do not expose power tools to rain or wet conditions. Water entering a power tool will increase the risk of electric shock. Do not abuse the cord. Never use the cord for carrying, pulling, or unplugging the power tool. Keep cord away from heat, oil, sharp edges, or moving parts.
- **Tool Use and Care:** Do not force the power tool. Use the correct power tool for your application. It will do the job better and safer at the rate for which it was designed. Disconnect the plug from the power source before making any adjustments, changing accessories, or storing power tools.
- **Maintenance:** Maintain power tools and accessories. Check for misalignment or binding of moving parts, breakage of parts, and any other condition that may affect the power tool's operation. If damaged, have the power tool repaired before use.

2. PRODUCT OVERVIEW

The CNCEST 1x30 Inch Belt Sander is a versatile and high-precision machine designed for various grinding and polishing tasks. Its robust construction and adjustable features make it suitable for a wide range of applications.

Key Features:

- **Multi-Function Sander:** CNC machined for high precision, suitable for metal processing, jewelry making, plastic resin art, acrylic polishing, and tool making.
- **Easy Sanding:** Supports both vertical and horizontal sanding configurations for convenience. Features a 3.9-inch

wheel for concave surfaces and larger arcs, and a flat grinding frame for large areas or complex shapes.

- **Adjustable Angles:** The worktable can be adjusted at multiple angles. The machine body can rotate 90° for horizontal sanding, allowing easier access for tubes or pipes.
- **Outstanding Performance:** Equipped with a 550W DC brushless motor, offering high speed (up to 5000rpm) and high torque for efficient task completion with low noise.
- **High Quality Material:** Constructed from premium stainless steel and Al-alloy materials with a galvanizing process, ensuring stable performance, strength, wear-resistance, and a thickened base for stability during high-speed operation.




Figure 2.1: The CNCEST 1x30 Inch Belt Sander, showcasing its compact and robust design.

Various Options



Driving Wheel

For Concave Surfaces and
Larger Arcs

Flat Grinding Frame

To Polish Large Areas or
Complex-shaped Items




Figure 2.2: Illustration of the belt sander's various configurations, including the flat grinding frame and driving wheel options for different sanding needs.

/ User-friendly Design /

Allow Users to Operate More Conveniently





Figure 2.3: Depiction of the user-friendly design, highlighting the adjustable angles and the ability to rotate the machine 90 degrees for horizontal sanding.

Safe to Use







Figure 2.4: Safety features of the belt sander, including heat dissipation holes for motor protection and a protective baffle to prevent belt breakage and shield from sparks.

Thoughtful Design



16.8 LBS

- Premium Materials with Process
- Corrosion Prevention Guaranteeing a Long Service Life
- Stable & Thickened Base
- Ensure Its Stability During High-speed Operation

Figure 2.5: Visual representation of the belt sander's outstanding performance, emphasizing its 550W DC motor, 5000rpm high speed, and low noise operation.

Product Details



Al-alloy Driving Wheel

Faster Acceleration and Deceleration
& Corrosion Prevention

Abrasive Belt

30*0.98in
Replaceable Belts to Meet
Your Needs



Motor Driver

Convenient for You to Better
Control the Machine

Please read the manual carefully


Figure 2.6: Detailed view of the thoughtful design, including product dimensions and the stable, thickened base for enhanced stability.

Wide Application

Meet Different Needs Through Various Sanding Ways



Jewelry Making



Plastic Resin Art



Acrylic Polishing



Tool Making



Metal Processing



Figure 2.7: Close-up of product details, showing the Al-alloy driving wheel, the 30x0.98 inch abrasive belt, and the motor driver for convenient control.

Outstanding Performance

Improve Your Work Efficiency



550W DC Motor



5000rpm High Speed



Low Noise




Figure 2.8: Examples of the wide application range of the belt sander, including jewelry making, plastic resin art, acrylic polishing, tool making, and metal processing.

3. SETUP AND ASSEMBLY

Before operating the belt sander, ensure all components are correctly assembled and secured. Refer to the included accessories for installation.

Assembly Steps:

1. Unpack all components and verify against the packing list.
2. Attach the main body of the sander to the base using the provided fasteners.
3. Install the desired worktable (flat grinding frame or wheel) onto the machine. Ensure it is securely fastened and adjusted to the desired angle.
4. Mount the protective baffle in place.

5. Install the abrasive belt onto the rollers, ensuring it is properly tensioned and aligned.
6. Connect the motor driver to the belt sander and plug it into a suitable 110V power outlet.

Your browser does not support the video tag.

Video 3.1: This video demonstrates the assembly process of the belt sander, including attaching components and installing the abrasive belt. It provides a visual guide for initial setup.

Ours	Others
	
✓ Electric Belt-sander ✓ Fast Sanding with High Efficiency ✓ Machine Sanding Saving Effort ✓ Various Sanding Ways to Meet Various Needs	✗ Manual Sanding ✗ Slow Speed and Low Efficiency ✗ Manual Sanding Using Great Effort ✗ Single Sanding Method Hard to Meet Requirements

Figure 3.1: All included components for the CNCEST 1x30 Inch Belt Sander, laid out for easy identification during assembly.

4. OPERATING INSTRUCTIONS

Follow these steps for safe and effective operation of your belt sander.

Basic Operation:

1. **Power On:** Ensure the sander is properly assembled and connected to a power source. Turn on the motor driver.

2. **Adjust Speed:** Use the variable speed control on the motor driver to set the desired RPM (up to 5000rpm) for your specific task and material. Start with a lower speed and gradually increase as needed.
3. **Select Configuration:** Choose between vertical or horizontal sanding by rotating the machine body 90° if horizontal use is desired. Adjust the worktable angle as required for your workpiece.
4. **Sanding Technique:** Gently bring the workpiece into contact with the moving abrasive belt. Apply even pressure and move the workpiece smoothly across the belt for consistent results. Avoid excessive pressure, which can cause overheating or damage to the belt and workpiece.
5. **Power Off:** When finished, turn off the motor driver and disconnect the power cord from the outlet.

5. MAINTENANCE

Regular maintenance ensures the longevity and optimal performance of your belt sander.

Abrasive Belt Replacement:

1. **Disconnect Power:** Always unplug the sander from the power source before performing any maintenance.
2. **Release Tension:** Locate the belt tensioning mechanism (typically a spring-loaded lever or knob) and release the tension on the abrasive belt.
3. **Remove Old Belt:** Carefully slide the worn or damaged belt off the rollers.
4. **Install New Belt:** Place the new 1x30 inch abrasive belt onto the rollers, ensuring the directional arrow on the belt (if present) matches the rotation direction of the sander.
5. **Apply Tension:** Re-engage the tensioning mechanism to secure the new belt firmly. Check for proper alignment.

Cleaning and General Care:


- After each use, clean dust and debris from the sander using a brush or compressed air.
- Inspect the power cord for any damage.
- Check all fasteners and ensure they are tight. Tighten any loose screws.
- Store the sander in a dry, clean environment away from moisture.

Wide Application

Meet Different Needs Through Various Sanding Ways



Jewelry Making



Plastic Resin Art



Acrylic Polishing



Tool Making



Metal Processing



Figure 5.1: Close-up view of the abrasive belt and its placement on the sander, illustrating the area for replacement.

6. TROUBLESHOOTING

This section addresses common issues you might encounter with your belt sander.

Problem	Possible Cause	Solution
Sander does not turn on.	No power supply; Faulty power cord/switch.	Check power outlet and connections. Inspect power cord for damage. Contact support if switch is faulty.
Belt tracking issues (belt drifts).	Improper belt tension; Worn rollers; Misaligned components.	Adjust belt tension. Inspect rollers for wear and replace if necessary. Ensure all components are securely fastened and aligned.

Problem	Possible Cause	Solution
Motor slows down or stops under load.	Overload; Insufficient power; Worn motor.	Reduce pressure on workpiece. Ensure adequate power supply. If motor is worn, contact support for repair or replacement.
Excessive noise or vibration.	Loose components; Worn bearings; Unbalanced belt.	Check and tighten all fasteners. Inspect bearings for wear. Replace the abrasive belt.

7. SPECIFICATIONS

Detailed technical specifications for the CNCEST 1x30 Inch Belt Sander.

Specification	Value
Brand	CNCEST
Product Dimensions	15"L x 5.5"W x 9.8"H
Grit Type	Coarse
Voltage	110 Volts
Power Source	Corded Electric
AC Adapter Current	5 Amps
Grit Number (Included)	60
Maximum Rotational Speed	5000 RPM
Item Weight	16.8 Pounds
Manufacturer	CBDYQ_US
Item Model Number	ZTCYT-2224
Included Components	1* Electric Mini Belt-sander, 1* Motor Driver + 1* Flat Grinding Frame, 1* Wheel + 1* Protective Baffle + 2* Abrasive Belts, 2* Different Worktables +1* Instruction, Other Accessories for Installation

8. WARRANTY AND SUPPORT

For warranty information, technical support, or service inquiries, please contact the manufacturer or your point of purchase. Keep your purchase receipt as proof of purchase.

Manufacturer: CBDYQ_US

For further assistance, please visit the CNCEST Store on Amazon:[CNCEST Amazon Store](#)

© 2024 CNCEST. All rights reserved.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question