

[Manuals.plus](#) /

› [DOESLAG](#) /

› DOESLAG ZC63ABKT6 Solar Pathway Lights User Manual

DOESLAG ZC63ABKT6

DOESLAG ZC63ABKT6 Solar Pathway Lights User Manual

Model: ZC63ABKT6

INTRODUCTION

This manual provides essential instructions for the safe and efficient installation, operation, and maintenance of your DOESLAG Solar Pathway Lights. Please read this manual thoroughly before using the product and retain it for future reference.

WHAT'S IN THE BOX

Upon opening your package, you should find the following components:

- 6 x Solar Pathway Lights
- Batteries (pre-installed or included separately)
- Bulb (pre-installed)
- Light kit (includes ground stakes and extension poles)



Image: All components included in the DOESLAG Solar Pathway Lights 6-pack.

SETUP INSTRUCTIONS

Follow these steps to assemble and install your solar pathway lights:

1. **Unpack Components:** Carefully remove all parts from the packaging.
2. **Activate the Light:** Locate the ON/OFF switch, usually found under the solar panel or inside the light housing. Slide the switch to the "ON" position.
3. **Assemble the Pole:** Connect the extension poles to achieve your desired height. Attach the ground stake to the bottom of the assembled pole.
4. **Attach Light Head:** Securely attach the light head (containing the solar panel and bulb) to the top of the assembled pole.
5. **Install in Ground:** Choose a location that receives direct sunlight for at least 6-8 hours daily. Gently push the assembled light into the ground using the ground stake. **Do not apply excessive force directly to the light head or solar panel.**

Your browser does not support the video tag.

Video: Demonstrates the unboxing and assembly process for the solar pathway lights.



Image: Visual representation of the solar charging process and automatic illumination.

OPERATING INSTRUCTIONS

Your DOESLAG Solar Pathway Lights are designed for automatic operation:

- **Automatic On/Off:** Once activated (switch set to "ON"), the lights will automatically turn on at dusk and turn off at dawn.
- **Solar Charging:** The integrated solar panel charges the internal battery during daylight hours. Ensure the solar panel is clean and free from obstructions for optimal charging. A full charge typically requires 6-8 hours of direct sunlight.
- **Illumination Duration:** Fully charged lights can provide illumination for 8-12 hours.



Image: Illustrates the weatherproof design of the solar lights, suitable for various outdoor conditions.

MAINTENANCE

To ensure the longevity and optimal performance of your solar lights, follow these maintenance tips:

- **Clean Solar Panel:** Regularly wipe the solar panel with a soft, damp cloth to remove dust, dirt, or debris that may hinder charging efficiency.
- **Clear Obstructions:** Ensure no trees, bushes, or structures block direct sunlight from reaching the solar panel.
- **Battery Replacement:** If the light's performance diminishes significantly over time, the rechargeable battery may need replacement. Refer to the product specifications for the correct battery type.
- **Winter Care:** In areas with heavy snowfall, clear snow from the solar panels to allow for charging.

TROUBLESHOOTING

If your solar light is not functioning as expected, consider the following:

- **Light Does Not Turn On:**
 - Ensure the ON/OFF switch is in the "ON" position.

- Verify the solar panel receives at least 6-8 hours of direct sunlight daily.
 - Check if the solar panel is dirty or obstructed. Clean it if necessary.
 - The battery might be depleted. Allow the light to charge for a full day in direct sunlight.
- **Short Illumination Time:**
 - Insufficient sunlight for charging. Relocate the light to a sunnier spot.
 - Battery may be old or damaged. Consider replacing the rechargeable battery.
- **Flickering Light:**
 - Check battery connections.
 - Battery may be nearing the end of its life.

SPECIFICATIONS

Feature	Detail
Brand	DOESLAG
Model Name	ZC63ABKT6
Material	Glass, Metal
Color	Black
Product Dimensions	5.2"L x 5.2"W x 21"H
Power Source	Solar Powered
Light Source Type	LED (Vintage LED bulb)
Light Color	Warm White (3000 Kelvin)
Battery Capacity	1000mAh (Rechargeable)
Charging Time	6-8 hours (direct sunlight)
Illumination Time	8-12 hours (fully charged)
Water Resistance Level	Waterproof (IP65)
Special Features	Auto ON/OFF, Durable Metal & Glass Construction

WARRANTY AND SUPPORT

For warranty information or technical support, please refer to the product packaging or contact DOESLAG customer service directly. Keep your purchase receipt as proof of purchase.
For additional information or to explore other products, visit the[DOESLAG Store](#).

