

**Melnor 65162AMZ**

# Melnor Metal Pulsating Sprinkler with QuickConnect Set

**MODEL: 65162AMZ**

**Brand: Melnor**

## Product Overview

The Melnor Metal Pulsating Sprinkler with QuickConnect Set is designed to provide efficient and wide-ranging watering for large lawns and gardens. This system features a sturdy tripod base that extends to 48 inches high, allowing for a natural, rain-like spray from above. Its all-metal construction ensures durability for long-term use across multiple seasons.

The included QuickConnect system simplifies the process of attaching and detaching watering tools, making setup and storage convenient. The product adapter remains on the sprinkler, allowing for quick connection to any standard garden hose.

## Key Features

- **Study metal tripod:** Extends to 48 inches high to water from above, providing elevated coverage.
- **Wide Coverage:** Capable of covering an area up to 85 feet in diameter, ideal for large-sized lawns and gardens.
- **Durable Metal Pulsating Head:** The all-metal pulsating head is designed for longevity and allows for precise adjustment of the water spray.
- **QuickConnect System:** Includes a Quick Connect Product Adapter and Product End Connector for fast and easy attachment and detachment from your hose.
- **Limited Lifetime Warranty:** Backed by a Melnor Limited Lifetime Warranty, ensuring product reliability and customer support.

## Setup Instructions

1. **Assemble the Tripod:** Unfold the tripod legs and extend them to the desired height. The tripod can extend up to 48 inches (122 cm). Ensure the legs are stable on the ground.
2. **Attach Sprinkler Head:** Securely screw the metal pulsating sprinkler head onto the top of the tripod.
3. **Connect to Water Source:** Attach your garden hose to the QuickConnect Product Adapter on the

sprinkler. Ensure the hose washer is properly seated to prevent leaks. If the washer is worn or damaged, replace it before use.

4. **Position the Sprinkler:** Place the assembled sprinkler in the desired area of your lawn or garden, ensuring it is stable and upright.



*Figure 1: Fully assembled Melnor Metal Pulsating Sprinkler on its tripod.*



Figure 2: The sturdy metal tripod extended to its full height of 4 feet (122 cm). Note the metal construction for durability.



Figure 3: Diagram illustrating the QuickConnect Product Adapter and Product End Connector for easy hose attachment.

## Operating Instructions

---

1. **Turn on Water:** Slowly turn on the water supply to the hose.
2. **Adjust Spray Pattern:** The pulsating head allows for adjustment of the spray pattern. Use the tabs or levers on the sprinkler head to set the desired arc of coverage (partial or full circle) and the spray distance.
3. **Optimize Coverage:** The sprinkler can cover an area up to 85 feet in diameter. Adjust the water pressure and sprinkler settings to achieve optimal coverage for your specific area. The design is effective even with low water pressure.
4. **Connect Multiple Units (Optional):** For very large areas, multiple Melnor pulsating sprinklers can be connected in series to extend coverage.



*Figure 4: The Melnor sprinkler actively watering a garden, demonstrating its elevated spray.*





Figure 5: A close-up view of the durable metal pulsating sprinkler head, showing its adjustment mechanisms.

## Maintenance

- **Check Washers:** Regularly inspect the hose washers for wear, damage, or loss. Replace them as needed to prevent leaks and ensure a secure connection.
- **Clean Sprinkler Head:** Periodically check the sprinkler head for any debris or mineral buildup that might obstruct the spray. Clean with a soft brush and water if necessary.
- **Winterization:** Before freezing temperatures, disconnect the sprinkler from the hose and drain all water from the unit. Store the sprinkler in a dry, protected area to prevent damage from freezing.

## Troubleshooting

Problem	Possible Cause	Solution
---------	----------------	----------

Problem	Possible Cause	Solution
Sprinkler not rotating or rotating intermittently.	Low water pressure; debris in the sprinkler mechanism; worn internal parts.	Ensure adequate water pressure. Check for and remove any debris from the sprinkler head. If issues persist, contact Melnor Customer Care for warranty support.
Water leaking from hose connection.	Loose connection; missing, worn, or damaged hose washer.	Tighten the hose connection. Inspect the hose washer and replace if necessary.
Insufficient spray distance or coverage.	Low water pressure; incorrect spray pattern adjustment.	Increase water pressure if possible. Adjust the sprinkler head settings to optimize spray distance and pattern.

### Specifications

Attribute	Detail
Brand	Melnor
Model Number	65162AMZ
Style	Tripod, Metal Head
Material	Metal
Color	Silver
Product Dimensions (L x W x H)	4.09 x 4.25 x 22.5 inches
Item Weight	5.14 pounds
Maximum Coverage Diameter	85 feet
Tripod Height (Extended)	Up to 48 inches (122 cm)
UPC	042206651624

### Warranty and Support

The Melnor Metal Pulsating Sprinkler with QuickConnect Set is backed by a **Melnor Limited Lifetime Warranty**. This warranty reflects Melnor's commitment to providing high-quality watering tools and exceptional customer care.

For any questions, concerns, troubleshooting assistance, or warranty claims, please contact Melnor Customer Care. They can assist with replacements, technical support, and general inquiries.



This product carries a



**Limited  
Lifetime  
Warranty**

Contact Melnor  
**Customer Care**

- Replacements
- Troubleshooting
- Questions/Concerns



*Figure 6: Melnor's commitment to quality, highlighted by their Limited Lifetime Warranty and customer support.*

Melnor is headquartered in Winchester, Virginia, and is dedicated to designing innovative watering tools and supporting gardeners across North America. Their mission is to help you grow a lush, vibrant garden season after season.