

[Manuals.plus](#) /

› [ZdalaMit](#) /

› User Manual for ZdalaMit KM15E Replacement Remote Control

ZdalaMit KM15E

User Manual for ZdalaMit KM15E Replacement Remote Control

Applicable for Mitsubishi Electric Mr. Slim Air Conditioners

INTRODUCTION

This manual provides instructions for the ZdalaMit KM15E replacement remote control, designed for use with various Mitsubishi Electric Mr. Slim Air Conditioner models. This remote offers a straightforward solution for controlling your air conditioning unit without the need for complex programming.

Note: This remote control displays temperature in Centigrade only.

SETUP

1. Battery Installation

The KM15E remote control requires two (2) 1.5V AAA Alkaline batteries (not included). Follow these steps to install the batteries:

1. Locate the battery compartment on the back of the remote control.
2. Slide the battery compartment cover downwards to open it.
3. Insert two AAA batteries, ensuring the positive (+) and negative (-) terminals align correctly with the markings inside the compartment.
4. Slide the battery compartment cover back into place until it clicks securely.



Figure 1: Battery compartment with cover removed, ready for AAA battery insertion.

2. Initial Use

No programming is required for this replacement remote control. Once the batteries are correctly installed, the remote is ready for immediate use with compatible Mitsubishi Electric Mr. Slim Air Conditioner models.

OPERATING INSTRUCTIONS

The KM15E remote control features an intuitive layout for easy operation of your air conditioner. Below is a guide to the main functions:





Figure 2: Front view of the KM15E remote control.

Button Functions:

- **ON/OFF Button** (Orange): Press to turn the air conditioner unit on or off.
- **TOO WARM / TOO COOL Buttons** (Grey, Up/Down Arrows): Adjust the desired temperature setting. The display shows temperature in Centigrade.
- **MODE Button**: Cycles through different operating modes (e.g., Cool, Heat, Fan, Dry, Auto).
- **FAN Button**: Adjusts the fan speed (e.g., Low, Medium, High, Auto).
- **VANE Button**: Controls the direction of the air vanes (louvers).
- **ECONO COOL Button**: Activates the Econo Cool function for energy-saving operation.
- **SMART SET Button**: Activates or deactivates the Smart Set function.
- **STOP / START Buttons**: Used for setting timer functions.
- **TIME Buttons** (Up/Down Arrows): Used to adjust time settings for timer functions.
- **RESET CLOCK Button**: Resets the internal clock of the remote.





Figure 3: The sliding cover reveals additional control buttons.

Some buttons may be hidden under a sliding cover at the bottom of the remote. Slide the cover down to access these additional functions.

MAINTENANCE

Battery Replacement:

Replace batteries when the remote's display becomes dim or the remote no longer responds to button presses. Always replace both batteries at the same time with new 1.5V AAA Alkaline batteries. Do not mix old and new batteries, or different types of batteries.

Cleaning:

To clean the remote control, wipe it gently with a soft, dry cloth. Do not use liquid cleaners, sprays, or abrasive materials, as these can damage the remote's surface or internal components.

TROUBLESHOOTING

- Remote not responding:**
 - Check if the batteries are installed correctly with the correct polarity.
 - Replace old batteries with new AAA Alkaline batteries.
 - Ensure there are no obstructions between the remote control and the air conditioner unit's receiver.
 - Verify that the remote is pointed directly at the air conditioner's receiver.
- Display is dim or blank:**
 - This usually indicates low battery power. Replace the batteries.
- Air conditioner not responding to specific commands:**
 - Ensure the remote is within the effective operating range.
 - Confirm that the air conditioner unit is powered on.
 - Some advanced functions may require specific air conditioner model compatibility. Refer to your air conditioner's manual for details.

SPECIFICATIONS

Feature	Detail
Model	KM15E
Compatibility	Mitsubishi Electric Mr. Slim Air Conditioner models: E1209C426, MSZ-GE06NA, MSZ-GE09NA, MSZ-GE18NA, MSY-GE09NA, MSZ-GE12NA, MSZ-GE15NA, MSY-GE12NA, MSY-GE15NA, MSY-GE18NA, MSZ-GE24NA, MSY-GE24NA, MSZ-GE06NA-8, MSZ-GE09NA-8, MSZ-GE12NA-8, MSZ-GE15NA-8, MSZ-GE18NA-8, MSY-GE09NA-8, MSY-GE12NA-8, MSY-GE15NA-8, MSY-GE18NA-8
Power Supply	2 x 1.5V AAA Alkaline Batteries (not included)
Display Unit	Centigrade only
Product Dimensions	5.9 x 1.57 x 0.55 inches (15 x 4 x 1.4 cm)
Item Weight	1.41 ounces (40 grams)
Color	White
Special Feature	Ergonomic design





6.38 inch



Figure 4: Approximate dimensions of the KM15E remote control.

WARRANTY AND SUPPORT

Specific warranty information for the ZdalaMit KM15E replacement remote control is not provided within this manual. For details regarding warranty coverage or technical support, please contact the manufacturer or your point of purchase. For further assistance or inquiries, please refer to the contact information provided by the seller or manufacturer.

© 2024 ZdalaMit. All rights reserved.
This manual is for informational purposes only. Product specifications are subject to change without notice.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Answered questions about this manual

How do I set the time on the ZdalaMit KM15E replacement remote control?

To set the time on your ZdalaMit KM15E remote control, follow these steps using the buttons located under the sliding cover at the bottom of the remote: Resetting the Clock: Press the RESET CLOCK...

[Read full answer](#)

Open the live page

<https://manuals.plus/asin/B0CX45GLZ9>

More documents and user manuals: <https://manuals.plus/>