

[Manuals.plus](#) /

› [HBN](#) /

› HBN Wireless Remote Control Outlet User Manual

HBN CP-U153R-1

HBN Wireless Remote Control Outlet User Manual

MODEL: CP-U153R-1



Image: The HBN Wireless Remote Control Outlet, a compact white two-socket plug, shown alongside its matching white remote control.

Product Overview

The HBN Wireless Remote Control Outlet provides convenient control over your electronic devices. Featuring two individually controlled sockets and a remote with a 100ft RF signal range, it allows for easy management of appliances

from a distance, even through walls and windows. Its compact design ensures that the upper outlet remains accessible.

Key Features:

- **2-in-1 Individually Control Design:** Two horizontally positioned sockets, each with its own switch, allowing independent control of different devices.
- **100ft Long Distance Control:** Strong RF signal penetrates doors, walls, and windows for control up to 100 ft indoors.
- **Energy-Saving:** Turn off devices remotely to prevent unnecessary energy consumption.
- **Compact Design:** Covers only a single outlet in a normal vertical outlet fixture, keeping the second outlet free.

What's in the Box

- 1x Wireless Remote Control Outlet
- 1x Remote Controller
- 1 x 12V 23A Battery (pre-installed in remote)

Setup Instructions

The HBN Wireless Remote Control Outlet is designed for easy plug-and-play operation, with the remote pre-paired at the factory.

1. **Plug in the Outlet:** Insert the HBN Wireless Remote Control Outlet into any standard 125V wall outlet. Its compact design ensures it won't block the second receptacle.
2. **Verify Power:** Ensure the outlet is securely plugged in.
3. **Test Remote Control:** The remote is pre-paired. Press the 'ON' or 'OFF' buttons for individual sockets (1 or 2) or 'ALL ON' / 'ALL OFF' to control both. The indicator light on the remote will illuminate when a button is pressed.

Easy Plug-and-Play

No wiring required—just plug the outlet into your wall and pair it with the remote



Image: A woman in bed easily operating a lamp connected to the HBN Wireless Remote Control Outlet with the remote, demonstrating the plug-and-play functionality.

Video: An official HBN video demonstrating the simple plug-and-play setup and operation of the wireless remote control outlet, including how to pair and control devices.

Operating Instructions

The remote control allows for flexible management of your connected devices.

Remote Control Functions:

- **ON/OFF Buttons (1 & 2):** Each pair of ON/OFF buttons (1 and 2) corresponds to one of the two sockets on the outlet. Press 'ON' to power on the device connected to that socket, and 'OFF' to power it off.
- **ALL ON / ALL OFF Buttons:** Use 'ALL ON' to power on both sockets simultaneously, and 'ALL OFF' to power off both sockets simultaneously.

Customizable Pairing:

You can customize the pairing between remotes and outlets:

- Pair one remote with multiple outlets.
- Pair multiple remotes with a single outlet.

Note: Each outlet can store up to 5 sets of remote codes.

100ft RF Signal Range

Through walls and windows, even from
a different floor



Image: A hand holding the remote control, with a wireless outlet plugged into a wall socket in the background, illustrating the independent control of two devices.

Dual Sockets Independent Control

Control two devices with a single remote independently



Image: A collage showing various scenarios where remote control simplifies life, including for pregnant women, individuals with limited mobility, and controlling desk lamps or bedside lamps.

Maintenance

The HBN Wireless Remote Control Outlet requires minimal maintenance.

- **Cleaning:** Disconnect the outlet from power before cleaning. Wipe the surface with a soft, dry cloth. Do not use liquid cleaners or abrasive materials.
- **Battery Replacement:** The remote control uses one 12V 23A battery. If the remote's indicator light does not illuminate or the range decreases significantly, replace the battery. To replace, open the battery compartment on the back of the remote, remove the old battery, and insert a new one, observing polarity.

Troubleshooting

Problem	Possible Cause	Solution
Outlet not responding to remote.	Low or dead remote battery.	Replace the 12V 23A battery in the remote.
Outlet not responding to remote.	Remote and outlet are out of sync or not paired.	Refer to the 'Customizable Pairing' section in Operating Instructions to re-pair the remote and outlet.
Reduced remote control range.	Obstructions (thick walls, metal objects) or interference.	Ensure there are no excessive obstructions between the remote and the outlet. Try moving closer to the outlet.
Device connected to outlet does not turn on.	Device itself is off or malfunctioning.	Check if the device is powered on manually or if it works when plugged directly into a wall outlet.

Specifications

Attribute	Value
Model Number	CP-U153R-1
Product Dimensions	4.4"D x 1.2"W x 1.8"H
Weight	4.8 ounces
Voltage	125 Volts
Max Resistive Load	15A / 1875W
Material	Plastic
Color	White
Certifications	ETL Certified

Warranty and Support

For warranty information and customer support, please refer to the documentation included with your product or visit the official HBN website. You can also contact HBN customer service directly for assistance with product inquiries, troubleshooting, or warranty claims.

Manufacturer: HBN

Official HBN Store: [Visit the HBN Store on Amazon](#)

© 2024 HBN. All rights reserved.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question