Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

GOJOOASIS LZ-C36W2

GOJOOASIS 10x20 Heavy Duty Carport Instruction Manual

Model: LZ-C36W2

Introduction Safety Information Package Contents Setup & Assembly Operating Instructions Maintenance Troubleshooting Specifications Warranty & Support

1. Introduction

Thank you for choosing the GOJOOASIS 10x20 Heavy Duty Carport. This portable garage is designed to provide reliable protection for your vehicles, equipment, or serve as a versatile outdoor shelter. Constructed with a robust metal frame and durable PE fabric, it offers UV protection, waterproofing, and rust resistance. Please read this manual thoroughly before assembly and use to ensure proper installation and safe operation.

Image: The GOJOOASIS 10x20 Heavy Duty Carport, fully assembled, providing shelter for a vehicle in an outdoor environment. Insets highlight ground nails, spring button connectors, elastic buckles, and the roll-up door mechanism.

2. Safety Information

WARNING: Failure to follow these safety instructions may result in serious injury or property damage.

- **Assembly:** Always assemble with at least two adults. Wear appropriate safety gear, including gloves, to prevent injury. Handle components with care during assembly and disassembly.
- **Anchoring:** Securely anchor the carport to the ground using the provided anchoring kit, foot plates, and wind ropes. Inadequate anchoring can lead to collapse in strong winds. Secure shelter to a stable foundation.
- **Weather Conditions:** This carport is designed for general weather protection. In extreme weather conditions (heavy snow, strong winds, severe thunderstorms), disassemble the carport or take additional precautions to prevent damage or collapse. Remove accumulated snow promptly from the canopy.
- **Location:** Choose a level, clear area for installation, away from overhead power lines, trees, or other structures that could cause damage.

- **Fire Hazard:** Keep all heat sources and open flames away from the canopy fabric. The fabric is not fireproof.
- **Children:** Keep children away from the assembly area. Do not allow children to play inside or around the carport unsupervised.
- **Structural Integrity:** Do not hang heavy objects from the frame. Do not modify the structure of the carport. Adhere to weight limits.

3. Package Contents

Before beginning assembly, verify that all parts listed below are present and undamaged. If any parts are missing or damaged, contact customer support immediately.

Component List:

- Steel Frame Poles (various lengths and types)
- Connectors/Joint Fittings (1.5-inch diameter, 1mm thick, grey powder-coated metal)
- PE Fabric Canopy Cover (Beige, UV protected, waterproof)
- Removable Sidewalls (Beige, with double zippers and buckles)
- Roll-up Zipper Doors (Front and back)
- Anchoring Kit (Foot plates, wind ropes, ground nails/stakes)
- Elastic Buckles/Bungees
- Assembly Instructions Manual

4. Setup & Assembly

Assembly requires two or more people. Follow these steps carefully for a secure installation.

Step-by-Step Guide:

1. **Prepare the Area:** Select a flat, clear, and well-drained area measuring at least 10x20 feet. Clear any debris, rocks, or sharp objects.
2. **Unpack Components:** Lay out all frame poles, connectors, and fabric parts. Organize them by type and size according to the component list.
3. **Assemble the Roof Frame:** Connect the roof frame poles using the appropriate connectors. Ensure all spring buttons snap into place securely.
4. **Attach Legs:** Connect the leg poles to the assembled roof frame. Lift the structure carefully, ensuring it remains stable.
5. **Install Foot Plates:** Attach the foot plates to the bottom of each leg pole.
6. **Drape Canopy Cover:** Carefully drape the PE fabric canopy cover over the assembled frame. Ensure it is centered and evenly distributed.
7. **Secure Canopy:** Use the elastic buckles or bungees to secure the canopy cover to the frame poles. Ensure a snug fit to prevent flapping in the wind.
8. **Attach Sidewalls and Doors:** Install the removable sidewalls and roll-up zipper doors. The sidewalls attach to the frame using buckles or ties, and the doors zip into place.
9. **Anchor the Carport:** This is a critical step. Use the provided ground nails/stakes through the foot plates and secure the wind ropes to the frame, tying them to additional ground anchors or sturdy fixed points. Ensure the carport is firmly rooted to prevent movement or collapse.

Image: An exploded view of the carport frame, illustrating the connection points for poles, the attachment method for sidewalls and doors, and the anchoring components.

5. Operating Instructions

Using the Roll-up Zipper Doors:

- The front and back doors feature double zippers for easy access.
- To open, unzip both sides of the door.
- Roll the door fabric upwards and secure it with the integrated buckles or ties to keep it open.
- To close, unfasten the buckles, unroll the door, and zip it completely shut to protect contents from elements.

Removable Sidewalls:

- The sidewalls can be removed individually to enhance air circulation and provide better ventilation, or for open-sided use.
- To remove, unfasten the buckles or ties securing the sidewall to the frame.
- To reattach, align the sidewall with the frame and secure all buckles or ties firmly.

Image: The carport configured for ventilation with sidewalls removed, and as an enclosed space offering full protection.

Multipurpose Use:

This carport is versatile and can be used for:

- Vehicle parking (cars, trucks, motorcycles)
- Equipment storage (lawnmowers, tools, seasonal items)
- Temporary shelter for outdoor activities or events
- Storage for firewood or other outdoor goods

Image: The carport used to shelter a small tractor and an attached trailer, demonstrating its utility for equipment storage.

6. Maintenance

Regular maintenance will extend the life of your carport.

- **Cleaning:** Clean the canopy fabric periodically with mild soap and water. Avoid harsh chemicals or abrasive cleaners, which can damage the UV coating and waterproof properties. Rinse thoroughly and allow to air dry completely before storage.
- **Frame Inspection:** Regularly check all frame connections and anchoring points. Tighten any loose bolts or ropes. Inspect poles for rust or damage.
- **Fabric Inspection:** Inspect the canopy and sidewalls for tears, punctures, or signs of wear. Small repairs can prevent larger damage.
- **Snow Removal:** In snowy conditions, promptly remove snow accumulation from the canopy to prevent structural stress and potential collapse.

- **Storage:** If disassembling for storage, clean all components, ensure they are dry, and store them in a cool, dry place away from direct sunlight and pests.

Image: Visual representation of the carport's weather-resistant PE fabric, highlighting its waterproof and UV protection capabilities.

7. Troubleshooting

Problem	Possible Cause	Solution
Carport is unstable or sways in wind.	Inadequate anchoring; loose frame connections.	Ensure all ground anchors are firmly secured. Tighten all frame connections. Add additional anchoring if necessary.
Water pooling on canopy.	Canopy not taut; improper assembly; heavy rain/snow.	Adjust canopy tension using elastic buckles. Ensure frame is assembled correctly and level. Remove snow promptly.
Zippers are difficult to operate or stuck.	Dirt/debris in zipper teeth; fabric tension.	Clean zipper teeth with a brush. Apply a silicone-based lubricant. Adjust fabric tension if it's pulling on the zipper.
Tears or holes in fabric.	Sharp objects; extreme weather; wear and tear.	Patch small tears with a repair kit. For large damage, consider replacing the canopy.

8. Specifications

Model: LZ-C36W2

Brand: GOJOOASIS

Dimensions (L x W x H): 233.46" x 116.93" x 106.3" (10 ft x 20 ft nominal)

Floor Area: 200 Square Feet

Material: Metal Frame, PE Fabric Canopy

Frame Material: Grey Powder Coated Metal

Pole Diameter: 1.5 inches

Pole Thickness: 1mm

Color: Beige

Water Resistance Level: Waterproof

UV Protection: Yes

Item Weight: 88 Pounds

Assembly Required: Yes

Image: A technical drawing illustrating the precise dimensions of the carport, including length, width, and height measurements.

9. Warranty & Support

GOJOOASIS products are designed for quality and durability. For specific warranty details, please refer to the warranty card included with your purchase or contact GOJOOASIS customer service.

Customer Support:

If you have any questions, require assistance with assembly, or need to report missing/damaged parts, please contact

GOJOOASIS customer support through the retailer where you purchased the product or visit the official GOJOOASIS website for contact information.
Please have your model number (LZ-C36W2) and purchase date ready when contacting support.

© 2026 GOJOOASIS. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B0D14PRGL8

More documents and user manuals: **https://manuals.plus/**