



Manuals.plus /

› ZYTIGHTER /

› ZYTIGHTER Motorcycle Windshield Instruction Manual for Suzuki GSX-8S (2023-2025)

ZYTIGHTER GSX-8S

ZYTIGHTER Motorcycle Windshield Instruction Manual

For Suzuki GSX-8S (2023-2025 Models)

[Contents](#) [Installation](#) [Operation](#) [Introduction](#) [Safety](#) [Package](#) [Maintenance](#) [Troubleshooting](#) [Specifications](#) [Warranty & Support](#)

1. INTRODUCTION

This instruction manual provides detailed guidance for the installation, operation, and maintenance of your ZYTIGHTER Motorcycle Windshield. This product is specifically designed for Suzuki GSX-8S motorcycle models from 2023 to 2025. Please read this manual thoroughly before installation and use to ensure proper function and safety.



Figure 1.1: ZYTIGHTER Motorcycle Windshield on a Suzuki GSX-8S.

2. SAFETY INFORMATION

Always prioritize safety when working on your motorcycle. Failure to follow these instructions could result in injury or damage to your motorcycle.

- Ensure the motorcycle is stable and on a level surface before beginning installation.
- Wear appropriate personal protective equipment, such as gloves and eye protection.
- If you are unsure about any part of the installation process, consult a qualified motorcycle mechanic.
- Do not overtighten fasteners, as this can damage components. Refer to your motorcycle's service manual for specific torque specifications if available.
- After installation, check all fasteners to ensure they are securely tightened before riding.
- Regularly inspect the windshield and mounting hardware for any signs of wear, damage, or looseness.

3. PACKAGE CONTENTS

Please verify that all components are present and undamaged before proceeding with installation.

- 1x ZYTIGHTER Motorcycle Windshield (Black PC plastic)
- 3x Mounting Brackets/Hardware (as pictured)



Figure 3.1: Included components: Windshield and mounting hardware.

If any parts are missing or damaged, contact your retailer or ZYTIGHTER customer support immediately.

4. INSTALLATION INSTRUCTIONS

This section outlines the general steps for installing the ZYTIGHTER Motorcycle Windshield on your Suzuki GSX-8S. While the product is designed for easy installation, professional assistance is recommended if you are unfamiliar with motorcycle accessory installation.

Tools Required (Not Included):

- Appropriate wrenches or hex keys for your motorcycle's existing hardware.
- Soft cloth to protect surfaces.

Installation Steps:

1. **Prepare the Motorcycle:** Park your Suzuki GSX-8S on a stable, level surface. Turn off the engine and remove the key.
2. **Identify Mounting Points:** Locate the existing mounting points on the front of your motorcycle where the windshield will attach. These are typically near the headlight assembly or instrument cluster.
3. **Attach Brackets:** Secure the provided mounting brackets to the motorcycle's frame or existing attachment points. Ensure they are oriented correctly as shown in the product images. Do not fully tighten at this stage.
4. **Position Windshield:** Carefully align the ZYTIGHTER windshield with the attached brackets. The windshield has pre-drilled holes that should match the bracket holes.
5. **Secure Windshield:** Use the provided hardware (if any, or existing motorcycle hardware if applicable) to attach the windshield to the brackets. Start all fasteners by hand to avoid cross-

threading.

6. **Adjust and Tighten:** Once all fasteners are in place, adjust the windshield for optimal alignment. Gradually tighten all fasteners, ensuring the windshield is secure but not overly stressed. Avoid overtightening.
7. **Final Check:** After tightening, gently attempt to move the windshield to confirm it is firmly mounted and does not wobble. Check all connections for security.




Figure 4.1: Visual comparison of the motorcycle before and after windshield installation.



Figure 4.2: Detailed view of the installed windshield and its integration with the motorcycle's front.

5. OPERATING INSTRUCTIONS

The ZYTIGHTER Motorcycle Windshield is a passive accessory. Once correctly installed, it functions by deflecting wind and debris away from the rider, contributing to a more comfortable riding experience. No active operation is required.

AERODYNAMICS

THE CIRCULAR ARC DESIGN CAN BETTER GUIDE THE WIND DIRECTION,
PREVENT DIRECT WIND DIRECTION



Figure 5.1: Illustration of aerodynamic benefits, showing wind deflection.

6. MAINTENANCE

Proper maintenance will extend the life and maintain the clarity of your windshield.

- **Cleaning:** Clean the windshield regularly with a soft cloth and mild soap and water. Avoid abrasive cleaners, harsh chemicals, or paper towels, as these can scratch the PC plastic surface. Rinse thoroughly with clean water and dry with a soft, lint-free cloth.
- **Inspection:** Periodically inspect the windshield for cracks, scratches, or other damage. Check all mounting hardware for tightness and corrosion. Tighten any loose fasteners.
- **Storage:** If storing the motorcycle for an extended period, consider covering the windshield to protect it from dust and UV exposure.

7. TROUBLESHOOTING

This section addresses common issues you might encounter.

Problem	Possible Cause	Solution
Windshield is loose or flapping.	Mounting hardware is not sufficiently tightened. Incorrect installation.	Ensure all mounting bolts and screws are securely tightened. Re-check installation steps to confirm correct assembly. If the issue persists, consult a professional.
Windshield arrived scratched or cracked.	Shipping damage or manufacturing defect.	Do not attempt to install. Contact ZYTIGHTER customer support or your retailer immediately for a replacement.
Difficulty aligning mounting holes.	Brackets are not correctly positioned or slightly misaligned.	Loosen all fasteners slightly, adjust the position of the brackets and windshield, then gradually tighten. Ensure the windshield is designed for your specific motorcycle model and year.

8. SPECIFICATIONS

Feature	Detail
Brand	ZYTIGHTER
Model Compatibility	Suzuki GSX-8S (2023, 2024, 2025)
Material	Premium PC Plastic (Durable, abrasion resistant, unbreakable)
Color	Black
Exterior Finish	Black
Style	Modern
Auto Part Position	Front
Item Weight	10.7 ounces
Package Dimensions	8.62 x 8.23 x 2.56 inches

9. WARRANTY AND SUPPORT

For warranty information, product support, or to report missing/damaged parts, please contact ZYTIGHTER customer service directly or refer to the retailer's return policy. Keep your proof of purchase for any warranty claims.

Contact information for ZYTIGHTER can typically be found on their official website or through the platform where the product was purchased.