

[Manuals.plus](#) /

› [ORIKOOL](#) /

› ORIKOOL Back Bar Cooler BBT350L - 480 Can Capacity Beverage Refrigerator Instruction Manual

ORIKOOL BBT350L

ORIKOOL Back Bar Cooler BBT350L Instruction Manual

Model: BBT350L

INTRODUCTION

This manual provides essential information for the safe and efficient operation of your ORIKOOL Back Bar Cooler, model BBT350L. Please read these instructions thoroughly before installation and use, and retain them for future reference. This beverage refrigerator is designed for displaying and cooling various bottled and canned beverages, featuring a 480-can capacity, three hinged glass doors, LED lighting, and adjustable shelving.



Figure 1: ORIKOOL Back Bar Cooler BBT350L

SETUP INSTRUCTIONS

1. Unpacking and Placement

Carefully remove all packaging materials. Ensure the unit is placed on a stable, level surface. The dimensions of the unit are approximately 53.15"W x 20.5"D x 35.43"H. Allow adequate ventilation space around the unit (at least 4 inches on all sides and top) for optimal performance.



Figure 2: Product Dimensions and Temperature Range

2. Leveling the Unit

The cooler is equipped with adjustable leveling feet. Use a spirit level to ensure the unit is perfectly level. Adjust the feet by turning them clockwise or counter-clockwise until the unit is stable and level. Proper leveling is crucial for door alignment and efficient operation.



Figure 3: Adjustable Leveling Feet

3. Shelf Installation and Adjustment

The cooler comes with six adjustable wire shelves. To install or adjust shelves, locate the shelf clips on the interior side walls. Insert the clips into the desired slots, ensuring they are securely in place and level. Then, place the shelves onto the clips. Each shelf can hold up to 60 pounds.

Your browser does not support the video tag.

Video 1: How to set the shelves. This video demonstrates the process of installing and adjusting the shelves within the cooler.



Figure 4: Heavy-Duty Epoxy-Coated Shelves

4. Electrical Connection

Connect the cooler to a standard 115 Volts electrical outlet using the NEMA 5-15P plug. Ensure the outlet is properly grounded and matches the voltage requirements of the unit. Avoid using extension cords.



Figure 5: NEMA 5-15P Plug

OPERATING INSTRUCTIONS

1. Power On and Initial Cooling

After connecting to power, the unit will begin cooling. Allow the cooler to operate empty for at least 2-4 hours to reach its set

temperature before loading beverages. This ensures the internal temperature stabilizes.

2. Temperature Control

The cooler features an intelligent temperature control system with an LED digital display. The optimal temperature range is 35.6°F to 46.4°F (2°C to 8°C). Use the digital controls to set your desired temperature. Refer to the specific temperature settings for different beverage types:

- Iced Cola: 35.6-40°F
- Pure Milk: 40-45°F
- Champagne: 45-46.4°F

Your browser does not support the video tag.

Video 2: Back Bar Cooler Display Details. This video highlights various features of the cooler, including temperature control.

Your browser does not support the video tag.

Video 3: ORIKOOL Commercial Beverage Refrigerator. This video provides an overview of the refrigerator's features and operation.

3. LED Lighting

The interior of the cooler is illuminated with energy-saving LED lighting, enhancing visibility of the stored beverages. The lighting can typically be controlled via a switch on the control panel.



Figure 6: Illuminated Interior

4. Safety Door Lock

Each door is equipped with a safety lock to secure your beverages. Use the provided keys to lock and unlock the doors as needed.

DELIBERATE DESIGN DETAILS



Figure 7: Safety Door Lock Detail

MAINTENANCE

1. Cleaning the Interior and Exterior

Regularly clean the interior and exterior surfaces of the cooler with a mild detergent and a soft cloth. Avoid abrasive cleaners or sharp objects that could damage the surfaces. The removable sealing strips on the doors can be detached for thorough cleaning.

Your browser does not support the video tag.

Video 4: Orikool Back Bar BBT350L. This video provides an overview of the product, including features relevant to maintenance like removable sealing strips.

2. Defrost System

This unit features a frost-free defrost system, minimizing the need for manual defrosting. However, it is recommended to periodically check for any ice buildup and ensure the drainage system is clear.

3. Condenser Coil Cleaning

For optimal efficiency, the condenser coils should be cleaned regularly (every 3-6 months) to remove dust and debris. This typically involves unplugging the unit and using a brush or vacuum cleaner to clean the coils located at the back or bottom of the unit. Consult a qualified technician if you are unsure.

TROUBLESHOOTING GUIDE

Before contacting customer support, please review the following common issues and solutions:

Problem	Possible Cause	Solution
Unit does not power on	No power supply; tripped circuit breaker; faulty power cord	Check power connection; reset circuit breaker; contact technician if cord is damaged
Insufficient cooling	Temperature setting too high; door not closed properly; condenser coils dirty; unit overloaded	Adjust temperature; ensure doors are sealed; clean condenser coils; do not overload unit
Excessive noise	Unit not level; fan obstruction; loose components	Level the unit; check for obstructions around fans; contact support if noise persists
Water leakage	Clogged drain hose; improper installation	Clear drain hose; ensure unit is level and properly installed

SPECIFICATIONS

Feature	Detail
Model Name	BBT350L
Product Dimensions (D x W x H)	20.5"D x 53.15"W x 35.43"H
Capacity	11.3 Cubic Feet (approx. 480 standard 12-ounce cans)
Number of Doors	3 (Hinged Glass Doors)
Temperature Range	35.6°F – 46.4°F
Defrost System	Frost Free
Voltage	115 Volts
Refrigerant	R-600A
Number of Shelves	6 (Wire, adjustable, 60 lbs capacity each)
Special Features	Adjustable Shelves, Digital Temperature Control, Door Lock, LED Lighting
Item Weight	167.6 Pounds
Certification	ETL

WARRANTY INFORMATION

The ORIKOOL Back Bar Cooler BBT350L comes with a manufacturer's warranty:

- **2 Years:** All Accessories

- **5 Years:** Compressor

Please retain your proof of purchase for warranty claims. The warranty covers defects in materials and workmanship under normal use. It does not cover damage resulting from misuse, accident, alteration, neglect, or unauthorized repair.

CUSTOMER SUPPORT

For technical assistance, warranty inquiries, or to order replacement parts, please contact ORIKOOL customer service. Refer to the contact information provided with your product packaging or visit the official ORIKOOL website for support details.

When contacting support, please have your model number (BBT350L) and purchase date readily available.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Email

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Details

Submit question