onerbl PTL-40

Onerbl 12V DC Adapter Instruction Manual

For ToolTronix Model PTL-40 Jump Starter and Compatible Devices

1. Introduction

This manual provides essential information for the safe and effective use of your Onerbl 12V DC Adapter. This adapter is designed as a high-quality replacement power charger for devices requiring a 12V DC input, specifically compatible with the ToolTronix Model PTL-40 (PTL40) 12V 12Ah 700A 4-in-1 Starter Jump Start Booster, Air Compressor, and Light unit. It converts AC power from electrical outlets into the DC power required by your device, enabling operation or battery charging.

2. Safety Information

Please read and understand all safety instructions before using the adapter. Failure to follow these instructions may result in electric shock, fire, or serious injury.

- **Over Voltage Protection:** The adapter is equipped with over-voltage protection to safeguard your device.
- **Over Heat Protection:** The adapter includes over-heat protection to prevent damage from excessive temperatures.
- Use only with compatible devices as specified in this manual.
- Do not expose the adapter to water, rain, or excessive moisture.
- Do not disassemble or modify the adapter. Refer all servicing to qualified personnel.
- Ensure the power outlet voltage matches the adapter's input requirements.
- Keep out of reach of children.

3. Package Contents

Verify that all items are present in your package:

- 1 x Onerbl 12V DC Adapter (Car 12V DC Adapter Replacement)

Note: The ToolTronix PTL-40 unit or other compatible devices are sold separately.

4. Setup

Setup

Follow these steps to set up your Onerbl 12V DC Adapter:

1. **Identify the Power Input:** Locate the 12V DC power input port on your compatible device (e.g., ToolTronix PTL-40 jump starter). This is typically a cigarette lighter style socket.
2. **Connect the Adapter:** Insert the male end of the Onerbl 12V DC Adapter into the 12V DC power input port of your device. Ensure a secure connection.
3. **Connect to Power Source:** Insert the other end of the adapter (cigarette lighter plug) into a 12V DC power source, such as a vehicle's cigarette lighter socket or a compatible 12V DC power outlet.
4. **Verify Connection:** Ensure both ends of the adapter are firmly connected before proceeding.

Image: Example of connecting the 12V DC adapter to a jump starter. (No product images or videos were provided in the input data.)

5. Operating Instructions

Once the adapter is properly connected, it will supply power to your device or charge its internal battery.

- **Powering the Device:** If your device is designed to operate directly from a 12V DC source, it should power on once the adapter is connected to a live 12V DC outlet.
- **Charging the Battery:** If your device has an internal rechargeable battery (e.g., ToolTronix PTL-40), the adapter will initiate the charging process. Refer to your device's manual for specific charging indicators and times.
- **Monitoring:** Observe your device's indicators to confirm it is receiving power or charging correctly.
- **Disconnection:** To disconnect, first remove the adapter from the 12V DC power source, then disconnect it from your device.

6. Maintenance

Proper maintenance ensures the longevity and safe operation of your Onerbl 12V DC Adapter.

- **Cleaning:** Wipe the adapter with a dry, soft cloth. Do not use liquid cleaners or solvents.
- **Storage:** Store the adapter in a cool, dry place away from direct sunlight and extreme temperatures when not in use.
- **Inspection:** Periodically inspect the adapter and its cables for any signs of damage, such as frayed wires or cracked casing. Discontinue use if damage is found.

7. Troubleshooting

Problem	Possible Cause	Solution

Problem	Possible Cause	Solution
Device not receiving power/charging.	Adapter not fully connected. 12V DC power source is not active. Device's power input port is faulty. Adapter is faulty.	Ensure both ends of the adapter are securely plugged in. Test the 12V DC power source with another device. Consult your device's manual or manufacturer. Contact customer support if other solutions fail.
Adapter feels excessively hot.	Overload or internal fault.	Immediately disconnect the adapter from both the power source and the device. Allow it to cool. Do not use if it continues to overheat.

8. Specifications

Brand: onerbl

Compatible Devices: ToolTronix Model PTL-40 PTL40 12 V 12Ah 700A 4 in 1 Starter Jump Start Booster Air Compressor Light 12VDC Auto Vehicle Boat

Manufacturer: Shenzhen Waweis Technology Co., Ltd

Type: Car 12V DC Adapter Replacement

Features: Over Voltage Protection, Over Heat Protection

9. Warranty and Support

Specific warranty information for this Onerbl product is not provided in the available product details. For warranty claims or technical support, please refer to the seller's return policy or contact the seller directly through the platform where the purchase was made. The product is described as a "Brand New, High Quality Replacement Car Power Charger/Adapter" and "Tested Units. In Great Working Condition."
Seller: GreatComputerParts
Return Policy: 30 days (refund/replacement)

© 2026 Onerbl. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question