



Manuals.plus /

› EasyAcc /

› EasyAcc 1200ml Electric Dehumidifier User Manual - Model KW-CS01

## EasyAcc KW-CS01

# EasyAcc 1200ml Electric Dehumidifier User Manual

Model: KW-CS01

## 1. IMPORTANT SAFETY INSTRUCTIONS

---

Please read all instructions carefully before using the EasyAcc Dehumidifier. Retain this manual for future reference.

- Ensure the power supply voltage matches the rating label on the dehumidifier.
- Do not block the air inlet or outlet. Maintain at least 10 cm (4 inches) clearance around the unit.
- Unplug the dehumidifier from the power outlet before cleaning, maintenance, or when not in use.
- Do not immerse the unit, power cord, or plug in water or other liquids.
- Do not operate the dehumidifier if the cord or plug is damaged, or if the unit malfunctions or has been dropped.
- Keep the appliance out of reach of children and pets.
- Use the dehumidifier on a stable, level surface to prevent water spillage.
- This appliance is designed for indoor use only. Do not use outdoors.
- Do not use this dehumidifier to dry clothes directly.
- Operating temperature range is 5°C to 40°C (41°F to 104°F).

## 2. PRODUCT OVERVIEW

---

The EasyAcc KW-CS01 is a compact electric dehumidifier designed to reduce excess moisture in small to medium-sized spaces, such as bedrooms, offices, bathrooms, and wardrobes. It features quiet operation, low power consumption, an automatic defrost function, and a colorful night light.



Image 2.1: Front view of the EasyAcc 1200ml Electric Dehumidifier, showing the water tank and control buttons.

### Key Features:

- **1200ml Water Tank:** Transparent and removable for easy monitoring and emptying.
- **Quiet Operation:** Operates at less than 35 dB, suitable for bedrooms.
- **Energy Efficient:** Consumes approximately 0.79 kW per day.
- **Automatic Shut-Off:** The unit automatically turns off when the water tank is full, indicated by a red flashing light.

- **7-Color Night Light:** Provides ambient lighting, with options to cycle through colors or turn off.
- **Automatic Defrost Function:** Activates when ambient temperature is below 15°C to prevent frost buildup.
- **Washable Filter:** Removable and reusable filter for easy maintenance.
- **Compact and Portable:** Designed with a handle for easy relocation.



Image 2.2: Graph illustrating the dehumidification capacity, showing the EasyAcc dehumidifier collecting up to 400ml/24H at 86°F, 85% RH.

### 3. SETUP

Follow these steps to set up your dehumidifier for the first time:

1. **Unpack the Unit:** Carefully remove the dehumidifier from its packaging. Retain packaging materials for future storage or transport.
2. **Placement:** Place the dehumidifier on a firm, level surface. Ensure there is at least 10 cm (4 inches) of clear space around the air inlet (rear) and air outlet (top) for optimal airflow. Avoid placing it near heat sources or in direct sunlight.
3. **Power Connection:** Plug the power adapter into a suitable electrical outlet.
4. **Initial Operation:** Press the Power On/Off button to start the dehumidifier. The unit will begin operating in dehumidification mode.

## Easy to Use & Auto Shut-Off



Image 3.1: Diagram showing the Power On/Off button, the light control button, and the red warning light that flashes when the water tank is full.

## 4. OPERATING INSTRUCTIONS

### Power On/Off:

- Press the **Power Button** (①) once to turn the unit on. The dehumidifier will start operating.
- Press the **Power Button** (①) again to turn the unit off.

### Night Light Function:

- Press the **Light Button** (②) once to activate the 7-color cycling night light.
- Press the **Light Button** (②) again to pause on the current color.
- Press the **Light Button** (②) a third time to turn the night light off.



Image 4.1: The dehumidifier operating with its night light function in a room, highlighting its quiet operation.

### Water Tank Management:

- The dehumidifier features a 1200ml transparent water tank, allowing you to monitor the water level.
- When the water tank is full, the unit will automatically shut off, and a red warning light will flash to indicate that the tank needs to be emptied.
- To empty the tank, gently pull it out from the front of the unit, discard the collected water, and then slide the tank back into place until it clicks securely.

### Automatic Defrost Function:

The dehumidifier is equipped with an automatic defrost function. If the ambient temperature drops below 15°C (59°F), frost may form on the condensing plate. The unit will automatically activate its defrost cycle to melt the frost, ensuring continuous and efficient operation. During this cycle, dehumidification may temporarily pause.

## 5. MAINTENANCE

Regular maintenance ensures optimal performance and extends the lifespan of your dehumidifier.

### Cleaning the Water Tank:

- Empty the water tank as described in the Operating Instructions.
- Rinse the tank with clean water. For thorough cleaning, use a mild detergent and a soft brush, then rinse thoroughly.
- Ensure the tank is completely dry before reinserting it into the dehumidifier.

### Cleaning the Air Filter:

The dehumidifier features a washable air filter located at the rear of the unit.

1. Turn off the dehumidifier and unplug it from the power outlet.
2. Gently pull out the filter cover from the rear of the unit.
3. Remove the filter.
4. Wash the filter with clean water, or use a soft brush to remove dust and debris.
5. Allow the filter to air dry completely before reinserting it. Do not use a dryer or direct heat.
6. Place the dry filter back into its slot and close the filter cover.



Image 5.1: Instructions for cleaning the washable filter and removing the 1.2L pull-out water tank.

## Exterior Cleaning:

- Wipe the exterior of the unit with a soft, damp cloth.
- Do not use abrasive cleaners, solvents, or harsh chemicals, as these may damage the surface.

## 6. TROUBLESHOOTING

---

If you encounter any issues with your dehumidifier, please refer to the following troubleshooting guide:

Problem	Possible Cause	Solution
Dehumidifier does not turn on.	No power supply. Power adapter not connected. Water tank full.	Check power connection. Ensure adapter is securely plugged in. Empty water tank if full.
No water collected or low collection.	Low ambient humidity. Temperature too low. Air inlets/outlets blocked. Filter dirty.	Ensure humidity is above 50% RH. Operate in temperatures above 5°C. Clear obstructions. Clean the air filter. Allow 3 days for continuous operation in low humidity environments.
Unit is noisy.	Unit not on a level surface. Obstruction in fan.	Place on a stable, level surface. Check for and remove any obstructions.
Red light flashing.	Water tank is full.	Empty the water tank and reinsert it securely.
Frost on condensing plate.	Ambient temperature is low (below 15°C).	This is normal. The automatic defrost function will activate to clear the frost. Dehumidification will resume once defrosting is complete.

## 7. SPECIFICATIONS

---

Feature	Specification
Brand	EasyAcc
Model Number	KW-CS01
Color	White
Water Tank Capacity	1200 Milliliters (1.2 Liters)
Dimensions (L x W x H)	13.8 x 13.7 x 25.5 cm (5.4 x 5.4 x 10 inches)
Item Weight	1.53 Kilograms (3.37 lbs)
Coverage Area	50-220 Square Feet
Noise Level	< 35 dB
Power Consumption	Approx. 0.79 kW/day
Operating Temperature	5°C ~ 40°C (41°F ~ 104°F)



Image 7.1: The dehumidifier displaying its compact dimensions: 137mm width, 258mm height, and 139mm depth.

## **8. WARRANTY AND SUPPORT**

---

EasyAcc is committed to providing high-quality products and customer satisfaction. If you have any questions, concerns, or require assistance with your EasyAcc 1200ml Electric Dehumidifier, please do not hesitate to contact our customer support team.

Please refer to your purchase documentation or the EasyAcc official website for specific warranty details and contact information.