Manuals+

Q & A | Deep Search | Upload

Givi SR6122

GIVI SR6122 Top Box Luggage Rack Motorcycle Instruction Manual

Model: SR6122

Product Overview

The GIVI SR6122 is a specific fitment kit designed to allow the installation of a GIVI Monokey or Monolock top case (sold separately) onto compatible motorcycles. This rack provides a secure and stable platform for carrying additional luggage.

Image: The GIVI SR6122 luggage rack with a GIVI top box mounted on the rear of a motorcycle. The rack provides a stable base for the top box, which features a black and silver design with red accents.

Setup and Installation

Package Contents

- GIVI SR6122 Specific Rear Rack Kit
- Mounting hardware (bolts, washers, spacers)
- Installation instructions (refer to this manual)

Required Tools

- Metric wrench set
- Allen key set
- Torque wrench (recommended for proper fastener tightening)

- Screwdriver (Phillips and/or flathead, depending on motorcycle model)

Installation Steps

Note: *Always refer to your motorcycle's service manual for specific instructions on removing and reattaching components. Ensure the motorcycle is stable on a center stand or paddock stand before beginning installation.*

1. **Prepare Motorcycle:** Remove any existing rear rack, passenger grab handles, or body panels as required to access the mounting points. Store removed parts safely.
2. **Identify Mounting Points:** Locate the designated mounting points on your motorcycle's rear frame or subframe. These are typically where the original grab handles or a factory rack would attach.
3. **Attach Brackets:** Secure the GIVI SR6122 support brackets to the motorcycle's mounting points using the provided hardware. Do not fully tighten bolts at this stage.
4. **Position Rack Plate:** Place the GIVI rack plate onto the support brackets. Align the holes on the rack plate with the corresponding holes on the brackets.
5. **Secure Rack Plate:** Attach the rack plate to the support brackets using the remaining hardware. Ensure all components are correctly aligned.
6. **Tighten All Fasteners:** Once all components are in place and aligned, progressively tighten all bolts to the manufacturer's specified torque settings. Start from the center and work outwards.
7. **Reassemble Motorcycle:** Reinstall any removed body panels or components. Ensure all parts are securely fastened.
8. **Final Check:** Verify that the rack is securely mounted and does not wobble. Check for any loose bolts or interference with other motorcycle components.

Operation

Attaching a GIVI Top Box (Monokey/Monolock)

1. Ensure the top box is unlocked.
2. Align the front hooks of the top box with the corresponding slots on the front of the GIVI rack plate.
3. Lower the rear of the top box onto the rack plate until the rear locking mechanism engages with the plate.
4. Press down firmly on the top box until you hear a "click," indicating it is securely locked.
5. Verify the top box is securely attached by gently pulling upwards on it.

Detaching a GIVI Top Box (Monokey/Monolock)

1. Insert the key into the top box lock and turn it to the unlock position.
2. Press the release button (typically located near the lock mechanism).
3. While holding the release button, lift the rear of the top box and slide it backward to disengage the front hooks.
4. Carefully remove the top box from the rack.

Weight Capacity

Always adhere to the maximum weight capacity specified by GIVI for the SR6122 rack and your specific top box. Overloading can affect motorcycle handling and stability. Consult your motorcycle's owner's manual for its maximum load capacity.

Maintenance

Cleaning

- Clean the rack regularly with mild soap and water.
- Avoid abrasive cleaners or solvents that could damage the finish.

- Rinse thoroughly and dry with a soft cloth.

Inspection

- Periodically inspect all mounting bolts for tightness. Re-tighten to specified torque if necessary.
- Check the rack for any signs of damage, cracks, or corrosion.
- Ensure the top box locking mechanism operates smoothly.

Troubleshooting

Common Issues and Solutions

Issue	Possible Cause	Solution
Rack feels loose or wobbly.	Mounting bolts are not sufficiently tightened.	Check and re-tighten all mounting bolts to the specified torque.
Top box does not attach securely.	Misalignment or obstruction in the locking mechanism.	Ensure the top box is correctly aligned with the rack plate. Check for debris in the locking mechanism.
Difficulty detaching top box.	Lock mechanism stiff or jammed.	Apply a small amount of lubricant to the lock mechanism. Ensure the key is fully turned and the release button is pressed correctly.

Specifications

Feature	Detail
Model Number	SR6122
Brand	Givi
Compatibility	Specific motorcycle models (check GIVI fitment guide)
Top Box System	Designed for GIVI Monokey or Monolock top cases
Material	Typically steel or aluminum (specifics may vary)
Color	Multicolor (as per product listing, typically black)
Parcel Dimensions	40 x 40 x 40 cm
Item Weight	3 kg

Warranty and Support

For warranty information, technical support, or replacement parts, please contact GIVI directly or refer to their official website. Keep your purchase receipt as proof of purchase.