NOIROT Flobain II 750 Watt

Noirot Flobain 2 Towel Dryer Radiator - 750 Watt User Manual

Model: Flobain II 750 Watt

Introduction Safety Instructions Product Overview Setup Operation Maintenance Troubleshooting Specifications Warranty & Support

1. Introduction

This manual provides essential information for the safe and efficient use of your Noirot Flobain 2 Towel Dryer Radiator, 750 Watt model. The Flobain 2 is designed to provide comfortable heating in your bathroom and ensure your towels are warm and dry. Please read these instructions carefully before installation and operation, and retain them for future reference.

2. Safety Instructions

Important: Always follow basic safety precautions when using electrical appliances to reduce the risk of fire, electric shock, and injury.

- Ensure the appliance is installed by a qualified electrician in accordance with local electrical codes and regulations.
- Do not operate the appliance with a damaged cord or plug, or after the appliance malfunctions or has been damaged in any manner.
- Keep all flammable materials at a safe distance from the radiator.
- Do not immerse the appliance in water or other liquids.
- This appliance is intended for domestic use only. Do not use outdoors.
- Do not cover the radiator, as this can lead to overheating.
- The surface of the radiator can become hot during operation. Avoid direct contact.
- Children should be supervised to ensure they do not play with the appliance.
- Disconnect the appliance from the power supply before cleaning or maintenance.

3. Product Overview

The Noirot Flobain 2 Towel Dryer Radiator features a design optimized for functionality and energy efficiency. It incorporates a fluid inertia heating system for consistent warmth and a user-friendly interface.

Key Features:

- **Fluid Inertia Heating:** Provides gentle and continuous heat distribution.
- **Round Tube Design:** Offers ample space for drying and warming towels and bathrobes.
- **Clip-on Hooks:** Includes two practical clip-on hooks for additional towel hanging capacity.
- **Programmable Thermostat:** Backlit LCD screen with direct access keys for easy temperature control and programming.
- **BOOST Function:** Activates maximum heating power for a user-adjustable duration (5 minutes to 2 hours).
- **REPEAT Function:** Allows activation of the BOOST mode at fixed, scheduled times.
- **Energy Saving Features:** Includes an open window detection system and a parental lock (PIN code) to prevent energy waste.
- **Pre-recorded and Free Programs:** Offers 3 pre-set programs and 3 customizable programs for enhanced comfort.

Product Components:



Figure 3.1: Noirot Flobain 2 Towel Dryer Radiator in a bathroom setting. This image shows the overall design and how it integrates into a modern bathroom environment, providing both heating and towel drying functionality.



Figure 3.2: The towel dryer radiator with an emphasis on its two clip-on hooks. These hooks provide additional space for hanging towels or bathrobes, enhancing the product's utility.



Figure 3.3: An internal view diagram of the fluid inertia heating core. This illustrates how the fluid circulates within the radiator to provide efficient and even heat distribution.



Figure 3.4: Detailed view of the practical and efficient thermostat. The backlit LCD screen and direct access buttons allow for intuitive control of temperature settings and functions like BOOST and programming.



Figure 3.5: Side profile of one of the clip-on hooks. These hooks are designed for easy attachment and removal from the radiator tubes.



Figure 3.6: Front view of a clip-on hook, showing its design for securely holding towels.



Figure 3.7: Angled perspective of a clip-on hook, demonstrating its robust construction and ease of use.

4. Setup and Installation

Installation of the Noirot Flobain 2 Towel Dryer Radiator should be performed by a qualified professional to ensure safety and compliance with all relevant electrical and building codes.

4.1. Mounting the Radiator

- Choose a suitable wall location in your bathroom, ensuring adequate clearance from water sources and flammable materials.
- Mark the drilling points on the wall using the provided mounting template (if applicable, refer to packaging for template).
- Drill holes and insert appropriate wall plugs.
- Secure the mounting brackets to the wall.
- Carefully lift and attach the radiator to the mounting brackets, ensuring it is level and securely fastened.

4.2. Electrical Connection

- Ensure the main power supply to the installation area is switched off at the circuit breaker.
- Connect the radiator's electrical wiring to the designated electrical outlet or junction box according to the wiring diagram provided in the full installation guide (not included in this manual, refer to product packaging).
- Verify all connections are secure and properly insulated.

4.3. Initial Power-On

- Once installation is complete and verified, restore power to the circuit.
- The radiator's display should illuminate. Follow the on-screen prompts for initial setup, such as setting the current time and date.

5. Operating Instructions

The Flobain 2 features an intuitive control panel with a backlit LCD screen and direct access buttons for easy operation.

5.1. Thermostat Control

- **Power On/Off:** Press the **Power button** (usually indicated by a circle with a vertical line) to turn the radiator on or off.
- **Mode Selection:** Press the **MODE button** to cycle through available operating modes (e.g., Comfort, Eco, Frost Protection, Program).
- **Temperature Adjustment:** Use the **'+'** and **'-'** buttons to increase or decrease the desired temperature in the current mode. The set temperature will be displayed on the LCD screen.

5.2. BOOST Function

The BOOST function provides a temporary burst of maximum heating power for quick warming of the bathroom or towels.

- **Activation:** Press the **BOOST button**. The display will show the active BOOST function and its default duration.
- **Duration Setting:** While BOOST is active, use the **'+'** and **'-'** buttons to adjust the duration from 5 minutes up to 2 hours.
- The radiator will return to its previous operating mode once the BOOST duration expires.

5.3. REPEAT Function

The REPEAT function allows you to schedule the BOOST mode to activate at specific, fixed times daily.

- Consult the full product manual for detailed instructions on setting up REPEAT schedules. This typically involves accessing a programming menu via the MODE button.

- You can set the start time and duration for the BOOST function to repeat daily.

5.4. Programming Modes

The Flobain 2 offers 3 pre-recorded programs and 3 free (customizable) programs to optimize your heating schedule.

- **Selecting Programs:** Use the **MODE button** to navigate to the program selection menu.
- **Pre-recorded Programs:** Choose from the factory-set programs designed for common usage patterns.
- **Custom Programs:** Access the free program slots to define your own heating schedules for different days and times. Refer to the detailed manual for step-by-step programming instructions.

5.5. Energy Saving Features

- **Open Window Detection:** The radiator automatically detects a sudden drop in temperature (indicating an open window) and temporarily pauses heating to prevent energy waste. Heating resumes when the window is closed or after a set period.
- **Parental Lock (PIN Code):** Activate the parental lock feature to prevent unauthorized changes to settings. This requires a PIN code to unlock the controls. Instructions for setting and activating the PIN code are in the detailed manual.

6. Maintenance

Regular maintenance ensures the longevity and efficient operation of your Noirot Flobain 2 Towel Dryer Radiator.

6.1. Cleaning

- **Before Cleaning:** Always disconnect the radiator from the main power supply.
- **Exterior Cleaning:** Wipe the exterior surfaces with a soft, damp cloth. Do not use abrasive cleaners, solvents, or harsh chemicals, as these can damage the finish.
- **Dust Removal:** Periodically dust the radiator fins and tubes to maintain optimal heat dissipation.
- Ensure the radiator is completely dry before reconnecting it to power.

6.2. General Checks

- Periodically inspect the power cord and plug for any signs of damage. If damaged, contact a qualified technician for repair.
- Ensure the radiator remains securely mounted to the wall.

7. Troubleshooting

If you encounter issues with your Flobain 2 radiator, refer to the following common problems and solutions before contacting customer support.

Problem	Possible Cause	Solution
Radiator does not turn on.	No power supply; circuit breaker tripped; power button not pressed.	Check if the radiator is plugged in correctly. Verify the circuit breaker. Press the power button.
Radiator is on but not heating.	Temperature setting too low; open window detected; program mode active with low heat.	Increase the set temperature. Close any open windows. Check the active program settings.

Problem	Possible Cause	Solution
Display shows an error code.	Internal malfunction or sensor issue.	Note the error code and consult the detailed product manual or contact customer support. Try resetting the device by turning it off and on.
Parental lock is active and controls are unresponsive.	PIN code protection is enabled.	Enter the correct PIN code to unlock the controls. Refer to the manual for PIN code management.

If the problem persists after attempting these solutions, please contact Noirot customer support for further assistance.

8. Specifications

Feature	Detail
Brand	NOIROT
Model	Flobain II 750 Watt
Type	Fluid Inertia Towel Dryer Radiator
Power Output	750 Watt
Dimensions (W x H x D)	500mm x 1400mm x 86mm
Net Weight	15.1 kg
Certification	NF Electricity certified
Control Panel	Backlit LCD screen with direct access keys
Functions	BOOST, REPEAT, 3 Pre-recorded Programs, 3 Free Programs
Energy Saving Features	Open window detection, Parental lock (PIN code)

9. Warranty and Support

9.1. Warranty Information

The Noirot Flobain 2 Towel Dryer Radiator is covered by a**3-year warranty** from the date of purchase. This warranty covers defects in materials and workmanship under normal use. Please retain your proof of purchase for warranty claims. The warranty does not cover damage resulting from improper installation, misuse, neglect, unauthorized repairs, or normal wear and tear.

9.2. Customer Support

For technical assistance, warranty claims, or spare parts inquiries, please contact Noirot customer service. You can find contact information on the official Noirot website or through your retailer.
When contacting support, please have your product model (Flobain II 750 Watt) and proof of purchase readily available.
Noirot Official Website: Visit the Noirot Store on Amazon.fr (This link directs to the brand's store page, which may

contain support contact information or links to the official website).

© 2024 NOIROT. All rights reserved.
This manual is for informational purposes only. Specifications are subject to change without notice.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question