Monstrum Banshee 2-10x30 FFP MPVO Scope

Monstrum Banshee 2-10x30 FFP MPVO Scope Instruction Manual

Model: Banshee 2-10x30 FFP MPVO Scope

1. Introduction

This manual provides detailed instructions for the proper setup, operation, and maintenance of your Monstrum Banshee 2-10x30 First Focal Plane (FFP) Mid Power Variable Optic (MPVO) Scope. Please read this manual thoroughly before using the product to ensure optimal performance and longevity.



Figure 1: Monstrum Banshee 2-10x30 FFP MPVO Scope.

2. Product Overview and Features

The Monstrum Banshee 2-10x30 FFP MPVO Scope is engineered for versatility and precision, offering a range of features designed to enhance your shooting experience.

- **First Focal Plane (FFP) Reticle:** The reticle scales proportionally with magnification, ensuring consistent ranging and holdover values across all power settings.
- **Variable Magnification:** Offers a 2x to 10x magnification range, suitable for various distances.

- **Integrated Throw Lever:** Facilitates quick and smooth adjustments to magnification.
- **CM2 Reticle:** Designed for rapid target acquisition at low power and precise ranging at longer distances.
- **Extra Low Dispersion (ED) Glass:** Reduces chromatic aberration, providing superior color contrast and sharper image quality.
- **Inline Dial Controlled Reticle Illumination:** Multiple brightness intensities for visibility in varying light conditions.
- **Fully Multi-Coated Lenses:** Enhances light transmission and reduces glare for a brighter, clearer image.
- **Durable Construction:** Made from high-grade metal alloy for reliability.



Figure 2: Fully Multi-Coated Lens for enhanced clarity.




Figure 3: ED Glass reduces chromatic aberration for a clearer image.

3. Setup and Installation

3.1 Package Contents

Verify that your package contains the following items:

- Monstrum Banshee 2-10x30 FFP MPVO Scope
- Offset Cantilever Scope Mount
- Spring-Loaded Flip-Up Lens Covers

3.2 Mounting the Scope

The scope includes an offset cantilever mount designed for secure attachment to your rifle's Picatinny rail. Ensure the mount is properly aligned and tightened according to your rifle's specifications and the mount's instructions. Proper mounting is crucial for maintaining zero and accuracy.



Figure 4: Scope mounted on a rifle using the included cantilever mount.

3.3 Installing Battery for Illumination

The reticle illumination requires a battery (typically a CR2032 coin cell, check the battery compartment for specific type). Unscrew the illumination dial cap, insert the battery with the positive (+) side facing up, and securely replace the cap.

4. Operating Instructions

4.1 Magnification Adjustment

Rotate the magnification ring, located at the eyepiece end of the scope, to adjust the magnification from 2x to 10x. The integrated throw lever assists in quick and smooth transitions between magnification levels.

4.2 Diopter Adjustment

To achieve a clear reticle image, look through the scope at a plain, bright background (like the sky). Rotate the diopter

adjustment ring, located on the eyepiece, until the reticle appears sharp and in focus. This adjustment is personal and should be set for your individual eyesight.

4.3 Reticle Illumination

The illumination dial is located on the left side of the scope. Rotate the dial to turn on the reticle illumination and select your desired brightness level. There are multiple intensity settings, with 'off' positions between each setting for convenience.



Figure 5: Adjusting the illuminated reticle.

4.4 Windage and Elevation Adjustments

The scope features precise and tactile turrets for windage (horizontal adjustment) and elevation (vertical adjustment). These turrets are typically capped to prevent accidental adjustments. Remove the caps to access the adjustment dials. Each click of the turret corresponds to a specific change in point of impact (e.g., 1/4 MOA per click). Refer to the specifications for your specific model's click value. Rotate the turrets as needed for zeroing and ballistic corrections.




Figure 6: Precise and tactile turrets for adjustments.

5. Reticle Information: CM2 FFP Reticle

The Banshee 2-10x30 FFP MPVO Scope utilizes the CM2 First Focal Plane (FFP) reticle. Understanding FFP technology is crucial for accurate use.

5.1 What is a First Focal Plane (FFP) Reticle?

In an FFP scope, the reticle is positioned in front of the magnification lens system. This means the reticle's size appears to change (grow or shrink) in proportion to the magnification setting. The key advantage of an FFP reticle is that all ranging, holdover, and windage correction values remain consistent and accurate across the entire magnification range. For example, a 1 MOA hashmark will always represent 1 MOA, regardless of whether the scope is set to 2x or 10x magnification.



Figure 7: FFP vs. SFP Reticle Comparison.

5.2 CM2 Reticle Design

The CM2 Reticle is designed for both rapid target acquisition at lower magnifications and precise ranging at higher magnifications. Its clear markings allow for quick estimations and accurate shot placement.




Figure 8: CM2 Reticle at 2x and 10x magnification.




Figure 9: Field of View comparison at 2x and 10x magnification.

6. Maintenance

6.1 Cleaning the Lenses

Use a soft, lint-free cloth or a lens brush to remove dust and loose debris. For smudges or fingerprints, use a lens cleaning solution specifically designed for optics and a clean microfiber cloth. Avoid using harsh chemicals or abrasive materials, as these can damage the lens coatings.

6.2 General Care and Storage

Keep the scope protected with the included lens covers when not in use. Store the scope in a cool, dry place, away from direct sunlight and extreme temperatures. Avoid dropping or subjecting the scope to severe impacts, which can affect its internal components and zero.

7. Troubleshooting

- **Blurry Image:** Ensure the diopter is correctly adjusted for your eye. Check that the objective and eyepiece lenses are clean.
- **Reticle Not Illuminating:** Verify the battery is correctly installed and has sufficient charge. Replace the battery if necessary. Ensure the illumination dial is turned to an 'on' setting.
- **Loss of Zero:** Confirm that the scope mount is securely tightened to the rifle. Check for any damage to the scope or mount.
- **Stiff Turrets/Magnification Ring:** New scopes may have stiff controls. With regular use, these should loosen slightly. Do not force adjustments.

8. Specifications

Feature	Specification
Brand	Monstrum
Model Name	Banshee
Manufacturer Part Number	FFB210X-CM2
Magnification	2-10x
Objective Lens Diameter	30 mm
Reticle Type	CM2 Reticle (First Focal Plane)
Material	High-grade Metal Alloy
Color	Black
Mounting Type	Cantilever Mount
Compatible Devices	Rifles
UPC	810088817427

9. Warranty and Support

For warranty information and customer support, please refer to the official Monstrum website or contact their customer service directly. Keep your proof of purchase for any warranty claims.

© 2026 Monstrum. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question