

Compustar CS932-A

Compustar CS932-A 1-Way AP Vehicle Security System User Manual

Model: CS932-A

1. INTRODUCTION

This manual provides essential information for the proper installation, operation, and maintenance of your Compustar CS932-A 1-Way AP Vehicle Security System. This system is designed to enhance the security of your vehicle and provide convenient remote access features. Please read this manual thoroughly before attempting any installation or operation to ensure safe and effective use.

2. SAFETY INFORMATION

- **Professional Installation Recommended:** Installation of this vehicle security system requires specialized knowledge and tools. It is highly recommended that installation be performed by a certified Compustar dealer or a qualified automotive electronics technician. Improper installation can lead to vehicle damage, system malfunction, or personal injury.
- **Vehicle Compatibility:** Ensure this system is compatible with your vehicle's make, model, and year before installation. Consult your dealer for compatibility details.
- **Electrical Safety:** Disconnect the vehicle's battery before performing any wiring. Avoid short circuits and ensure all connections are secure and properly insulated.
- **Remote Control Usage:** Do not operate the remote control while driving. Ensure the vehicle is in a safe, parked position before using remote functions.
- **Children and Pets:** Never leave children or pets unattended in a vehicle, especially when the security system is armed or remote start features are active.

3. PACKAGE CONTENTS

Verify that all items are present in the package before proceeding with installation.

- Compustar CS932-A Control Module

- 1-Way Remote Control (Quantity: 1)
- Antenna Module
- Wiring Harnesses
- Installation Guide
- User Manual (this document)



Image 1: Illustrative view of the Compustar CS932-A system components, including the control module and remote.

4. SETUP AND INSTALLATION

As mentioned in the safety information, professional installation is strongly recommended for the Compustar CS932-A system. This section provides a general overview; detailed wiring diagrams and specific vehicle instructions are typically found in the separate installation guide provided to certified installers.

1. **Pre-Installation Check:** Ensure the vehicle battery is disconnected. Identify suitable mounting locations for the control module and antenna, away from heat sources and moving parts.
2. **Wiring Connections:** Connect the main power, ground, ignition, accessory, and starter wires according to the vehicle's wiring diagram and the system's installation guide. Integrate door trigger, hood trigger, and trunk trigger wires for comprehensive security.

3. **Antenna Placement:** Mount the antenna module on the vehicle's windshield, ensuring it has a clear line of sight to the remote control for optimal range (up to 200 feet).
4. **Remote Pairing:** Once the system is wired, the remote control must be paired with the control module. This typically involves a sequence of ignition cycles and button presses as detailed in the installation guide.
5. **System Testing:** After installation, reconnect the battery and thoroughly test all functions: arming/disarming, door lock/unlock, shock sensor, and any optional features.

5. OPERATING INSTRUCTIONS

The Compustar CS932-A system operates using a 1-way remote control. The remote sends commands to the vehicle, but does not receive confirmation back from the vehicle.

5.1 Remote Control Functions

Your 1-way remote control typically features a few buttons for primary functions:

- **Lock/Arm Button:** Press once to lock the doors and arm the security system. The vehicle's lights may flash once, and the horn may chirp once (if configured).
- **Unlock/Disarm Button:** Press once to unlock the doors and disarm the security system. The vehicle's lights may flash twice, and the horn may chirp twice (if configured).
- **Trunk Release Button (if configured):** Press and hold for a few seconds to open the vehicle's trunk or hatch.
- **Panic Button (if configured):** Press and hold for a few seconds to activate the alarm siren and flashing lights. Press again to deactivate.

5.2 Security System Indicators

The system uses the vehicle's parking lights and horn/siren to indicate its status:

- **Armed:** Parking lights flash once, horn/siren chirps once.
- **Disarmed:** Parking lights flash twice, horn/siren chirps twice.
- **Alarm Triggered:** Parking lights flash continuously, horn/siren sounds continuously.

6. MAINTENANCE

- **Remote Control Battery:** Replace the remote control battery when its range decreases significantly or it stops responding. Refer to the remote's specific manual for battery type and replacement instructions.
- **System Cleaning:** Keep the control module and antenna free from dust and moisture. Do not use harsh chemicals for cleaning.
- **Regular Checks:** Periodically test the system's functions (arming, disarming, shock sensor) to ensure proper operation.

7. TROUBLESHOOTING

Problem	Possible Cause	Solution
---------	----------------	----------

Problem	Possible Cause	Solution
Remote control not working.	Dead battery in remote. Out of range. Remote not paired.	Replace remote battery. Move closer to the vehicle. Re-pair remote (refer to installation guide).
System does not arm/disarm.	Door/hood/trunk open. Faulty sensor.	Ensure all doors, hood, and trunk are closed. Check for faulty sensors (professional inspection recommended).
Alarm triggers randomly.	Shock sensor sensitivity too high. Faulty sensor.	Adjust shock sensor sensitivity (professional adjustment recommended). Inspect for faulty sensors.
Reduced remote range.	Weak remote battery. Environmental interference. Antenna obstruction.	Replace remote battery. Avoid areas with high radio frequency interference. Ensure antenna is not obstructed.

If troubleshooting steps do not resolve the issue, contact your authorized Compustar dealer for assistance.

8. SPECIFICATIONS

Model: CS932-A

Brand: Compustar

Type: 1-Way AP Vehicle Security System

Compatible Devices: Cars

Maximum Range: 200 Feet

Remote Control: Included (1-Way)

Unit Count: 1.0 Count

Manufacturer: Compustar

UPC: 840127710600

ASIN: B0DCP97H54

9. WARRANTY AND SUPPORT

9.1 Warranty Information

The Compustar CS932-A Vehicle Security System comes with a **1 Year Warranty** from the date of purchase. This warranty covers defects in materials and workmanship under normal use. It does not cover damage caused by improper installation, accident, abuse, misuse, natural disaster, or unauthorized modification. Please retain your proof of purchase for warranty claims.

9.2 Customer Support

For technical assistance, troubleshooting, or warranty service, please contact your authorized Compustar dealer where the system was purchased or installed. You may also visit the official Compustar website for additional resources and contact information.

Official Compustar Website: www.compustar.com

