

## TOPAZ DLX

# Generic Topaz DLX Kitchen Chimney User Manual

Models: 60 cm, 75 cm, 90 cm

## 1. INTRODUCTION

This manual provides essential information for the safe and efficient operation, installation, and maintenance of your Generic Topaz DLX Kitchen Chimney. Please read these instructions carefully before using the appliance and retain them for future reference.

The Topaz DLX chimney is designed to remove smoke, steam, and cooking odors from your kitchen. It features a powerful BLDC motor, LED illumination, touch controls with a wave sensor, and a 3rd Generation DRY Auto Clean system for simplified maintenance.

## 2. SAFETY INSTRUCTIONS

To reduce the risk of fire, electric shock, or injury, observe the following safety precautions:

- **Electrical Safety:** Ensure the power supply matches the appliance's requirements (AC 220-240 V/50 Hz). Do not use extension cords or adapters. Disconnect power before servicing or cleaning.
- **Installation:** Installation must be performed by a qualified technician in accordance with local regulations. Ensure adequate ventilation in the room. The chimney must be securely mounted to a wall.
- **Usage:** This appliance is for household use only. Do not operate the chimney without filters. Do not flambé under the range hood. Never leave frying food unattended.
- **Maintenance:** Clean the appliance regularly to prevent grease buildup. Do not use abrasive cleaners or flammable liquids.
- **Children:** Keep children away from the appliance during operation and cleaning.

## 3. PACKAGE CONTENTS

Verify that all components are present and undamaged upon unpacking:

- Topaz DLX Kitchen Chimney Unit
- Exhaust Pipe (included free)
- Mounting Hardware (screws, wall plugs)
- User Manual

## 4. SETUP AND INSTALLATION

---

The Topaz DLX Kitchen Chimney is designed for wall-mounted installation. Professional installation is recommended.

### 4.1 Pre-Installation Checks

- Ensure the wall structure can support the weight of the chimney.
- Verify the availability of a suitable power outlet (AC 220-240 V/50 Hz).
- Confirm the exhaust ducting path is clear and leads to the outside. The outlet diameter is 150 mm.
- Choose the appropriate chimney size (60 cm, 75 cm, or 90 cm) based on your cooking range width.

### 4.2 Mounting Steps (General Guide)

1. Mark the drilling points on the wall according to the provided template (not included in this manual, refer to packaging).
2. Drill holes and insert wall plugs.
3. Secure the mounting bracket to the wall.
4. Carefully lift and attach the chimney unit to the mounting bracket.
5. Connect the exhaust pipe to the chimney outlet and route it to the exterior.
6. Connect the power cable to a grounded electrical outlet.



Image 1: Front view of the Topaz DLX Kitchen Chimney. This image shows the overall design of the chimney, including the control panel and the LED illumination strip.

## 5. OPERATING INSTRUCTIONS

---

The Topaz DLX chimney features a user-friendly touch control panel and a wave sensor for convenient operation.

### 5.1 Touch Control Panel

The control panel allows you to adjust suction speed, activate the auto-clean function, and control the LED lights. Specific icons on the panel correspond to these functions.

### 5.2 Wave Sensor Operation

The wave sensor enables hands-free control. Simply wave your hand in front of the sensor to turn the chimney on/off or adjust settings (refer to specific wave gestures in the quick start guide, if provided with the product).



*Image 2: Demonstration of the wave sensor feature. A hand is shown interacting with the sensor area to illustrate hands-free operation.*

### 5.3 Suction Power

The chimney offers a powerful suction capacity of  $1500 \pm 50 \text{ m}^3/\text{Hr}$  to effectively remove smoke and odors. Adjust the suction level via the touch control panel as needed for different cooking intensities.



*Image 3: Visual representation of the chimney's suction power. Arrows indicate air being drawn into the chimney, illustrating its function.*

## 5.4 LED Illumination

The integrated LED lights provide clear illumination over your cooking area. These lights can be controlled independently via the touch panel.

## 6. MAINTENANCE

---

Regular maintenance ensures optimal performance and longevity of your chimney.

### 6.1 3rd Generation DRY Auto Clean

The chimney is equipped with an advanced DRY, 3rd Generation Auto Clean feature. Activate this function via the touch control panel. This system helps to melt and collect grease, simplifying the cleaning process.



*Image 4: Close-up view highlighting the "3rd Generation DRY Auto-Clean" feature, indicating its presence on the chimney model.*

## **6.2 Filter Cleaning (Mesh Filter)**

The chimney uses a mesh filter. While the auto-clean function reduces manual cleaning, periodic inspection and cleaning of the mesh filter and metal oil collector are recommended. Refer to the product's quick start guide for detailed instructions on removing and cleaning these components.



Image 5: Overview of key features including Filterless Technology (referring to the auto-clean system reducing filter maintenance), Wave Sensor, LED Panel, and Metal Oil Collector.

## 6.3 Exterior Cleaning

Wipe the exterior surfaces with a soft, damp cloth and mild detergent. Do not use abrasive cleaners or solvents.

## 7. TROUBLESHOOTING

Before contacting customer support, refer to the following common issues and solutions:

| Problem                   | Possible Cause                                                  | Solution                                                                                  |
|---------------------------|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| Chimney does not turn on. | No power supply; loose connection; power outage.                | Check power cord connection; verify power outlet functionality; check circuit breaker.    |
| Low suction power.        | Clogged filters; blocked exhaust duct; incorrect speed setting. | Clean filters and oil collector; check exhaust duct for obstructions; increase fan speed. |

| Problem                 | Possible Cause                                                  | Solution                                                                                               |
|-------------------------|-----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| Excessive noise.        | Loose components; foreign object in fan; improper installation. | Ensure all parts are secure; inspect fan for obstructions (disconnect power first); consult installer. |
| LED lights not working. | Bulb failure; electrical issue.                                 | Check light switch; if problem persists, contact service.                                              |

## 8. SPECIFICATIONS

Detailed technical specifications for the Topaz DLX Kitchen Chimney:

| Feature                        | Detail                                                                                       |
|--------------------------------|----------------------------------------------------------------------------------------------|
| Brand                          | Generic                                                                                      |
| Model Number                   | TOPAZ DLX                                                                                    |
| Available Sizes                | 60 cm, 75 cm, 90 cm                                                                          |
| Voltage / Frequency            | AC 220-240 V / 50 Hz                                                                         |
| Motor Power                    | 1 x 150 W (BLDC Motor)                                                                       |
| Total Power Consumption        | 209 W                                                                                        |
| Illumination Type              | LED                                                                                          |
| Illumination Power             | 2 x Max 1.5 W                                                                                |
| Auto Clean Type                | DRY, 3rd Generation                                                                          |
| Suction Capacity               | 1500±50m³/Hr                                                                                 |
| Noise Level                    | 58 dB                                                                                        |
| Controls Type                  | Touch Control with Wave Sensor                                                               |
| Outlet Diameter                | 150 mm                                                                                       |
| Filter Type                    | Mesh                                                                                         |
| Product Dimensions (L x W x H) | 60 cm: L595 X W480 X H575 mm<br>75 cm: L745 X W480 X H575 mm<br>90 cm: L895 X W480 X H575 mm |
| Item Weight                    | 12 Kilograms                                                                                 |

# TOPAZ DLX

## TECHNICAL SPECIFICATIONS

|                             |                                |
|-----------------------------|--------------------------------|
| Size                        | 60 cm, 75 cm, 90 cm            |
| Voltage / Frequency         | AC 220-240 V / 50 Hz           |
| Motor Power (W)             | 1 x 150 W (BLDC MOTOR)         |
| Illumination Type           | LED                            |
| Illumination Power          | 2 x Max 1.5 W                  |
| Auto Clean Type             | DRY, 3rd Generation            |
| Total Power (W)             | 209 W                          |
| Suction (m <sup>3</sup> /h) | 1500±50m <sup>3</sup> /Hr      |
| Noise Level (dBA)           | 58 db                          |
| Switch Control              | Touch Control with Wave Sensor |
| Outlet Diameter             | 150 mm                         |
| Unit Dimension 60 cm        | L595 X W480 X H575 mm          |
| Unit Dimension 75 cm        | L745 X W480 X H575 mm          |
| Unit Dimension 90 cm        | L895 X W480 X H575 mm          |



Image 6: A visual representation of the technical specifications, including dimensions, power, and features, for the Topaz DLX chimney.

## 9. WARRANTY AND SUPPORT

### 9.1 Warranty Information

The Generic Topaz DLX Kitchen Chimney comes with a **2-year brand warranty**. Please retain your purchase receipt for warranty claims. The warranty covers manufacturing defects under normal use conditions.

### 9.2 Customer Support

For technical assistance, service requests, or warranty claims, please contact the manufacturer or authorized service center.

- **Manufacturer:** KUTCHINA
- **Packer Contact Information:** SONAI ROAD, NEAR BM TECHNOLOGY, SILCHAR, ASSAM, 788006
- Please refer to the product packaging or official website for the most current contact details.