SimPure SimPure Q3-600

SimPure Q3-600 Tankless Reverse Osmosis System User Manual

Model: SimPure Q3-600

1. Product Overview

The SimPure Q3-600 is a state-of-the-art tankless reverse osmosis water filtration system designed for under-sink installation. It provides clean, purified water on demand, eliminating the need for a bulky storage tank. This system is certified against SGS and complies with NSF/ANSI 58 standards, effectively removing 99.99% of over 1,000 contaminants from your tap water. The package also includes a high-accuracy TDS meter for monitoring water quality.



Image: SimPure Q3-600 RO system, accompanying faucet, and a digital TDS meter.

Key Features:

- SGS Certified & NSF/ANSI 58 Compliant: Removes 99.99% of 1,000+ contaminants.
- 600 GPD High Flow Rate: Delivers a cup of pure water in approximately 8 seconds.
- 2:1 Pure to Drain Ratio: Efficient water usage, saving up to 1,057 barrels of water per filter set compared to traditional systems.
- Tankless Design: Saves space and provides fresh water on demand without a storage tank.
- Fresh Water Technology: No need to waste the first cup of water due to high TDS.
- High Accuracy TDS Meter: Provides accurate and quick readings of TDS and temperature.

2. Product Components

The SimPure Q3-600 system comes with the following components:

- 1 x SimPure Q3-600 Tankless Reverse Osmosis System Unit
- 1 x TDS Meter Digital Water Tester
- Necessary installation accessories (faucet, tubing, connectors - implied by system type)
- Filter cartridges (implied by "1 set of filters" and images)



Image: The main components of the SimPure Q3-600 package, including the RO unit and TDS meter.

3. Setup and Installation

The SimPure Q3-600 is designed for under-sink installation. Please ensure you have adequate space and access to a cold water line and a drain. Professional installation is recommended if you are unfamiliar with plumbing work.

Space Requirements:

The tankless design of the Q3-600 saves significant under-sink space compared to traditional RO systems with tanks. The unit dimensions are approximately 6.5 inches (width) x 13.5 inches (depth) x 12 inches (height).



Image: The SimPure Q3-600 unit neatly installed under a kitchen counter, highlighting its compact, tankless design.

Installation Steps (General Overview):

1. Turn off the cold water supply and relieve pressure.

2. Install the included faucet on your sink or countertop.
3. Connect the system to the cold water supply using the provided adapter.
4. Connect the drain line to your sink's drain pipe.
5. Insert the filter cartridges into the system unit.
6. Connect the purified water line from the system to the new faucet.
7. Turn on the water supply and check for leaks.
8. Flush the system according to the initial startup instructions (refer to the detailed manual for specific flushing times).

For detailed, step-by-step installation instructions, please refer to the comprehensive manual included in your product packaging.

4. Operating Instructions

Water Dispensing:

To dispense purified water, simply turn on the dedicated RO faucet. The Q3-600 provides instant purified water at a high flow rate of 600 GPD, meaning you can fill a cup in approximately 8 seconds. There is no need to drain the first cup of water, as the system provides fresh water on demand.



Image: Visual representation of the SimPure Q3-600's 600 GPD flow rate, indicating a cup of water can be filled in 8 seconds.

Using the TDS Meter:

The included SimPure TDS meter allows you to quickly and accurately measure the Total Dissolved Solids (TDS) and temperature of your water. This helps you monitor the performance of your RO system and ensure water quality.

1. Turn on the TDS meter by pressing the "ON/OFF" button.
2. Dip the probe end of the meter into the water sample (e.g., a glass of tap water or purified water).
3. Wait for the reading to stabilize on the digital display.
4. The display will show the TDS level in parts per million (ppm). Press the "TEMP" button to switch to temperature reading.
5. A green display indicates TDS levels below 40 ppm, while a red display indicates TDS levels at or above 40 ppm, suggesting potential issues or higher impurity levels.
6. Press "HOLD" to freeze the reading for easier viewing.
7. Turn off the meter after use to conserve battery.



Image: The SimPure TDS meter showing its green display for low TDS water and red display for high TDS water, indicating water quality.



Image: A hand holding the SimPure TDS meter, demonstrating its ease of use by dipping it into a glass of water to get a reading.

5. Maintenance

Filter Replacement:

The SimPure Q3-600 system utilizes multiple stages of filtration, including CF (Composite Filter) and RO (Reverse Osmosis) membranes. Filter lifespan depends on local water quality and usage. The system typically indicates when filters need replacement. Regular filter replacement ensures optimal performance and water quality.
Refer to the detailed product manual for specific filter replacement intervals and instructions. Always use genuine SimPure replacement filters to maintain system warranty and performance.



Image: Two SimPure filter cartridges, labeled CF (Composite Filter) and RO (Reverse Osmosis), which are essential for the system's filtration process.

Cleaning:

Periodically wipe down the exterior of the RO system unit and faucet with a clean, damp cloth. Do not use abrasive cleaners or solvents.

6. Troubleshooting

If you encounter any issues with your SimPure Q3-600 system, please refer to the following common troubleshooting tips. For more complex problems, contact SimPure customer support.

Problem	Possible Cause	Solution

Problem	Possible Cause	Solution
Low Water Flow	Clogged filters, low incoming water pressure, kinked tubing.	Check water supply, replace filters, inspect tubing for kinks.
High TDS Reading	Worn out RO membrane, improper flushing, high incoming TDS.	Replace RO membrane, ensure proper flushing after installation, check incoming water quality.
Leaking	Loose connections, damaged O-rings, cracked housing.	Tighten all connections, inspect and replace O-rings if damaged, contact support if housing is cracked.
Unusual Noise	Air in the system, pump issues.	Allow system to run to purge air, contact support if noise persists.

7. Specifications

- **Model Name:** SimPure Q3-600
- **Purification Method:** Reverse Osmosis
- **Installation Type:** Under Sink
- **Special Feature:** Tankless, NSF certified (SGS Certified & NSF/ANSI 58 Compliant)
- **Supported Water TDS Level Maximum:** 1000 PPM
- **Manufacturer:** SimPure
- **Item Model Number:** SimPure Q3-600
- **ASIN:** B0DDKYMHHK

8. Warranty and Support

Return Policy:

This product is eligible for a 30-day return policy, allowing for a refund or replacement. Please refer to your purchase platform's specific return guidelines for detailed information.

Customer Support:

For technical assistance, warranty claims, or general inquiries regarding your SimPure Q3-600 system, please contact SimPure customer support. You can find more information and contact details on the official SimPure store page:

Visit the SimPure Store on Amazon

© 2024 SimPure. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question