

TOUCHUP KING 726R

TOUCHUP KING Custom 2K Paint Kit Instruction Manual

Model: 726R - Daewoo Green Cocktail Metallic

1. PRODUCT OVERVIEW

This TOUCHUP KING Custom 2K Paint Kit provides a high-quality solution for automotive paint repair. It includes one can of urethane-based basecoat paint, precisely matched to your vehicle's color, and one can of Touch Up King 2K High Gloss Glamour Clear Coat Spray/Aerosol. The kit is designed to deliver professional results with superior gloss and depth. The proprietary 2K Clearcoat technology is pre-catalyzed inside the can and activates upon release, ensuring an easy-to-use application and a durable, high-gloss finish.



Image 1.1: The TOUCHUP KING Custom 2K Paint Kit, featuring a can of custom-matched basecoat paint and a can of 2K high-gloss clear coat. Both cans are aerosol format, designed for easy application and a professional finish.

Key Features:

- **Perfect Color Match:** Custom paint tailored to your vehicle's exact color code for a flawless match.
- **High-Quality 2K Finish:** Pre-catalyzed 2K Clearcoat technology activates upon release, providing a durable, high-gloss finish.
- **Easy Application:** User-friendly aerosol formula for smooth and even coverage.
- **Superior Urethane-Based Paint:** Ensures accurate color reproduction.
- **UV & Weather Resistant:** Protects against fading, chipping, and environmental damage.
- **Versatile Use:** Suitable for cars, trucks, motorcycles, and other applications.
- **Fast Drying Time:** Allows for quicker project completion.
- **OEM Color Compatibility:** Designed to perfectly match original factory colors for seamless repair.

2. SAFETY INFORMATION

WARNING: This product contains chemicals known to be flammable, harmful, and an irritant. Always prioritize safety during application.

- **Ventilation:** Use in a well-ventilated area. Avoid breathing vapors. If working indoors, ensure adequate airflow or use a respirator.
- **Personal Protective Equipment (PPE):** Wear appropriate PPE, including safety glasses or goggles to protect eyes, chemical-resistant gloves to protect skin, and a respirator approved for organic vapors.
- **Flammability:** Keep away from heat, sparks, open flames, and hot surfaces. Do not smoke during application.
- **Storage:** Store in a cool, dry, well-ventilated place, away from direct sunlight and sources of ignition. Keep out of reach of children and pets.
- **First Aid:**
 - **Inhalation:** If inhaled, move to fresh air. If breathing is difficult, administer oxygen. Seek medical attention.
 - **Skin Contact:** Wash thoroughly with soap and water. Remove contaminated clothing.
 - **Eye Contact:** Rinse immediately with plenty of water for at least 15 minutes, holding eyelids open. Seek medical attention.
 - **Ingestion:** Do NOT induce vomiting. Call a poison control center or doctor immediately.
- **Disposal:** Dispose of contents and container in accordance with local, regional, national, and international regulations.

3. PACKAGE CONTENTS

Your TOUCHUP KING Custom 2K Paint Kit includes the following items:

- 1 x Aerosol Can of Custom-Matched Urethane-Based Basecoat Paint (Daewoo Green Cocktail Metallic, Model 726R)
- 1 x Aerosol Can of TOUCHUP KING 2K High Gloss Glamour Clear Coat

4. SETUP AND PREPARATION

4.1. Work Area Preparation

- Ensure the work area is clean, dry, and well-ventilated.
- Maintain an ambient temperature between 65°F (18°C) and 75°F (24°C) with low humidity for optimal results.
- Protect surrounding areas from overspray using masking tape and paper/plastic sheeting.

4.2. Surface Preparation

- Clean the surface thoroughly with a wax and grease remover to eliminate contaminants.
- Sand the repair area with appropriate grit sandpaper (e.g., 400-600 grit for existing paint, finer for primer) to create a smooth, even surface for adhesion.
- Wipe the sanded area with a tack cloth to remove any dust or debris.
- Mask off any areas not intended for painting.

4.3. Can Preparation

- Shake the basecoat can vigorously for at least one minute after the mixing ball begins to rattle. Continue shaking periodically during application.
- For the 2K Clear Coat, refer to Section 5.2 for activation instructions.

5. OPERATING INSTRUCTIONS (APPLICATION)

5.1. Basecoat Application

1. **Test Spray:** Before applying to the vehicle, perform a test spray on a piece of scrap material to check color match and spray pattern.
2. **First Coat:** Hold the can approximately 8-10 inches (20-25 cm) from the surface. Apply a light, even mist coat. This coat should appear slightly mottled.
3. **Flash Time:** Allow 5-10 minutes flash time between coats, or until the paint appears dull.
4. **Subsequent Coats:** Apply medium, even coats, overlapping each pass by about 50%. Continue applying coats until full coverage and desired color depth are achieved. Typically 2-3 coats are sufficient.
5. **Final Flash:** After the last basecoat, allow 30-60 minutes for the basecoat to fully flash off before applying clear coat. The surface should be dull and dry to the touch.

5.2. 2K High Gloss Clear Coat Application

The 2K Clear Coat is a two-component system activated just before use. Once activated, the pot life is limited.

1. **Activation:**
 - Remove the red button from the cap.
 - Place the can on a firm surface.
 - Attach the red button to the pin on the bottom of the can.
 - Press the red button firmly until the pin punctures the inner container.
 - Shake the can vigorously for at least 2 minutes to ensure thorough mixing of the two components.
2. **Pot Life:** Once activated, the clear coat has a pot life of approximately 24-48 hours, depending on temperature. Use within this timeframe.
3. **Test Spray:** Perform a test spray on scrap material to check the spray pattern.
4. **First Coat:** Apply a light, even mist coat over the basecoat.
5. **Flash Time:** Allow 5-10 minutes flash time between coats.
6. **Subsequent Coats:** Apply 2-3 medium wet coats, allowing proper flash time between each. Aim for a smooth, glossy finish. Avoid applying too heavily to prevent runs.
7. **Drying Time:** The clear coat will be dust-free in approximately 30 minutes, touch-dry in 2-4 hours, and fully cured in 24-48 hours (depending on temperature and humidity).

6. MAINTENANCE AND CARE

- Allow the clear coat to fully cure before washing or waxing the painted area. This typically takes 24-48 hours.
- After full cure, treat the repaired area like the rest of your vehicle's finish. Wash with mild automotive soap and wax regularly to maintain gloss and protection.
- Avoid harsh chemicals or abrasive cleaners on the newly painted surface.

7. TROUBLESHOOTING

Problem	Possible Cause	Solution
---------	----------------	----------

Problem	Possible Cause	Solution
Runs or Sags	Applying paint too heavily or holding the can too close.	Apply lighter, more even coats. Maintain proper distance from the surface. Allow adequate flash time between coats.
Poor Adhesion / Peeling	Improper surface preparation (e.g., not cleaned, not sanded).	Ensure surface is thoroughly cleaned, degreased, and properly sanded before application.
Uneven Finish / Mottling	Inconsistent spray pattern, insufficient shaking of can, or improper application technique.	Shake cans thoroughly. Apply even, overlapping passes. Practice on scrap material first.
Dull Finish (Clear Coat)	Insufficient clear coat applied, improper activation of 2K clear, or environmental conditions.	Ensure 2K clear coat is fully activated and shaken. Apply 2-3 medium wet coats. Ensure proper temperature and humidity.

8. SPECIFICATIONS

Brand	TOUCHUP KING
Model Number	726R
Color	Daewoo Green Cocktail Metallic
Item Volume	12 Fluid Ounces (6 oz Basecoat, 6 oz Clear Coat)
Item Form	Aerosol
Basecoat Type	Urethane-Based
Clear Coat Type	2K High Gloss Glamour Clear Coat (Pre-catalyzed)
Manufacturer	Sherwin

9. WARRANTY AND SUPPORT

For specific warranty information or technical support regarding your TOUCHUP KING Custom 2K Paint Kit, please contact the manufacturer directly. Refer to the product packaging or the official TOUCHUP KING website for contact details.

Manufacturer: Sherwin

Brand: TOUCHUP KING