

TOUCHUP KING 1262D

TOUCHUP KING Custom 2K Paint Kit User Manual

For Aston Martin Tungsten Silver Metallic (Color Code 1262D)

1. INTRODUCTION

This manual provides detailed instructions for the proper use and application of the TOUCHUP KING Custom 2K Paint Kit. This kit is designed to provide a professional-quality finish for your Aston Martin, matching the Tungsten Silver Metallic color (1262D). It includes a urethane-based basecoat and a 2K high-gloss glamour clear coat for superior durability and appearance.

2. SAFETY INFORMATION

WARNING: FLAMMABLE. VAPOR HARMFUL. IRRITANT.

- Use in a well-ventilated area. Avoid breathing vapors.
- Wear appropriate personal protective equipment (PPE), including gloves, eye protection, and a respirator.
- Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
- Store in a cool, dry place, out of direct sunlight and away from children and pets.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, wash immediately with soap and water.
- Dispose of contents/container in accordance with local regulations.

3. KIT CONTENTS

Your TOUCHUP KING Custom 2K Paint Kit includes the following items:

- One (1) can of Custom Matched Basecoat Paint (Urethane-based, Aston Martin Tungsten Silver Metallic 1262D)
- One (1) can of TOUCHUP KING 2K High-Gloss Glamour Clear Coat Spray/Aerosol



Image 1: The TOUCHUP KING Custom 2K Paint Kit, showing the basecoat and 2K clear coat aerosol cans. The basecoat can is labeled 'BASECOAT CUSTOM MATCHED PAINT' and includes warnings about flammability. The clear coat can is labeled 'UNIVERSAL 2K HI-GLOSS CLEAR COAT' and indicates fast drying and UV protection.

4. SETUP AND PREPARATION

Proper preparation is crucial for a successful paint application and durable finish.

1. **Clean the Surface:** Thoroughly clean the area to be painted. Remove all dirt, grease, wax, and rust. Use a suitable automotive degreaser or wax and grease remover.
2. **Sand the Surface:** Lightly sand the repair area with fine-grit sandpaper (e.g., 400-600 grit wet/dry) to create a smooth, even surface for paint adhesion. Feather the edges of the repair area.
3. **Masking:** Carefully mask off surrounding areas that you do not wish to paint using automotive masking tape and paper or plastic sheeting. Ensure clean, crisp edges.
4. **Temperature and Humidity:** Apply paint in a dry, dust-free environment with temperatures between

65°F and 75°F (18°C and 24°C) and relative humidity below 60%. Avoid direct sunlight.

5. **Shake Cans:** Before use, shake each aerosol can vigorously for at least 2 minutes after the mixing ball begins to rattle. Continue shaking periodically during application.
6. **Test Spray:** Always perform a test spray on a scrap piece of material to check color match, spray pattern, and flow.

5. OPERATING INSTRUCTIONS (PAINT APPLICATION)

Follow these steps for optimal results:

5.1. Basecoat Application

1. Hold the basecoat can approximately 8-10 inches (20-25 cm) from the surface.
2. Apply the basecoat in thin, even coats using a steady, sweeping motion. Overlap each pass by about 50%.
3. Allow 5-10 minutes flash time between coats, or until the paint appears dull and dry to the touch.
4. Apply 2-3 coats, or until full coverage and desired color depth are achieved.
5. After the final basecoat, allow it to dry for at least 30-60 minutes before applying the clear coat. The basecoat should be completely dry and dull.

5.2. 2K High-Gloss Clear Coat Application

Important: The 2K Clearcoat is pre-catalyzed and activates upon release. Once activated, the pot life is limited (typically 24-48 hours, depending on temperature). Plan to complete your clear coat application within this timeframe.

1. **Activate the Clear Coat:** Follow the instructions on the clear coat can to activate the 2K clear coat. This usually involves pressing a button on the bottom of the can or twisting a component to release the hardener. Shake vigorously for 2 minutes after activation.
2. Hold the clear coat can approximately 8-10 inches (20-25 cm) from the surface.
3. Apply the clear coat in medium-wet, even coats. The first coat should be a light mist coat to promote adhesion.
4. Allow 5-10 minutes flash time between coats. The surface should appear slightly tacky but not wet.
5. Apply 2-3 full, wet coats to achieve a high-gloss finish and maximum protection. Avoid applying too heavily to prevent runs.
6. After the final clear coat, allow the painted surface to cure. Initial dry time is typically 1-2 hours, but full cure can take 24-72 hours depending on environmental conditions. Avoid washing or waxing the area for at least 7 days.

6. MAINTENANCE

Once the paint has fully cured, maintain the finish as you would the rest of your vehicle's paintwork.

- Wash with mild automotive soap and a soft sponge or microfiber cloth.
- Avoid abrasive cleaners or harsh chemicals.
- Regular waxing or sealant application can help protect the clear coat and maintain its gloss.

7. TROUBLESHOOTING

Problem	Possible Cause	Solution
Runs or Sags	Too much paint applied in one coat; can held too close.	Apply thinner coats; hold can further from surface. Allow to dry, then sand and reapply.
Orange Peel	Paint applied too dry; insufficient wetness; improper atomization.	Apply slightly wetter coats; ensure proper shaking. Can be wet-sanded and polished after full cure.
Poor Adhesion	Improper surface preparation (grease, dirt, insufficient sanding).	Ensure surface is thoroughly cleaned and properly sanded before painting.
Dull Finish (Clear Coat)	Insufficient clear coat applied; improper activation of 2K clear.	Ensure 2K clear coat is properly activated and applied in sufficient wet coats. After full cure, can be polished.

8. SPECIFICATIONS

- **Brand:** TOUCHUP KING
- **Model Number:** 1262D
- **Color:** Tungsten Silver Metallic (Custom Matched)
- **Item Form:** Aerosol
- **Item Volume:** 12 Fluid Ounces (Total, 6 oz per can)
- **Paint Type:** Urethane-based Basecoat, 2K High-Gloss Clear Coat
- **Manufacturer:** Sherwin

9. WARRANTY AND SUPPORT

For warranty information or technical support, please refer to the TOUCHUP KING official website or contact their customer service directly. Keep your purchase receipt as proof of purchase.

Contact Information: Please visit the [TOUCHUP KING Store on Amazon](#) for further details and support options.