

TOUCHUP KING 147

TOUCHUP KING Custom 2K Paint Kit for Daewoo CZERWON RED 147 User Manual

PRODUCT OVERVIEW

This manual provides instructions for the TOUCHUP KING Custom 2K Paint Kit, designed for achieving a professional-grade finish on automotive surfaces. The kit includes a custom-matched urethane-based basecoat and a 2K high-gloss glamour clear coat, formulated for durability and superior aesthetic results.

Key Features

- **Perfect Color Match:** Custom paint tailored to your vehicle's exact color code.
- **High-Quality Finish:** 2K Clearcoat technology ensures a durable, high-gloss finish with excellent depth of image.
- **Easy Application:** User-friendly formula for smooth and even coverage.
- **Superior Urethane-Based Paint:** Offers excellent color accuracy and adhesion.
- **UV & Weather Resistant:** Protects against fading, chipping, and weather-related damage.
- **Versatile Use:** Suitable for cars, trucks, motorcycles, and miscellaneous automotive applications.
- **Fast Drying Time:** Allows for quicker project completion and handling.
- **OEM Color Compatibility:** Perfectly matches original factory colors for seamless repairs.

PRODUCT COMPONENTS



The TOUCHUP KING Custom 2K Paint Kit includes two aerosol cans: one for the custom-matched basecoat paint and one for the 2K Hi-Gloss Clear Coat. The basecoat is formulated for precise color matching, while the clear coat provides a durable, high-gloss protective layer.

SETUP AND PREPARATION

Safety Precautions

- Work in a well-ventilated area to prevent inhalation of fumes.
- Wear appropriate personal protective equipment (PPE), including gloves, eye protection, and a respirator.
- Keep away from open flames, sparks, and other heat sources.
- Refer to the warning label on the product for detailed safety information regarding flammability and irritants.

Surface Preparation

1. Clean the surface thoroughly to remove all dirt, grease, wax, and rust. Use a suitable automotive degreaser.
2. Sand the repair area with appropriate grit sandpaper (e.g., 400-600 grit wet sanding) to ensure proper adhesion. Feather edge the repair area into the surrounding paint.
3. Wipe the surface with a tack cloth to remove any sanding dust or contaminants.
4. Mask off adjacent areas to protect them from overspray.

APPLICATION INSTRUCTIONS

Basecoat Application

1. Shake the basecoat can vigorously for at least one minute after the mixing ball begins to rattle.
2. Perform a test spray on a scrap piece of material to check color match and spray pattern.
3. Hold the can approximately 8-10 inches (20-25 cm) from the surface.
4. Apply thin, even coats using a steady, sweeping motion. Overlap each pass by about 50%.
5. Allow 5-10 minutes flash time between coats. Apply 2-3 coats or until full coverage is achieved.
6. Allow the basecoat to dry for at least 30-60 minutes before applying the clear coat.

2K Hi-Gloss Clear Coat Application

1. Before activating, shake the 2K Clear Coat can vigorously for at least one minute.
2. To activate the 2K clear coat, remove the red button from the cap. Place the can on a firm surface. Invert the can and place the red button onto the pin on the bottom of the can. Press the red button firmly until it clicks.
3. Shake the activated can vigorously for at least two minutes to ensure proper mixing of components.
4. Perform a test spray on a scrap piece of material to verify spray pattern.
5. Hold the can approximately 8-10 inches (20-25 cm) from the surface.
6. Apply 2-3 medium wet coats, allowing 10-15 minutes flash time between coats.
7. Avoid applying too heavily in one area to prevent runs or sags.
8. The clear coat will be touch-dry in approximately 1-2 hours and fully cured in 24-48 hours, depending on temperature and humidity.

CARE AND MAINTENANCE

To maintain the finish, avoid harsh chemicals or abrasive cleaners for the first 30 days after application, as the paint continues to cure. Wash the painted area with mild automotive soap and water. Regular waxing after the full cure period (typically 30 days) can help protect the finish, enhance its gloss, and extend its lifespan.

TROUBLESHOOTING COMMON ISSUES

Issue	Possible Cause	Solution
Orange Peel	Paint applied too dry or too thick; improper can distance.	Apply slightly wetter coats; maintain consistent distance; light wet sanding and polishing after full cure.

Issue	Possible Cause	Solution
Runs/Sags	Paint applied too heavily in one area; insufficient flash time between coats.	Apply thinner, more even coats; increase flash time between coats.
Poor Adhesion	Inadequate surface preparation; surface not clean or properly sanded.	Ensure thorough cleaning and proper sanding of the surface before painting.
Dull Finish (Clear Coat)	Insufficient clear coat applied; improper mixing/activation of 2K clear.	Apply recommended number of clear coats; ensure 2K clear is properly activated and shaken.

PRODUCT SPECIFICATIONS

Brand	TOUCHUP KING
Color	CZERWON RED
Model Number	147
Item Volume	12 Fluid Ounces (total)
Unit Count	12.0 Ounce
Item Form	Aerosol
Manufacturer	Sherwin
Date First Available	August 30, 2024

WARRANTY INFORMATION

For specific warranty details regarding your TOUCHUP KING Custom 2K Paint Kit, please refer to the product packaging or contact TOUCHUP KING customer support directly. Warranty terms typically cover manufacturing defects.

CUSTOMER SUPPORT

If you require further assistance or have questions about the TOUCHUP KING Custom 2K Paint Kit, please visit the official TOUCHUP KING website or contact their customer service department. Contact information can typically be found on the product packaging or the brand's official online presence.