

LIVINGbasics GZA-00048

LIVINGbasics Bidet Toilet Attachment User Manual

Model: GZA-00048

1. INTRODUCTION

Thank you for choosing the LIVINGbasics Bidet Toilet Attachment. This non-electric bidet provides a hygienic and comfortable cleaning experience with adjustable hot and cold water temperature, pressure control, and dual self-cleaning nozzles. This manual provides detailed instructions for installation, operation, and maintenance to ensure optimal performance and longevity of your product.



Image 1.1: The LIVINGbasics Bidet Toilet Attachment shown installed on a standard toilet, highlighting its compact design and control panel.

2. SAFETY INFORMATION

- Always turn off the main water supply valve and drain the toilet tank before beginning installation.
- Ensure all connections are tight to prevent leaks. Do not overtighten.
- This product is designed for use with standard potable water supplies.
- Do not use abrasive cleaners or harsh chemicals on the bidet attachment, as this may damage the finish or internal components.
- Keep out of reach of children during installation to prevent accidental ingestion of small parts.

3. PACKAGE CONTENTS

Please verify that all components are present before installation:

- LIVINGbasics Bidet Toilet Attachment
- Cold Water Flexible Metal Pipe (15/16" to 9/16")
- Hot Water Flexible Metal Pipe (1/2" to 9/16")

- Plastic Cold Water Adapter (7/8" to 15/16")
- Metal Hot Water Adapter (3/8" to 15/16")
- 0.8m Plastic Tube
- 2.2m Plastic Tube
- Faucet Tape
- Rubber Washers
- User Manual



Image 3.1: A visual representation of all included accessories and connection pipes for the bidet attachment.

4. PRODUCT FEATURES

- **Hot and Cold Water Supply:** Connects to both hot and cold water lines for temperature-controlled washing. Can be used with cold water only if hot water connection is unavailable.
- **Dual Nozzles:** Features two separate nozzles: one for regular rear washing and a second for feminine use, designed with a different angle and more holes for a gentler spray.
- **Self-Cleaning Function:** Retractable nozzles include a self-cleaning feature to maintain hygiene.

- **Adjustable Spray:** Control dial allows adjustment of water pressure and temperature for personalized comfort.
- **Durable Construction:** Made from impact-resistant and corrosion-resistant ABS material for long-lasting use.
- **Easy Installation:** Designed for quick and straightforward installation on most standard toilets.

Dual nozzle system



Highlight: Illustrate the two nozzles, showing the different angles and spray patterns for rear and feminine use.

Image 4.1: A detailed view of the bidet's dual nozzle system, illustrating the distinct spray patterns for rear and feminine wash functions.

5. SETUP AND INSTALLATION

Follow these steps for proper installation of your bidet attachment:

1. **Turn off Water Supply:** Locate the main water supply valve for your toilet and turn it off. Flush the toilet to drain the tank completely.
2. **Remove Toilet Seat:** Remove the existing toilet seat by unscrewing the bolts at the back of the toilet bowl.
3. **Position Bidet Attachment:** Place the bidet attachment on the toilet bowl, aligning the mounting holes with the toilet seat holes. Adjust the position to ensure a proper fit. The mounting hole distance is adjustable from 140mm to 200mm (5.51" to 7.87").

4. **Reinstall Toilet Seat:** Place your toilet seat back on top of the bidet attachment and secure it with the original bolts. Ensure the bidet is stable.
5. **Connect Cold Water:** Disconnect the cold water supply line from the toilet tank. Install the Plastic Cold Water Adapter (T-adapter) to the toilet tank's fill valve. Connect the cold water flexible metal pipe from the adapter to the bidet's cold water inlet.
6. **Connect Hot Water (Optional):** If connecting hot water, locate a hot water source near the toilet (e.g., under the sink). Install the Metal Hot Water Adapter to the hot water supply. Connect the hot water flexible metal pipe from the adapter to the bidet's hot water inlet. Use the provided plastic tubes to extend connections if necessary.
7. **Check Connections:** Ensure all connections are secure and hand-tightened. Use faucet tape on threaded connections if needed to prevent leaks.
8. **Restore Water Supply:** Slowly turn the main water supply valve back on. Check for any leaks. If leaks occur, tighten the connections.



Image 5.1: A step-by-step diagram showing the installation process, from removing the toilet seat to connecting the hot and cold water lines.

ULTRA-SLIM TOILET BIDET

Ultra-slim bidet provides better toilet seat fit



SCOPE OF APPLICATION



Tow-piece ✓

One-piece ✓

Skirted ✓

Concealed ✗

Please note: it must be placed on a flat toilet surface and can only be used with toilet seats that have a flat bottom

Image 5.2: This image illustrates the adjustable mounting hole distance (140mm to 200mm) on the bidet attachment, ensuring compatibility with various toilet designs.

6. OPERATING INSTRUCTIONS

The bidet attachment features intuitive control dials for ease of use:

Customizable Water Pressure & Temperature

Highlight: Showcase the adjustable dials, emphasizing ease of use and the comfort of personalized settings.



Image 6.1: The control panel of the bidet, featuring three dials for selecting nozzle function, adjusting water pressure, and controlling water temperature.

- **Nozzle Selection Dial:** Rotate the top dial to select your desired cleaning mode:
 - **Rear Wash:** For general posterior cleaning.
 - **Feminine Wash:** For a gentler, wider spray suitable for feminine hygiene.
 - **Nozzle Cleaning:** Activates the self-cleaning function for the nozzles.
- **Water Pressure Control Dial:** The middle dial adjusts the intensity of the water spray. Turn towards 'HI' for stronger pressure and 'LOW' for gentler pressure.
- **Water Temperature Control Dial:** The bottom dial controls the water temperature. Turn towards the red indicator for warmer water and the blue indicator for cooler water.

7. MAINTENANCE

Regular maintenance ensures the longevity and hygiene of your bidet attachment:

- **Nozzle Self-Cleaning:** Regularly use the 'Nozzle Cleaning' setting on the control dial to rinse the nozzles with fresh water before or after use.
- **Exterior Cleaning:** Wipe the exterior of the bidet attachment with a soft, damp cloth and mild soap.

Avoid abrasive cleaners, brushes, or harsh chemicals that can scratch or damage the surface.

- **Deep Cleaning:** For a more thorough cleaning, you may gently pull down the nozzles (if accessible) and clean them with a soft brush and mild soap. Ensure they retract properly afterward.
- **Winterization (if applicable):** If the bidet is in an unheated area and temperatures may drop below freezing, disconnect the water supply and drain the bidet to prevent freezing and damage.



Image 7.1: An animated illustration depicting the self-cleaning mechanism of the bidet nozzles, showing water rinsing away impurities.

8. TROUBLESHOOTING

If you encounter issues, refer to the following common troubleshooting steps:

- **No Water Spray:**
 - Ensure the main water supply valve is fully open.
 - Check that the water pressure control dial is not set to 'LOW' or off.
 - Verify that the water supply lines are not kinked or blocked.
- **Water Leaks:**

- Turn off the water supply immediately.
- Check all connections for tightness. Hand-tighten any loose fittings.
- Ensure rubber washers are correctly seated in all connections. Apply faucet tape if necessary.

- **Insufficient Water Pressure:**

- Adjust the water pressure control dial to a higher setting.
- Confirm that your household water pressure is adequate.

- **Incorrect Water Temperature:**

- Adjust the water temperature control dial.
- Ensure both hot and cold water lines are properly connected and supplying water.

- **Nozzles Not Retracting:**

- Check for any obstructions around the nozzles.
- Ensure the bidet is clean and free of debris.

If problems persist after following these steps, please contact customer support.

9. SPECIFICATIONS

Attribute	Specification
Model Number	GZA-00048
Manufacturer	LIVINGbasics
Material	ABS
Color	White
Installation Method	Toilet Bidet Attachment
Mounting Hole Distance	Adjustable 140mm - 200mm (5.51" - 7.87")
Thickness	0.47in / 1.2cm (Ultra-slim design)
Country of Origin	China








Image 9.1: A side profile view of the bidet attachment, highlighting its ultra-slim thickness of 0.47 inches (1.2 cm) and overall length.

10. WARRANTY AND SUPPORT

LIVINGbasics products are manufactured to high-quality standards. For warranty information or technical support, please refer to the contact details provided with your purchase documentation or visit the official LIVINGbasics website. Please retain your proof of purchase for any warranty claims.

© 2024 LIVINGbasics. All rights reserved.

Related Documents - GZA-00048

<div><div>LIVING basics</div><div>Autocuiseur 6 pintes de bonne qualité</div><div></div><div>SKU: LB-PC-10061H2</div></div>	<p>LIVINGbasics 6-Quart Pressure Cooker User Manual</p> <p>Comprehensive user manual for the LIVINGbasics 6-Quart Pressure Cooker, covering safety instructions, operation, cooking functions, maintenance, troubleshooting, and warranty information.</p>
<div><div>LIVING basics</div><div>Autocuiseur 6 pintes de bonne qualité</div><div></div><div>SKU: LB-PC-10061H2</div></div>	<p>LIVINGbasics 6-Quart Pressure Cooker User Manual</p> <p>Comprehensive user manual for the LIVINGbasics 6-Quart Pressure Cooker, covering safety instructions, operation, cooking functions, maintenance, troubleshooting, and warranty information.</p>
<div><div><div>Specifications</div><div></div></div></div>	<p>Marsail L-Shaped Electric Standing Desk Assembly and Operation Guide</p> <p>Comprehensive guide for assembling and operating the Marsail L-Shaped Electric Standing Desk, including specifications, parts list, step-by-step instructions, controller functions, and error code explanations.</p>
<div><div>Laird</div><div>Datasheet</div><div>LWB5+ M.2</div></div>	<p>Laird LWB5+ M.2 Datasheet: 802.11ac WLAN & Bluetooth 5.0 Module</p> <p>Explore the technical specifications and features of the Laird LWB5+ M.2 module, a compact solution for 802.11ac Wi-Fi and Bluetooth 5.0 connectivity, designed for embedded applications.</p>
<div><div></div></div>	<p>PrimeCables Cab-GZA-00492 Musical Classic Double X Keyboard Stand Installation Guide</p> <p>Official installation instructions for the PrimeCables Cab-GZA-00492 Musical Classic Double X Keyboard Stand. This guide details assembly steps and parts for the double X keyboard stand.</p>
<div><div>RadWagon 4</div><div>OWNER'S MANUAL</div><div></div><div>RAD POWER BIKES</div></div>	<p>RadWagon 4 Owner's Manual - Rad Power Bikes</p> <p>Comprehensive owner's manual for the RadWagon 4 electric cargo bike from Rad Power Bikes. Learn about assembly, safety, operation, maintenance, and troubleshooting.</p>

