Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

WEN CT1274, CT9110, CT992F

WEN 12-Amp 7-1/4-Inch Variable Speed Plunge Cut Circular Track Saw

Model: CT1274, CT9110, CT992F

Brand: WEN

Product Overview

The WEN 12-Amp 7-1/4-Inch Variable Speed Plunge Cut Circular Track Saw is designed for precise and efficient cutting operations. This tool, combined with its track guide rail and clamps, allows for accurate straight and bevel cuts on various materials.



This image displays the WEN 12-Amp 7-1/4-Inch Variable Speed Plunge Cut Circular Track Saw, along with its accompanying 110-inch track saw track guide rail (composed of two 55-inch sections) and two clamps. The saw itself is dark gray with orange accents, featuring a dust port and ergonomic handles. The track sections are silver with orange strips, and the clamps are black and orange with squeeze grip triggers.

Setup

Before operating the WEN Plunge Cut Circular Track Saw, ensure all components are properly assembled and secured. This kit includes the track saw, two 55-inch track saw tracks, and an adapter set, along with two clamps.

Track Assembly

- Connect the two 55-inch track saw tracks using the provided adapter set.
- Ensure the adapter set is securely fastened with the four set screws for maximum stability.
- Place the assembled track guide rail on your workpiece, aligning it with your desired cut line.

Clamp Installation

- Utilize the two clamps to secure the track guide rail to your workpiece.
- The clamps feature a 2.5-inch throat and a 7.5-inch maximum opening, suitable for various material thicknesses.
- Use the quick release buttons for easy installation and removal of the clamps.
- Apply squeeze grip triggers to provide maximum security and support during operation.

Operating Instructions

The WEN Plunge Cut Circular Track Saw offers versatile cutting capabilities for various applications.

Cutting Operations

- **Plunge Cuts:** The saw can rip boards and create plunge cuts up to 2.6 inches thick.
- **Bevel Cuts:** Achieve 45-degree bevel cuts up to 1.85 inches thick.
- **Blade Compatibility:** This saw accepts standard 7-1/4-inch miter and circular saw blades with 5/8-inch arbors.
- **Variable Speed:** Adjust the blade speed anywhere from 2000 to 6000 RPM to match the material and cutting requirements.
- **Guided Cutting:** For precise, straight cuts, always use the saw with the 110-inch track saw track guide rail and clamps. This setup is ideal for ripping large sheets, such as 8-foot by 4-foot plywood.

Always ensure the workpiece is stable and secured before initiating a cut. Wear appropriate safety gear, including eye protection and hearing protection.

Maintenance

Regular maintenance ensures the longevity and optimal performance of your WEN Plunge Cut Circular Track Saw.

- **Cleaning:** After each use, disconnect the saw from the power source and clean off any sawdust or debris from the tool and track. Use a dry cloth or compressed air.
- **Blade Inspection:** Regularly inspect the saw blade for sharpness and damage. Replace dull or damaged blades promptly to ensure clean cuts and prevent strain on the motor.
- **Cord Inspection:** Check the power cord for any signs of damage, fraying, or cuts. Do not use the tool if the cord is damaged.
- **Storage:** Store the saw and its accessories in a clean, dry place, away from moisture and extreme temperatures.

Troubleshooting

This section addresses common issues you might encounter with your WEN Plunge Cut Circular Track Saw. For problems not listed here, please contact customer support.

- **Saw not starting:** Ensure the power cord is securely plugged into a functional outlet. Check for tripped circuit breakers.
- **Poor cut quality:** Inspect the blade for dullness or damage. Ensure the blade is installed correctly and the track is securely clamped to the workpiece.
- **Excessive vibration:** Check if the blade is properly tightened and not warped. Ensure all components of the saw and track system are securely assembled.

Specifications

Brand	WEN
Model Numbers	CT1274, CT9110, CT992F
Power Source	Corded Electric
Voltage	108 Volts (DC)
Blade Size	7-1/4-inch (with 5/8-inch arbor)
Blade Material	High Speed Steel
Variable Speed Range	2000 to 6000 RPM
Max Plunge Cut Depth	2.6 inches
Max Bevel Cut Depth (45°)	1.85 inches
Included Components	Track Saw Tracks (two 55-inch sections), Adapter Set, Clamps (two)
Color	Black
Handle Material	Plastic
Item Package Quantity	1
Date First Available	September 13, 2024

Warranty Information

The WEN 12-Amp 7-1/4-Inch Variable Speed Plunge Cut Circular Track Saw comes with a**limited warranty**. For specific details regarding the terms, conditions, and duration of your warranty, please refer to the documentation included with your product or visit the official WEN website.

Customer Support

For technical assistance, replacement parts, or any inquiries not covered in this manual, please contact WEN customer support. Have your product model number (CT1274, CT9110, CT992F) ready when contacting support.

You can typically find contact information on the official WEN website or within the product packaging.

© 2024 WEN. All rights reserved.
This manual is intended for informational purposes only. Specifications are subject to change without notice.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B0DGXWP4N5

More documents and user manuals: **https://manuals.plus/**