

RecPro RP-FPC-30

RecPro RV 30" Recessed Electric Fireplace

Model: RP-FPC-30

INTRODUCTION

This manual provides essential information for the safe and efficient operation of your RecPro RV 30" Recessed Electric Fireplace. Please read all instructions carefully before installation and use. Keep this manual for future reference.



Front view of the RecPro RV 30-inch Recessed Electric Fireplace, showcasing the realistic log and flame effects through the glass panel.

IMPORTANT SAFETY INFORMATION

WARNING: To reduce the risk of fire, electric shock, or injury, read all instructions before using this appliance.

- Ensure the fireplace is connected to a properly grounded outlet.
- Do not operate the fireplace with a damaged cord or plug.
- Keep combustible materials at least 3 feet (0.9 meters) away from the front of the fireplace.
- Do not insert or allow foreign objects to enter any ventilation or exhaust opening.
- This fireplace is equipped with **Zero Clearance Safety Technology**, including proximity and thermal cut-off sensors. These sensors automatically shut down the unit if safety is compromised due to overheating or obstruction.
- Always unplug the fireplace before cleaning or performing maintenance.

SETUP AND INSTALLATION

The RecPro RV Electric Fireplace is designed for **Recess Mounted** installation. Proper installation is crucial for safety and performance.

Dimensions and Cutout Requirements



Detailed diagram illustrating the product dimensions (8"D x 30"W x 21.75"H) and the required wall cutout size (26.25"W x 20.5"H with a minimum 6" depth).

- **Product Dimensions:** 8"D x 30"W x 21.75"H
- **Wall Cutout Size:** 26.25"W x 20.5"H
- **Minimum Cutout Depth:** 6 inches. Ensure sufficient depth from the wall surface to the back of the cutout.

Power Connection

This unit operates on 120 Volt electric power. Ensure the electrical supply meets the fireplace's requirements

(1500 Watts heat output) and is installed by a qualified electrician if necessary.



Rear view of the fireplace, displaying the power cord connection and product information label.

OPERATING INSTRUCTIONS

Your RecPro Electric Fireplace can be controlled using the included remote control or the intuitive LED touch panel on the unit.

Remote Control Functions



A hand operating the remote control, with buttons for power, temperature, flame effects, and timer visible.

- **Power Button:** Turns the fireplace ON/OFF.
- **Temperature Control:** Adjusts the heat output. The fireplace offers 8 heat settings, ranging from 68°F to 82°F.
- **Flame Color Modes:** Cycles through four distinct flame color options: Orange, Blue, Orange + Blue, and Cycle (automatically transitions through colors).
- **Brightness Control:** Adjusts the intensity of the flame effect.
- **Timer Function:** Sets an automatic shut-off timer.

LED Touch Panel

The LED touch panel on the fireplace unit provides access to the same functions as the remote control. Gently press the icons to adjust settings.



The fireplace showcasing different flame color modes, including blue, orange, and a combination of both.

MAINTENANCE

Regular maintenance ensures the longevity and optimal performance of your electric fireplace.

Cleaning

- Always unplug the unit before cleaning.
- The **curved tempered glass panel** is designed for easy cleaning. Use a soft, damp cloth to wipe the glass and exterior surfaces. Avoid abrasive cleaners or sprays directly on the unit.
- Periodically check the air intake and exhaust vents for dust or obstructions. Use a vacuum cleaner with a soft brush attachment to remove any buildup.

Storage

If storing the fireplace for an extended period, ensure it is clean and dry. Store in a cool, dry place, preferably in its original packaging to protect it from dust and damage.

TROUBLESHOOTING

If you experience issues with your electric fireplace, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Fireplace does not turn on.	No power supply; Power cord not plugged in; Circuit breaker tripped; Thermal cut-off activated.	Check power outlet; Ensure cord is securely plugged in; Reset circuit breaker; Allow unit to cool down and reset.
No heat output.	Heat function not activated; Temperature setting too low; Heater element malfunction.	Activate heat function via remote/panel; Increase temperature setting; Contact customer support if issue persists.
Flame effect not working.	Flame effect turned off; LED light malfunction.	Turn on flame effect via remote/panel; Contact customer support if issue persists.
Remote control not working.	Dead batteries; Obstruction between remote and unit.	Replace batteries; Ensure clear line of sight to the fireplace sensor.

If the problem persists after attempting these solutions, please contact RecPro customer support.

SPECIFICATIONS

Brand: RecPro

Model Name: RP-FPC-30

Power Source: Electric

Voltage: 120 Volt

Product Dimensions: 8"D x 30"W x 21.75"H

Material: Alloy Steel

Finish Type: Steel Construction with Black Finish

Installation Type: Recess Mounted

Heat Output: 1500 Watts

Special Features: LED Flame, Multicolor Flame, Thermal cut-off sensors, Timer

Style: Modern

Color: Black

Ventilation Type: Vent Free

Included Components: Remote Control

Specific Uses For Product: Indoor, Recreational Vehicle

Item Weight: 55 pounds





CUSTOMER SUPPORT

For any questions, technical assistance, or warranty inquiries regarding your RecPro RV 30" Recessed Electric Fireplace, please contact RecPro customer support.

Visit the official RecPro store for more information:[RecPro Store on Amazon](#)

© 2024 RecPro. All rights reserved.

Related Documents - RP-FPC-30

	<p>Progeny JB-70 Dental X-Ray System Installation and Service Manual</p> <p>Essential installation and service manual for the Progeny JB-70 Dental X-Ray System, detailing setup, safety, operation, and troubleshooting for dental radiography professionals.</p>
	<p>Taymor Flush Deadbolt: Features, Specifications, and Finishes</p> <p>Detailed specifications and features of the Taymor Flush Deadbolt, including installation details, available finishes, and ordering information.</p>
	<p>Mitutoyo AOS Absolute Digimatic Caliper CD-AX/APX Series: Precision Measuring Tool</p> <p>Discover the Mitutoyo AOS Absolute Digimatic Caliper CD-AX/APX Series, engineered with advanced AOS (Advanced Onsite Sensor) and electromagnetic induction absolute encoder technology for superior accuracy, durability, and coolant resistance. This brochure details key features, specifications, and the technological evolution of Mitutoyo's precision measuring instruments.</p>
	<p>SimpliFire Electric Fireplaces: Product Guide and Features</p> <p>Explore the comprehensive range of SimpliFire electric fireplaces, including models like Triton, Scion, Allusion Edge, Allusion Platinum, Allusion Slim, Format, Forum, and Inception. Discover features, customization options, media choices, installation guidance, and technical specifications for creating a warm and stylish home environment.</p>

OPW

iTouch™



[SiteSentinel iTouch Tank Monitoring System Installation Manual](#)

Comprehensive installation manual for the OPW SiteSentinel iTouch Tank Monitoring System, covering controller and probe/sensor installation, wiring, and setup.



[OPW M1500 SiteSentinel iTouch Tank-Gauge Monitoring System Installation Guide](#)

Installation guide for the OPW M1500 SiteSentinel iTouch Tank-Gauge Monitoring System, covering controller, probes, and sensor installation procedures.