

[Manuals.plus](#) /

› [SEALIGHT](#) /

› SEALIGHT SUV Tent for Camping: Model 8216WDE113CUS Instruction Manual

SEALIGHT 8216WDE113CUS

SEALIGHT SUV Tent for Camping: Model 8216WDE113CUS Instruction Manual

[Introduction](#) [Setup](#) [Operation](#) [Maintenance](#) [Troubleshooting](#) [Specifications](#) [Warranty](#) [Support](#)

1. INTRODUCTION

This manual provides detailed instructions for the proper setup, operation, maintenance, and troubleshooting of your SEALIGHT SUV Tent, Model 8216WDE113CUS. Please read this manual thoroughly before using the tent to ensure safe and efficient use. This tent is designed for car camping and offers versatility for various outdoor adventures.



Image 1.1: The SEALIGHT SUV Tent in use, demonstrating its integration with a vehicle for family camping.

2. SETUP INSTRUCTIONS

2.1 Unpacking and Components

Carefully unpack the tent and all its components. Ensure all parts are present before beginning setup.



Image 2.1: Included components: Tent, Rainfly, Tent Bag, Stake Bag, Connectors, 2 Suction Cups, 8 Stakes, 4 Guy Lines, 4 Clasps.

2.2 Quick Release Bracket System

The tent features an automatic quick-release bracket system for rapid deployment. This system allows for setup by one person in approximately 3 to 5 minutes.



Image 2.2: Detail of the quick release bracket for fast installation.

2.3 Step-by-Step Installation

Follow these steps for quick and efficient tent setup:



Image 2.3: Visual guide for quick installation.

1. **Step 1: Unfold the Tent.** Lay the tent flat on the ground at your desired camping spot.
2. **Step 2: Assemble Poles.** Extend the tent poles and connect them at the central hub. The quick-release bracket will assist in this process.
3. **Step 3: Raise the Tent.** Lift the tent structure, allowing the poles to lock into place.
4. **Step 4: Position for Vehicle Attachment.** Move the tent towards the rear of your SUV or compatible vehicle.
5. **Step 5: Secure with Suction Cups.** Use the provided suction cups to attach the tent fabric to the vehicle's body, such as the rear window.
6. **Step 6: Attach to Vehicle Wheels/Doors.** Utilize straps to secure the tent to the vehicle's wheels or door handles for stability.
7. **Step 7: Stake Down.** Use the stakes and guy lines to firmly anchor the tent to the ground, especially in windy conditions.
8. **Step 8: Final Adjustments.** Ensure all connections are secure and the tent is taut.

Your browser does not support the video tag.

Video 2.1: Overview of the SEALIGHT SUV Tent, showcasing its features and general setup process. This video is provided by the seller.

3. OPERATING YOUR TENT

3.1 Vehicle Attachment and Standalone Use

The SEALIGHT SUV Tent is designed for dual functionality. It can be securely attached to the rear of compatible hatchback vehicles (MPVs, SUVs, Model Ys, vans, Jeep Wranglers, and pickup trucks with bed covers) or used as a standalone tent by detaching it from the vehicle.



Image 3.1: Examples of vehicle attachment points: tire strap and suction cup.

3.2 Ventilation and Views

The tent features three mesh windows and a skylight to ensure optimal airflow and minimize condensation. These openings also provide expansive views of your surroundings.



Image 3.2: Interior view highlighting ventilation and clear views.

3.3 Weather Resistance

Constructed from high-grade PU 3000mm and 210D Oxford fabric, the tent offers excellent weather resistance and waterproof capabilities, suitable for all four seasons. Factory-sealed seams enhance rain protection.



Image 3.3: Waterproofing technology detail, showing PU3000mm coating and 210D Oxford cloth.

4. CARE AND MAINTENANCE

4.1 Cleaning Your Tent

- **Spot Cleaning:** For small dirt spots, use a soft brush or sponge with mild soap and lukewarm water. Gently scrub the affected area.
- **Thorough Cleaning:** For a more extensive clean, set up the tent and hose it down with water. Use a soft brush and mild, non-detergent soap (specifically designed for outdoor gear if possible) to clean the fabric. Avoid harsh chemicals or bleach, as these can damage the waterproof coating and fabric.
- **Rinsing:** Rinse the tent thoroughly to remove all soap residue.
- **Drying:** It is crucial to dry the tent completely before packing it away. Hang it in a shaded, well-ventilated area. Packing a damp tent can lead to mildew and fabric degradation.

Note: The product specifications mention "Dry Clean Only." This is generally not applicable to outdoor tents. Please follow the cleaning instructions above to maintain the tent's integrity and waterproofing.

4.2 Storage

Store your tent in a cool, dry place, away from direct sunlight and extreme temperatures. Ensure it is completely dry before storage to prevent mildew and odors. Keep it in its original storage bag to protect it from dust and damage.

5. TROUBLESHOOTING COMMON ISSUES

5.1 Leaking

- **Check Seams:** Inspect all seams for any signs of damage or inadequate sealing. While the tent features factory-sealed seams, extreme weather or wear can compromise them. Seam sealer products can be applied to reinforce.
- **Proper Pitch:** Ensure the tent is pitched correctly and tautly, allowing water to run off the rainfly without pooling.
- **Rainfly Position:** Verify that the rainfly is correctly positioned and fully covers the tent, extending beyond the main body to direct water away.

5.2 Zipper Malfunctions

- **Stuck Zipper:** If a zipper is stuck, gently try to move it back and forth. Avoid forcing it, as this can cause further damage. Check for fabric caught in the zipper teeth.
- **Separating Teeth:** If zipper teeth are separating, try to re-align them by moving the slider to the beginning of the track and slowly zipping it up again.
- **Lubrication:** Apply a zipper lubricant or a small amount of graphite (from a pencil) to the zipper teeth to improve smooth operation.
- **Careful Handling:** Always operate zippers carefully and avoid pulling them at sharp angles or with excessive force.

6. PRODUCT SPECIFICATIONS

Feature	Detail
Brand	SEALIGHT
Model Number	8216WDE113CUS
Product Dimensions (L x W x H)	96.5" x 86.6" x 120.1" (245cm x 220cm x 305cm)
Item Weight	9.8 kg (21.6 lbs)
Occupancy	6 Person
Seasons	4 Season
Material Type	210D Oxford Fabric
Water Resistance Technology	PU 3000mm Coating
UV Protection	Yes
Installation Type	Attached to Vehicle Back / Standalone
Number Of Windows	3 (Mesh)
Number Of Pockets	3
Form Factor	Pop-up
Compatible Vehicle Type	SUVs and similar vehicles (CUVs, MPVs, Vans, Jeep Wranglers, Pickup Trucks with bed covers)

7. WARRANTY INFORMATION

The SEALIGHT SUV Tent, Model 8216WDE113CUS, comes with a **1-Year Limited Warranty** from the date of purchase. This warranty covers manufacturing defects in materials and workmanship under normal use. It does not cover damage caused by misuse, improper setup, accidents, modifications, or normal wear and tear. Please retain your proof of purchase for warranty claims.

8. CUSTOMER SUPPORT

If you have any questions, require assistance with setup, or encounter any issues not covered in this manual, please contact SEALIGHT customer support. For the most up-to-date contact information, please refer to the product packaging or the

official SEALIGHT website.

When contacting support, please have your product model number (8216WDE113CUS) and proof of purchase readily available.

© 2026 SEALIGHT. All rights reserved.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

<https://manuals.plus/asin/B0DLB5XB8H>

More documents and user manuals: <https://manuals.plus/>