NTSUMI DB7651 Carburetor Kit

NTSUMI DB7651 Carburetor Kit Instruction Manual for Powersmart Snowblowers

Model: DB7651 Carburetor Kit

1. Product Overview

This manual provides essential information for the installation, operation, and maintenance of your NTSUMI DB7651 Carburetor Kit. This kit is designed to ensure optimal performance and longevity for compatible snowblowers.

1.1. Kit Components

The NTSUMI DB7651 Carburetor Kit includes the following items:

- 1 x Carburetor
- 1 x Fuel Filter
- 1 x Spark Plug
- 1 x Primer Bulb
- 1 x Insulator
- 1 x Fuel Hose
- 1 x Shut Off Valve
- 3 x Gaskets
- 2 x Fitted Clamps



Figure 1: All components included in the NTSUMI DB7651 Carburetor Kit.

1.2. Compatible Models

This carburetor kit is compatible with the following Powersmart snow thrower models:

- Powersmart DB7659
- Powersmart DB7651
- Powersmart DB7659-22
- Powersmart DB7651-24

- Powersmart DB7651-26

It is designed to replace part number PC210101. Please verify your snowblower's model and existing carburetor specifications before installation. The fuel nozzle outside diameter is 0.33 inches (8.4mm), and the center-to-center mounting hole distance is 1.6 inches (40mm).



Figure 2: Carburetor dimensions and examples of compatible snowblower models.




Figure 3: Comparison of carburetor types (Replace 142534 with red plastic choke, Replace 210101 with metal vertical choke). Ensure you select the correct version for your snowblower.

2. Key Features

- **Smooth Operation:** Designed for easy starting and consistent engine performance in various temperatures.
- **Stable Power Output:** Helps maintain a stable fuel and air mixture ratio, ensuring reliable power delivery.
- **Fuel Efficiency:** Optimized to reduce fuel consumption while providing strong engine power.
- **Durable Construction:** Manufactured from high-quality aluminum alloy for strength and longevity.



Figure 4: The carburetor is constructed from high-quality aluminum alloy for superior durability.




Figure 5: The NTSUMI carburetor ensures stable fuel-air mixture for consistent and steady power output.

3. Setup and Installation

Proper installation of the carburetor kit is crucial for optimal performance and safety. If you are unsure about any step, it is recommended to consult a qualified technician.

1. **Safety First:** Before beginning any work, ensure the snowblower engine is off and cool. Disconnect the spark plug wire to prevent accidental starting.
2. **Drain Fuel:** Drain any remaining fuel from the fuel tank and carburetor bowl into an approved container.

3. **Remove Old Carburetor:** Carefully disconnect the fuel lines, throttle linkage, and choke linkage from the old carburetor. Remove the mounting bolts and detach the old carburetor. Note the orientation of all components for reassembly.
4. **Install New Gaskets:** Place the new gaskets in their correct positions between the engine, insulator, and the new carburetor. Ensure they are properly aligned to prevent air leaks.
5. **Install New Carburetor:** Mount the new carburetor, securing it with the mounting bolts. Reconnect the throttle and choke linkages.
6. **Connect Fuel Lines:** Install the new fuel hose, fuel filter, and shut-off valve as needed. Ensure all connections are secure and free of leaks.
7. **Install Spark Plug and Primer Bulb:** Replace the old spark plug with the new one provided. Install the new primer bulb.
8. **Refill Fuel:** Refill the fuel tank with fresh, appropriate fuel for your snowblower.
9. **Test Run:** Reconnect the spark plug wire. Follow your snowblower's starting procedure. Check for any fuel leaks or unusual engine behavior.

Your browser does not support the video tag.

Video 1: An overview of the carburetor kit components and a demonstration of its features, providing visual guidance for installation and function.

4. Operating Instructions

Once the carburetor kit is installed, operate your snowblower according to the manufacturer's instructions. The new carburetor is designed to provide improved starting and consistent engine performance.

- **Starting:** Ensure the fuel shut-off valve is open. Prime the engine as per your snowblower's manual. Set the choke and throttle appropriately for cold or warm starts.
- **Performance:** The carburetor will regulate the fuel-air mixture to maintain steady power output during operation.
- **Shut Down:** Always turn off the engine and close the fuel shut-off valve after use, especially for storage.



Figure 6: The NTSUMI carburetor kit helps ensure strong power output for efficient snow removal.



Figure 7: The NTSUMI carburetor promotes smooth and reliable operation in various conditions.

5. Maintenance

Regular maintenance of your carburetor and related components will extend the life of your snowblower and ensure consistent performance.

- **Fuel Filter:** Inspect the fuel filter periodically and replace it if it appears dirty or clogged. A clean fuel filter prevents contaminants from reaching the carburetor.
- **Spark Plug:** Check the spark plug for wear and proper gap. Replace it annually or as recommended by your snowblower's manufacturer.

- **Fuel Quality:** Always use fresh, clean fuel. Stale or contaminated fuel can cause carburetor issues. Consider using a fuel stabilizer during off-season storage.
- **Carburetor Cleaning:** If the engine experiences rough idling, difficulty starting, or loss of power, the carburetor may need cleaning. This often involves disassembling the carburetor and cleaning jets and passages with carburetor cleaner.
- **Gaskets:** Ensure all gaskets are in good condition and properly sealed to prevent air or fuel leaks.

6. Troubleshooting

Here are some common issues and potential solutions:

Problem	Possible Cause	Solution
Engine won't start	No fuel, clogged fuel filter, faulty spark plug, clogged carburetor jet.	Check fuel level, replace fuel filter, replace spark plug, clean carburetor.
Engine runs rough or stalls	Dirty carburetor, improper fuel-air mixture, old fuel.	Clean carburetor, adjust carburetor (if adjustable), use fresh fuel.
Loss of power	Clogged fuel filter, dirty carburetor, worn spark plug.	Replace fuel filter, clean carburetor, replace spark plug.
Fuel leaks	Loose fuel line connections, damaged gaskets, cracked fuel hose.	Tighten connections, replace gaskets, replace fuel hose.

If troubleshooting steps do not resolve the issue, contact a qualified service technician.

7. Specifications

- **Material:** High-quality Aluminum Alloy
- **Fuel Nozzle Outside Diameter:** 0.33 inches (8.4mm)
- **Center-to-Center Mounting Hole Distance:** 1.6 inches (40mm)
- **Weight:** Approximately 1.13 pounds
- **Package Dimensions:** 9 x 3.5 x 2.5 inches
- **Replaces Part Number:** PC210101

8. Warranty and Support

For warranty information or technical support, please refer to the documentation provided with your original snowblower or contact NTSUMI customer service directly. Keep your purchase receipt as proof of purchase. NTSUMI is committed to providing high-quality replacement parts and customer satisfaction. For further assistance, please visit the official NTSUMI website or contact their support channels.

© 2025 NTSUMI. All rights reserved.