

TEMOLA TN09

TEMOLA TN09 Portable Tire Inflator User Manual

Model: TN09

[Overview](#) [Setup](#) [Introduction](#) [Safety Information](#) [Product](#)
[Operation](#) [Maintenance](#) [Troubleshooting](#) [Specifications](#) [Warranty & Support](#)

1. INTRODUCTION

Thank you for choosing the TEMOLA TN09 Portable Tire Inflator. This device is designed for convenient and efficient inflation of various items, including car tires, motorcycle tires, bicycle tires, and sports balls. It features a digital pressure gauge, auto-off function, LED lighting, and multiple power supply options for versatile use.

2. SAFETY INFORMATION

- Read all instructions carefully before use.
- Keep out of reach of children.
- Do not operate the inflator in wet conditions or near flammable liquids or gases.
- Ensure the correct pressure setting for the item being inflated to prevent over-inflation, which can cause damage or injury.
- Do not leave the inflator unattended during operation.
- Allow the device to cool down after prolonged use to prevent overheating.
- Use only the provided accessories and charging cables.
- The emergency escape hammer is for emergency use only. Handle with care.

3. PRODUCT OVERVIEW

3.1 Package Contents

The TEMOLA TN09 Portable Tire Inflator package includes the following items:

1. 1 x TEMOLA TN09 Tire Inflator
2. 1 x Air Tube (Inflation Hose)
3. 2 x Air Nozzle Cones
4. 1 x Needle Valve Adapter
5. 1 x Presta to Schrader Adapter
6. 1 x Safety Hammer (integrated or separate, depending on model variant)
7. 1 x User Manual
8. 1 x Type-C Charging Cable
9. 1 x Storage Bag
10. 1 x 12V Car Power Supply Cable

PACKING INCLUDES

- | | |
|-------------------------------|--------------------------------|
| 1. AIR INFLATOR | 6. SAFETY HAMMER |
| 2. AIR TUBE | 7. USER MANUAL |
| 3. AIR NOZZLE CONES | 8. TYPE-C CHARGING CABLE |
| 4. NEEDLE VALVE | 9. STORAGE BAG |
| 5. PRESTA TO SCHRADER ADAPTER | 10. 12V CAR POWER SUPPLY CABLE |



Image: All items included in the TEMOLA TN09 package, laid out neatly. This includes the inflator unit, various nozzle

adapters, charging cables, and a storage bag.



Image: A visual representation of the TEMOLA TN09 inflator and its accessories, including the air tube, various adapters, charging cables, and storage bag.

3.2 Device Components

- **Digital Display:** Shows real-time pressure, preset pressure, battery level, and selected mode.
- **Control Buttons:** Power on/off, mode selection, increase/decrease pressure, start/stop inflation, SOS light.
- **Air Outlet:** Connection point for the inflation hose.
- **LED Light:** Provides illumination for night use, strobe, and SOS signals.
- **TYPE-C Charging Port:** For charging the internal battery.
- **USB Discharge Port:** Can be used as a power bank to charge other devices.
- **12V DC Power Port:** For external power supply from a car cigarette lighter.
- **Emergency Escape Hammer:** Located at one end of the device for emergency situations.



Image: Front view of the TEMOLA TN09 inflator, highlighting the digital display and control buttons.



Image: The TEMOLA TN09 inflator connected to a car tire, showing the digital display with real-time and preset pressure values. An indicator shows inflation completes in less than 1 minute for 29-36 PSI.

MULTIFUNCTION INFLATOR

It has versatility



Image: The TEMOLA TN09 inflator connected via USB-C cable to a smartphone, demonstrating its power bank functionality.

4. SETUP

4.1 Initial Charging

Before first use, fully charge the inflator using the provided Type-C charging cable and a suitable USB power adapter (not included). The battery indicator on the digital display will show charging status.

4.2 Attaching the Air Tube and Adapters

1. Screw one end of the air tube securely into the air outlet on the top of the inflator.
2. Select the appropriate nozzle adapter for the item you wish to inflate (e.g., Presta to Schrader

adapter for bicycles, needle valve for balls, cone nozzles for swimming rings).

3. Screw the selected adapter onto the other end of the air tube.

EASY TO INFLATOR

A wide range of accessories to choose from

For Car



For Motorcycles



For Swimming Ring



For Bikes



For Balls



Image: Various inflation adapters included with the TEMOLA TN09, suitable for cars, motorcycles, swimming rings, bikes, and balls.

4.3 Power Supply Options

The inflator can be powered in two ways:

- **Cordless (Internal Battery):** For maximum portability. Ensure the battery is charged.
- **Corded (12V DC Car Power):** Connect the provided 12V car power supply cable to the inflator's 12V DC port and your car's cigarette lighter socket. This allows for continuous operation without relying on the internal battery.



Image: Comparison showing the TEMOLA TN09 operating in cordless mode (battery supply) and corded mode (12V DC supply from a car).

5. OPERATING INSTRUCTIONS

5.1 Basic Inflation Steps

1. **Connect Air Hose:** Connect the air hose to the item you wish to inflate.
2. **Power On:** Long press the power button to turn on the inflator. The digital display will activate.
3. **Select Mode:** Short press the mode button to cycle through the 4 preset inflation modes: car, motorbike, bike, and ball. Each mode has a default pressure value.
4. **Set Pressure Unit:** Long press the mode button to switch between pressure units (PSI, KPA, BAR, KG/CM²).
5. **Adjust Target Pressure:** Use the '+' and '-' buttons to increase or decrease the target pressure value.
6. **Start Inflation:** Short press the power button to begin inflation. The inflator will automatically stop once the preset pressure is reached.
7. **Stop Inflation (Manual):** To stop inflation manually, short press the power button again.



Image: A four-step visual guide demonstrating how to use the TEMOLA TN09: 1. Connect air hose to tire. 2. Long press to activate power. 3. Press to choose mode. 4. Press to start inflation.

5.2 LED Light Functions

The built-in LED light offers multiple functions for visibility and emergencies:

- **White Light:** For general illumination in dark environments.
- **Red Strobe Light:** For warning alerts.
- **Red & White SOS Flashing:** For emergency signaling.



Image: The TEMOLA TN09 inflator in a dark setting, demonstrating its LED light functions including standard lighting, strobe, and SOS modes.

5.3 Emergency Escape Hammer

The inflator is equipped with an emergency escape hammer for critical situations. In an emergency, use the pointed end to break vehicle windows. Always aim for the corner of the window for best results.

EMERGENCY ESCAPE HAMMER

Guard your safety in travel



Image: A hand using the emergency escape hammer feature of the TEMOLA TN09 to break a car window, illustrating its use in an emergency.



Image: The TEMOLA TN09's emergency escape hammer shown breaking glass, with additional images depicting scenarios like fire hazards, hydrops, and falling into water, where the hammer could be useful.

5.4 Video Demonstration

Your browser does not support the video tag.

Video: A demonstration of the TEMOLA TN09 Portable Tire Inflator, showcasing its unboxing, features, operation, and various inflation applications for balls, swimming rings, and tires.

6. MAINTENANCE

- **Charging:** Recharge the inflator when the battery indicator is low to ensure it's ready for use.
- **Cleaning:** Wipe the device with a soft, dry cloth. Do not use harsh chemicals or abrasive cleaners.
- **Storage:** Store the inflator and its accessories in the provided storage bag in a cool, dry place, away from direct sunlight and extreme temperatures.
- **Hose Care:** Ensure the air hose is not kinked or damaged during storage.

7. TROUBLESHOOTING

Problem	Possible Cause	Solution
Inflator does not turn on.	Low battery or no power.	Charge the inflator using the Type-C cable or connect to a 12V DC car power source.
Inflation is slow or not working.	Incorrect adapter, loose connection, or hose leak.	Ensure the correct adapter is used and all connections are tight. Check the hose for damage.
Inflator stops before reaching target pressure.	Auto-off function activated due to overheating or low battery.	Allow the device to cool down. Recharge the battery if low.
Inaccurate pressure reading.	Sensor issue or external factors.	Ensure the connection is secure. If the problem persists, contact customer support.

8. SPECIFICATIONS

- **Model Number:** TN09

- **Maximum Pressure:** 150 PSI
- **Voltage:** 7.4 Volts
- **Wattage:** 65 Watts
- **Power Source:** Battery Powered (Lithium Ion) / 12V DC
- **Product Dimensions:** 14 x 7.5 x 20.5 cm
- **Item Weight:** 650 g
- **Material:** Plastic
- **Special Features:** Cordless, Digital Display, LED Light, Emergency Escape Hammer

9. WARRANTY & SUPPORT

TEMOLA products come with a standard manufacturer's warranty. For specific warranty details, product support, or service inquiries, please refer to the warranty card included in your package or visit the official TEMOLA website. Please retain your proof of purchase for warranty claims.