

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [OVE Decors](#) /

› [OVE Decors Bel Frameless Sliding Shower Door User Manual](#)

OVE Decors Bel

OVE Decors Bel Frameless Sliding Shower Door

Model: Bel 58-in to 60-in W x 78.75-in H

IMPORTANT SAFETY INFORMATION

Please read this entire manual carefully before installation and use. Failure to follow these instructions could result in injury or product damage. Keep these instructions for future reference.

- **Glass Handling:** Tempered glass is strong but can shatter if struck at the edges. Always handle glass panels with care and wear appropriate safety gloves and eye protection.
- **Installation:** Installation should be performed by two or more people due to the weight and size of the glass panels. Ensure the wall structure can support the weight of the shower door.
- **Sealing:** Proper sealing is crucial to prevent water leakage. Use a high-quality silicone sealant as directed.
- **Children and Pets:** Keep children and pets away from the installation area.
- **Tools:** Use only the recommended tools and ensure they are in good working condition.

PACKAGE CONTENTS

Verify that all components are present and undamaged before beginning installation. If any parts are missing or damaged, do not proceed with installation and contact customer support.

- Fixed Glass Panel (1)
- Sliding Glass Panel (1)
- Top Track Assembly (1)
- Bottom Guide Rail (1)
- Wall Profiles (2)
- Roller Assemblies (4)

- Soft-Close Mechanisms (2)
- Vertical Bar Handles (2)
- Water Seals/Gaskets (various)
- Hardware Kit (screws, anchors, washers, etc.)
- Arroyo Shower Wall Panels (4)
- Shower Wall Edge Protection Aluminum Profile (1)
- Shower Wall Corner Connection Profile (1)

Image: All components of the OVE Decors Bel shower door and Arroyo shower wall system.

TOOLS REQUIRED

The following tools are recommended for a successful installation:

- Measuring Tape
- Pencil
- Level
- Drill with appropriate drill bits (for tile/masonry and wood studs)
- Screwdriver (Phillips and Flathead)
- Caulking Gun
- Silicone Sealant (mildew-resistant, clear)
- Utility Knife
- Safety Glasses
- Work Gloves

SETUP AND INSTALLATION

Professional installation is highly recommended for this product. Ensure the shower base or tub is level and properly installed before beginning. This section provides a general overview; refer to the detailed installation guide included with your product for specific step-by-step instructions.

Pre-Installation Steps:

1. **Inspect:** Unpack all components and inspect for any damage or missing parts.
2. **Measure:** Carefully measure the width and height of your shower opening to ensure it falls within the specified range (58-in to 60-in W x 78.75-in H).
3. **Prepare Surface:** Ensure shower walls and base are clean, dry, and level.

Arroyo Shower Wall Installation:

Install the Arroyo shower wall panels according to their specific instructions before installing the shower door. These panels are 5mm thick and include edge protection and corner connection profiles for a seamless finish.

Shower Door Installation Steps:

- 1. Install Wall Profiles:** Secure the vertical wall profiles to the finished shower walls using appropriate fasteners and anchors. Use a level to ensure they are perfectly plumb.
- 2. Install Top Track:** Attach the top track assembly to the wall profiles, ensuring it is level and securely fastened.
- 3. Install Fixed Glass Panel:** Carefully place the fixed glass panel into its designated wall profile and secure it. Ensure proper alignment and use shims if necessary.
- 4. Install Rollers and Soft-Close:** Attach the roller assemblies and soft-close mechanisms to the sliding glass panel according to the detailed diagram.
- 5. Hang Sliding Glass Panel:** With assistance, carefully lift and hang the sliding glass panel onto the top track rollers.
- 6. Install Bottom Guide Rail:** Position and secure the bottom guide rail to the shower base, ensuring the sliding panel moves smoothly within it.
- 7. Install Handles:** Attach the oversized 23-5/8-in vertical bar handles to the sliding glass panel.
- 8. Install Water Seals:** Apply all necessary water seals and gaskets to the edges of the glass panels and profiles to ensure a watertight enclosure.
- 9. Adjust and Test:** Adjust the rollers for smooth operation and ensure the soft-close feature functions correctly. Test for any leaks by running water. Apply silicone sealant to all exterior joints where water could escape.

Image: General installation diagram for the OVE Decors Bel shower door.

OPERATING INSTRUCTIONS

The OVE Decors Bel shower door features a smooth-gliding, soft-close mechanism for effortless operation.

- Opening/Closing:** Gently push or pull the vertical bar handle on the sliding glass panel to open or close the door.
- Soft-Close Feature:** As the door approaches its fully open or closed position, the integrated soft-close mechanism will engage, slowing the door's movement for a quiet and controlled stop. Avoid forcing the door against the soft-close mechanism.
- Smooth Movement:** The premium engineered rolling mechanism ensures an easy gliding experience. If the door feels stiff, refer to the Troubleshooting section.

Image: Detail of the soft-close mechanism.

MAINTENANCE

Regular cleaning and maintenance will ensure the longevity and optimal performance of your shower door.

Cleaning the Glass:

- Use a soft cloth or sponge with a non-abrasive glass cleaner or a solution of mild soap and water.
- Avoid abrasive cleaners, scouring pads, or harsh chemicals, as these can scratch the glass or damage protective coatings.

- For best results, wipe down the glass after each use to prevent water spot buildup. A squeegee can also be used.

Cleaning the Metal Components (Oil-Rubbed Bronze):

- Wipe down the oil-rubbed bronze finish with a soft, damp cloth.
- For stubborn spots, use a mild, non-abrasive cleaner specifically designed for metal finishes.
- **Do NOT** use abrasive cleaners, ammonia-based cleaners, or harsh chemicals, as these can damage the finish.
- Dry thoroughly with a soft cloth to prevent water spots.

Maintaining Rollers and Seals:

- Periodically inspect the rollers and bottom guide for any debris or buildup. Clean with a soft brush or cloth.
- Check the water seals and gaskets for wear or damage. Replace them if they appear cracked or are no longer providing an effective seal.
- Ensure the soft-close mechanism remains free of obstructions.

Image: Recommended cleaning practices for the shower door.

TROUBLESHOOTING

If you encounter any issues with your OVE Decors Bel shower door, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Door does not slide smoothly.	Debris in bottom guide rail; rollers are dirty or misaligned; track obstruction.	Clean the bottom guide rail and rollers. Inspect the top track for obstructions. Adjust roller alignment if necessary (refer to installation guide).
Water leaks from the shower enclosure.	Improperly installed water seals; insufficient silicone sealant; damaged seals.	Check all water seals for proper placement and condition. Reapply silicone sealant to all exterior joints. Replace damaged seals. Ensure the shower base is level.
Soft-close feature not engaging or working correctly.	Obstruction in the soft-close mechanism; mechanism misaligned or damaged.	Inspect the soft-close mechanism for any debris. Ensure the rollers are properly aligned with the mechanism. If damaged, contact customer support for replacement parts.
Door is difficult to open or close.	Rollers are dirty or worn; track is not level; door is binding.	Clean and lubricate rollers. Verify the top track and bottom guide rail are level. Check for any binding points and adjust the door's position if possible.

If the problem persists after attempting these solutions, please contact OVE Decors customer support.

SPECIFICATIONS

- **Model:** Bel
- **Dimensions:** 58-in to 60-in W x 78.75-in H (Adjustable Width)
- **Glass Type:** 8 mm (5/16-in) thick clear tempered glass
- **Door Style:** Frameless, Sliding (Barn door style)
- **Finish:** Oil-Rubbed Bronze
- **Features:** Soft-Close Technology, Watertight Seals, Oversized Vertical Bar Handles (23-5/8-in long)
- **Shower Wall:** Arroyo Shower Wall (4 panels, 5 mm thick, SPC Carrera marble finish)
- **Material:** Glass, Metal (Oil-Rubbed Bronze), SPC
- **Assembly Required:** Yes (Professional installation recommended)

WARRANTY AND SUPPORT

OVE Decors products are manufactured to high-quality standards and are backed by a manufacturer's warranty. Please refer to the warranty card included with your product for specific terms and conditions, including coverage duration and limitations.

For technical assistance, missing parts, or warranty claims, please contact OVE Decors customer support. Have your model number and purchase date ready when contacting support.

Contact Information:

Please visit the official OVE Decors website or refer to your product packaging for the most current customer support contact details.