



Manuals.plus /

- › Graco /
- › Graco EasyTurn 360 2-in-1 Convertible Car Seat Instruction Manual

## Graco EasyTurn 360 2-in-1

# Graco EasyTurn 360 2-in-1 Convertible Car Seat Instruction Manual

Model: EasyTurn 360 2-in-1

## 1. PRODUCT OVERVIEW

---

The Graco EasyTurn 360 2-in-1 Convertible Car Seat is designed for safety and convenience, accommodating children from infancy through toddlerhood. It features a unique 360-degree rotation for easy access, two modes of use (rear-facing and forward-facing), and Graco's SnugLock technology for secure installation.



Figure 1: Graco EasyTurn 360 2-in-1 Convertible Car Seat.

## Key Features:

- **360-Degree Rotation:** Allows for easy loading and unloading of your child in both rear-facing and forward-facing modes.
- **2 Modes of Use:** Supports rear-facing harness for children 4-40 lb and forward-facing harness for children 26.5-65 lb.
- **SnugLock Technology:** Provides quick and secure installation using either the vehicle seat belt or LATCH system.
- **No-Rethread Simply Safe Adjust Harness System:** Adjusts the 10-position headrest and harness simultaneously for a proper fit.
- **4-Position Recline:** Ensures comfort for your child and aids in correct installation.
- **Slim Design:** Optimizes backseat space without compromising safety or comfort.
- **Graco ProtectPlus Engineered:** Tested to meet or exceed US safety standards for frontal, side, rear, and rollover impacts.
- **Integrated Cup Holders:** Two easy-to-clean cup holders for drinks and snacks.
- **Plush Infant Inserts:** Removable head and body supports for infant comfort.

- **Fuss-Free Harness Storage:** Pockets to keep the harness out of the way for easy access.

## 2. SETUP AND INSTALLATION

---

Proper installation is crucial for your child's safety. Always refer to your vehicle's owner's manual and the car seat manual for complete instructions.

### 2.1 Preparing the Car Seat

- For forward-facing use, remove the plush infant head and body supports. These are for rear-facing use only.
- Ensure the car seat is rotated to the rear-facing position before beginning installation. Slide and hold the blue trigger, then pull out the gray lever and rotate the seat until the turn-lock indicator is green.
- Store the lower anchor connectors in the designated compartment in the seat base if using the vehicle seat belt for installation.
- Unhook the tether strap from its storage and lay it over the anti-rebound panel. It will be attached later.

### 2.2 Rear-Facing Installation (4-40 lb)

Place the car seat rear-facing in your vehicle. Ensure the base is flat on the vehicle seat, with at least 80% of the base on the seat.

- Adjust the recline to one of the rear-facing positions (1-4) using the recline handle on the front of the base. The level indicator on the side of the base should be within the blue zone.
- Open the SnugLock lock-off by pulling the gray lever.
- Route the vehicle lap and shoulder belt through the designated belt path, ensuring it is flat and untwisted. Buckle the seat belt.
- Remove slack from the vehicle seat belt by pulling on the shoulder belt while feeding the slack back into the retractor.
- Close the SnugLock lock-off firmly until you hear a click.
- Test for tightness: The car seat should not move more than 1 inch side-to-side or front-to-back at the belt path.

### 2.3 Forward-Facing Installation (26.5-65 lb)

Place the car seat forward-facing in your vehicle. Ensure the base is flat on the vehicle seat, with at least 80% of the base on the seat.

- Adjust the recline to one of the forward-facing positions (1-4) using the recline handle on the front of the base. The level indicator on the side of the base should be within the red zone.
- Open the SnugLock lock-off by pulling the gray lever.
- Route the vehicle lap and shoulder belt through the designated belt path, ensuring it is flat and untwisted. Buckle the seat belt.
- Remove slack from the vehicle seat belt by pulling on the shoulder belt while feeding the slack back into the retractor.
- Close the SnugLock lock-off firmly until you hear a click.
- Attach the tether strap to the vehicle's top tether anchor and tighten to remove all slack.
- Test for tightness: The car seat should not move more than 1 inch side-to-side or front-to-back at the belt path.

*Video 1: Graco EasyTurn 360 - Forward Facing Seat Belt Installation. This video demonstrates the steps for installing the car seat in a forward-facing position using the vehicle's seat belt.*

## 3. OPERATING THE CAR SEAT

---

### 3.1 360-Degree Rotation

The EasyTurn 360 allows you to rotate the car seat for effortless loading and unloading of your child.

- To rotate, slide and hold the blue trigger located on the side of the base.
- While holding the trigger, pull out the gray lever and turn the car seat towards the vehicle door.
- Place your child in the seat and secure the harness.
- Rotate the seat back to its rear-facing or forward-facing position until you hear a distinct "click." The turn-lock indicator on the side of the base should be green, confirming it is securely locked for travel.



Figure 2: Easy ins and outs with 360-degree rotation.

## Easy ins and outs

### 360-Degree Rotation

A simple, one-handed turn makes it easy to get your little one in and out, whether rear-facing or forward-facing.



Figure 3: Easy ins and outs with 360-degree rotation.

### 3.2 Harness Adjustment

The No-Rethread Simply Safe Adjust Harness System allows you to adjust the harness and headrest height simultaneously.

- To adjust the harness height, squeeze the handle at the top of the headrest and slide it up or down to the appropriate position. The harness straps should be at or just below your child's shoulders for rear-facing, and at or just above for forward-facing.
- To loosen the harness, press the harness release button located at the front of the seat and pull the shoulder straps forward.
- To tighten the harness, pull the harness adjustment strap until the harness is snug against your child's body. Ensure you cannot pinch any excess webbing at your child's shoulder.

### 3.3 Recline Positions

The car seat offers 4 recline positions to ensure comfort and proper installation angle.

- Pull the recline handle located on the front of the base to adjust the recline angle.
- Refer to the level indicator on the side of the base to ensure the correct recline position for rear-facing (blue zone) or forward-facing (red zone).

# Safe rides at every turn 4-65 lb



**Rear-Facing  
Harness**  
4-40 lb



**Forward-Facing  
Harness**  
26.5-65 lb

Figure 4: Two modes of use: Rear-Facing (4-40 lb) and Forward-Facing (26.5-65 lb).

## Grows with your child

### 2 Growing Stages

- 1 Rear-Facing Harness 4-40 lb
- 2 Forward-Facing Harness 26.5-65 lb



Figure 5: The car seat grows with your child, offering two stages of use.

## 4. MAINTENANCE AND CLEANING

---

Regular maintenance ensures the longevity and hygiene of your car seat.

- **Seat Pad:** The seat pad is machine washable on a delicate cycle with cold water. Do not use bleach. Tumble dry on low heat.
- **Harness Straps:** Wipe harness straps with a damp cloth. Do not machine wash or immerse in water, as this may weaken the straps.
- **Buckle:** Clean the buckle by placing it in a cup of warm water and gently agitating. Do not use soaps or detergents.
- **Plastic and Metal Parts:** Wipe plastic and metal parts with mild soap and cool water.
- **Cup Holders:** The two integrated cup holders are removable for easy cleaning.

## 5. TROUBLESHOOTING

---

If you encounter any issues with your Graco EasyTurn 360 car seat, please refer to the following common solutions or contact customer support.

- **Car Seat is Loose After Installation:** Ensure the SnugLock lock-off is fully closed and you have removed all slack from the vehicle seat belt or LATCH strap. Re-test for tightness; movement should not exceed 1 inch.
- **Harness is Difficult to Tighten/Loosen:** Check that the harness straps are not twisted. Ensure the harness release button is fully pressed when loosening.
- **Seat Not Rotating Smoothly:** Verify that there are no obstructions around the base of the seat. Ensure the blue trigger and gray lever are fully engaged during rotation.
- **Turn-Lock Indicator Not Green:** This indicates the seat is not securely locked in position for travel. Re-engage the rotation mechanism until a click is heard and the indicator turns green.

## 6. SPECIFICATIONS

---

Feature	Specification
Brand	Graco
Model	EasyTurn 360 2-in-1
Rear-Facing Harness Weight	4-40 Pounds
Forward-Facing Harness Weight	26.5-65 Pounds
Maximum Weight Recommendation	65 Pounds
Maximum Height Recommended	49 Inches
Installation Type	LATCH, Vehicle Seat Belt
Harness Type	5-Point
Number of Height Positions	10
Item Dimensions (D x W x H)	20.2"D x 17"W x 25.5"H
Item Weight	30.82 Pounds
Material Type	Polyester
UPC	047406191208

## 7. WARRANTY AND SUPPORT

---

Graco products are designed for quality and durability. For specific warranty information, please refer to the warranty card included with your product packaging or visit the official Graco website.

### Customer Support:

If you have questions, require assistance with installation, or need to report a safety concern, please contact Graco customer service:

- **Website:** [www.gracobaby.com](http://www.gracobaby.com)
- **Phone:** 1-800-345-4109 (for US customers)

Always register your car seat to receive important safety notices and recall information.