

[Manuals.plus](#) /

› [Kircuit](#) /

› Kircuit USB-C Charging Cable User Manual for AUTOONE Jump Starters

## Kircuit USB-C Charging Cable

# Kircuit USB-C Charging Cable User Manual

For AUTOONE JS01, JS02, JS-01, JS-02, DY-ATO, DYATO Car Battery Jump Starters

## 1. PRODUCT OVERVIEW

The Kircuit USB-C Charging Cable is designed to provide reliable power delivery for compatible devices, specifically AUTOONE Car Battery Jump Starters. This cable facilitates charging the jump starter's internal battery from a standard USB power source, ensuring your device is ready when needed. It features a USB-A connector on one end and a USB-C connector on the other, enabling broad compatibility with various charging adapters and ports.



**Image 1.1:** A black Kircuit USB-A to USB-C charging cable. The cable is coiled in a circular shape, with a standard USB-A connector visible on the left and a USB-C connector visible on the right. Both connectors are black with silver-colored metal tips.

## 2. SETUP

To prepare your AUTOONE Car Battery Jump Starter for charging using the Kircuit USB-C Charging Cable, follow these steps:

1. **Identify Ports:** Locate the USB-C charging input port on your AUTOONE jump starter and an available USB-A output port on a compatible power source (e.g., wall adapter, car charger, computer USB port). Ensure the power source provides 5V DC output.
2. **Connect USB-A:** Insert the standard USB-A end of the Kircuit charging cable into the USB-A output port of your power source.
3. **Connect USB-C:** Insert the USB-C end of the Kircuit charging cable into the USB-C input port of your AUTOONE jump starter.
4. **Verify Connection:** Ensure both ends of the cable are securely connected. The jump starter should indicate that it is receiving power, typically through an LED indicator or display.

### 3. OPERATING INSTRUCTIONS

Once the cable is connected as described in the Setup section, the AUTOONE jump starter will begin charging. The charging process is typically automatic.

- **Charging Indication:** Refer to your AUTOONE jump starter's specific user manual for details on its charging indicators (e.g., blinking lights, battery level display).
- **Charging Time:** Charging time will vary depending on the jump starter's battery capacity and the output current of your USB power source.
- **Disconnection:** Once the jump starter is fully charged, or if you need to stop charging, gently disconnect the USB-C end from the jump starter first, then the USB-A end from the power source. Avoid pulling the cable by the cord; always grasp the connector housing.

### 4. MAINTENANCE

Proper care of your Kircuit USB-C Charging Cable will ensure its longevity and reliable performance.

- **Storage:** Store the cable in a cool, dry place away from direct sunlight and extreme temperatures. Avoid tightly coiling or bending the cable sharply, which can damage internal wires.
- **Cleaning:** If the cable or connectors become dirty, gently wipe them with a soft, dry cloth. Do not use harsh chemicals or abrasive cleaners.
- **Inspection:** Periodically inspect the cable for any signs of wear, fraying, or damage to the connectors. Discontinue use if any damage is observed.
- **Handling:** Always grasp the connector housing when plugging or unplugging the cable. Avoid pulling on the cable itself, as this can strain the connections and lead to damage.

### 5. TROUBLESHOOTING

If you encounter issues while using your Kircuit USB-C Charging Cable, consider the following common solutions:

- **Device Not Charging:**
  - Ensure both ends of the cable are fully and securely inserted into their respective ports.
  - Verify that the power source (e.g., wall adapter) is functioning correctly and providing power. Try a different power source if available.
  - Check the USB-C port on your jump starter for any obstructions or damage.
  - Confirm that your AUTOONE jump starter is compatible with 5V USB charging.
- **Slow Charging:**
  - Ensure your power source provides sufficient current (amperage) for optimal charging. A low-power USB port may charge slower.
  - Avoid using excessively long extension cords or USB hubs, which can reduce power delivery.
- **Cable Damage:**
  - Inspect the cable for any visible signs of damage, such as cuts, fraying, or bent connectors. A damaged cable should be

replaced immediately to prevent potential hazards.

## 6. SPECIFICATIONS

|                      |                                                                           |
|----------------------|---------------------------------------------------------------------------|
| Brand                | Kircuit                                                                   |
| Connector Type       | USB-A to USB-C                                                            |
| Connector Gender     | Male-to-Male                                                              |
| Color                | Black                                                                     |
| Compatible Devices   | AUTOONE JS01, JS02, JS-01, JS-02, DY-ATO, DYATO Car Battery Jump Starters |
| Input/Output Voltage | 5V DC (Standard USB Power)                                                |

## 7. WARRANTY AND SUPPORT

For information regarding warranty coverage or technical support for your Kircuit USB-C Charging Cable, please refer to the documentation provided with your purchase or contact the retailer directly. Keep your proof of purchase for any warranty claims.

© 2024 Kircuit. All rights reserved.

### ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

**Submit question**